# FJM Lineup & Feature - Indoor Units

## Wall-mounted

| MODEL | | Y Series | P Series | P Plus Series | Crystal | Neo Forte |
|---|---|---|---|---|---|---|
| CAPACITY (kW) | | | ● | ● | ● | ● |
| | 2.6 | ● | ● | ● | ● | ● |
| | | ● | ● | ● | ● | ● |
| | 5.2 | ● | ● | ● | ● | ● |
| | 6.8 | | ● | ● | | |
| FEATURES | S-Plasma ion | ● | ● | ● | ● | |
| | Full HD Filter | ● | ● | ● | ● | |
| | DNA Filter | | | | | |
| | Deodorizing Filter | | | | ● | ● |
| | Catechin Filter | | | | ● | |
| | Smart Inverter | ● | ● | ● | ● | ● |
| | Smart Saver | | ● | ● | ● | |
| | d'light Cool | ● | | | ● | |
| | good'sleep | ● | ● | ● | ● | ● |
| | Wide Twin Blade | ● | | | | |
| | 3D Wind | ● | | | | |
| | Turbo Cooling | ● | ● | ● | ● | |

## Console

| MODEL | | Console |
|---|---|---|
| CAPACITY (kW) | | ● |
| | 3.5 | ● |
| | 5.2 | ● |
| FEATURES | S-Plasma ion | ● |
| | Interior Design | ● |
| | Anti-virus Filter | ● |
| | Lightweight Unit | ● |
| | Flexible Pipe Installation | ● |

# FJM Specification - Outdoor Units

## Free Joint Multi

- One Outdoor Unit, Multiple Indoor Units
- Universal Indoor Units
- Twin BLDC Compressor
- Sine Wave Controller
- Sound Insulator for the Compressor
- Easy Installation

| Model Name | | | | RJ040F2HXEB | RJ050F2HXEB | RJ052F3HXEA | RJ060F3HXEB |
|---|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | Heat Pump | Heat Pump | Heat Pump | Heat Pump |
| Performance | HP | | HP | 1.5 | 1.8 | | 2.0 |
| | Capacity (Nominal) | Cooling | kW | 4.0 | 5.0 | 5.2 | 5.9 |
| | | | Btu/h | 13,600 | 17,100 | 17,700 | 20,100 |
| | | Heating | kW | 4.4 | 5.7 | 6.3 | 6.3 |
| | | | Btu/h | 15,000 | 19,400 | 21,500 | 21,500 |
| Power | Power Input (Nominal) | Cooling | kW | 1.02 | 1.32 | 1.35 | 1.60 |
| | | Heating | | 0.99 | 1.35 | 1.40 | 1.40 |
| | Current Input (Nominal) | Cooling | A | 4.70 | 6.00 | 6.20 | 7.30 |
| | | Heating | | 4.50 | 6.20 | 6.40 | 6.40 |
| | Circuit Breaker (MCCB+ELB / ELCB) | | A | | 20 | | 20 |
| COP | Nominal Cooling | | - | 3.92 | 3.79 | 3.85 | 3.69 |
| | Nominal Heating | | - | 4.44 | 4.22 | 4.50 | 4.50 |
| Compressor | Type | | - | Inverter Twin Rotary | Inverter Twin Rotary | Inverter Twin Rotary | Inverter Twin Rotary |
| | Oil | Type | - | POE | POE | POE | POE |
| | | Initial Charge | cc | 650 | 650 | 650 | 650 |
| Fan | Type | | - | Propeller Fan / BLDC | Propeller Fan / BLDC | Propeller Fan / BLDC | Propeller Fan / BLDC |
| | Output | | W | 35 | 35 | 45 | 124 |
| | Number of Units | | EA | 1 | 1 | 1 | 1 |
| | Air Flow Rate | | CMM | 30.4 | 33.1 | 32.9 | 41.0 |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 x 2 | 6.35 x 2 | 6.35 x 3 | 6.35 x 3 |
| | | | Φ, inch | 1/4 x 2 | 1/4 x 2 | 1/4 x 3 | 1/4 x 3 |
| | Gas Pipe | | Φ, mm | 9.52 x 2 | 9.52 x 1 + 12.7 x 1 | 9.52 x 2 + 12.7 x 1 | 9.52 x 2 + 12.7 x 1 |
| | | | Φ, inch | 3/8 x 2 | 3/8 x 1 + 1/2 x 1 | 3/8 x 2 + 1/2 x 1 | 3/8 x 2 + 1/2 x 1 |
| | Installation Limitation | Total Piping Length | m | 30.0 | 30.0 | 50.0 | 50.0 |
| | | Max. Length (Outdoor to indoor) | m | 20.0 | 20.0 | 20.0 | 20.0 |
| | | Max. Height (Between indoors) | m | 7.5 | 7.5 | 7.5 | 7.5 |
| | | Max. Height (Between ID/OD) | m | 15.0 | 15.0 | 15.0 | 15.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A | R410A |
| | Factory Charging | | kg | 1.3 | 1.6 | 2.2 | 2.2 |
| Sound | Sound Pressure | | dB(A) | 47 | 48 | 48 | 48 |
| External Dimension | Net Weight | | kg | 37 | 40 | 49 | 56 |
| | Shipping Weight | | kg | 40 | 43 | 53 | 60 |
| | Net Dimensions (WxHxD) | | mm | 790 x 545 x 285 | 790 x 545 x 285 | 880 x 638 x 310 | 880 x 798 x 310 |
| | Shipping Dimensions (WxHxD) | | mm | 926 x 599 x 382 | 926 x 599 x 382 | 1,053 x 695 x 413 | 1,023 x 889 x 413 |
| Operating Temp. Range | Cooling | | °C | -5 ~ 46 | -5 ~ 46 | -5 ~ 46 | -5 ~ 46 |
| | Heating | | °C | -15 ~ 24 | -15 ~ 24 | -15 ~ 24 | -15 ~ 24 |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvem

# FJM Specification - Outdoor Units

## Free Joint Multi

- One Outdoor Unit, Multiple Indoor Units
- Universal Indoor Units
- Twin BLDC Compressor
- Sine Wave Controller
- Sound Insulator for the Compressor
- Easy Installation

| Model Name | | | | RJ070F4HXEA | RJ080F4HXEA | RJ100F5HXEA |
|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | | Heat Pump | Heat Pump |
| Performance | HP | | HP | 2.5 | | 3.5 |
| | Capacity (Nominal) | Cooling | kW | | 8.0 | 10.0 |
| | | | Btu/h | | 27,300 | 34,100 |
| | | Heating | | 3.6 | 9.3 | 12.0 |
| | | | Btu/h | | 31,700 | 40,900 |
| Power | Power Input (Nominal) | Cooling | kW | 1.90 | | 2.80 |
| | | Heating | | | 2.20 | 2.93 |
| | Current Input (Nominal) | Cooling | A | 8.70 | | 13.30 |
| | | Heating | | 9.20 | | 13.40 |
| | Circuit Breaker (MCCB+ELB / ELCB) | | A | | 30 | 40 |
| COP | Nominal Cooling | | - | | 3.48 | 3.45 |
| | Nominal Heating | | - | | 4.23 | 4.10 |
| Compressor | Type | | - | | Inverter Twin Rotary | Inverter Twin Rotary |
| | Oil | Type | - | | POE | POE |
| | | Initial Charge | cc | 700 | 700 | 1,200 |
| Fan | Type | | - | | Propeller Fan / BLDC | Propeller Fan / BLDC |
| | Output | | W | | 124 | 150 |
| | Number of Units | | EA | | 1 | 1 |
| | Air Flow Rate | | CMM | | 45.4 | 70.6 |
| Piping Connections | Liquid Pipe | | Φ, mm | | 6.35 x 4 | 6.35 x 5 |
| | | | Φ, inch | | 1/4 x 4 | 1/4 x 5 |
| | Gas Pipe | | Φ, mm | | 9.52 x 2 + 12.7 x 2 | 9.52 x 2 + 12.7 x 3 |
| | | | Φ, inch | | 3/8 x 2 + 1/2 x 2 | 3/8 x 2 + 1/2 x 3 |
| | Installation Limitation | Total Piping Length | m | | 70.0 | 80.0 |
| | | Max. Length (Outdoor to indoor) | m | | 25.0 | 25.0 |
| | | Max. Height (Between indoors) | m | | 7.5 | 7.5 |
| | | Max. Height (Between ID/OD) | m | | 15.0 | 15.0 |
| Refrigerant | Type | | - | | R410A | R410A |
| | Factory Charging | | kg | 2.8 | | 3.2 |
| Sound | Sound Pressure | | dB(A) | 49 | | 52 |
| External Dimension | Net Weight | | kg | | 65 | 74.5 |
| | Shipping Weight | | kg | | 70 | 80 |
| | Net Dimensions (WxHxD) | | mm | | 850 x 758 x 310 | 940 x 998 x 330 |
| | Shipping Dimensions (WxHxD) | | mm | | 1,023 x 869 x 413 | 995 x 1,096 x 426 |
| Operating Temp. Range | Cooling | | °C | | -5 ~ 46 | -10 ~ 46 |
| | Heating | | °C | | -15 ~ 24 | -15 ~ 24 |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvem

# FJM Specification - Indoor Units

NEW

## Mini 4Way Cassette S

- Compact and Light Unit
- S-Plasma ion (Optional)
- Motion Detect Sensor (Optional)
- No Overflowing Drain Water

| Model | | | | AJN016NDEHA/EU | AJN020NDEHA/EU | AJN026NDEHA/EU | AJN035NDEHA/EU | AJN052NDEHA/EU |
|---|---|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 1.6 | 2.0 | 2.6 | 3.5 | 5.2 |
| | | | Btu/h | 5,500 | 6,800 | 8,900 | 11,900 | 17,700 |
| | | Heating | kW | 2.0 | 2.2 | 2.9 | 3.8 | 5.6 |
| | | | Btu/h | 6,800 | 7,500 | 9,900 | 13,000 | 19,100 |
| Power | Power Input (Nominal) | Cooling | W | 19 | 19 | 19 | 22 | 28 |
| | | Heating | | 19 | 19 | 19 | 22 | 28 |
| | Current Input (Nominal) | Cooling | A | 0.51 | 0.51 | 0.51 | 0.52 | 0.53 |
| | | Heating | | 0.51 | 0.51 | 0.51 | 0.52 | 0.53 |
| Fan | Motor | Type | - | Turbo Fan / BLDC | Turbo Fan / BLDC | Turbo Fan / BLDC | Turbo Fan / BLDC | Turbo Fan / BLDC |
| | | Output | W | 65 | 65 | 65 | 65 | 65 |
| | Air Flow Rate | High / Mid / Low | CMM | 9.9 / 8.2 / 6.9 | 9.9 / 8.2 / 6.9 | 9.9 / 8.2 / 6.9 | 10.7 / 9.0 / 7.4 | 12.4 / 10.7 / 9.0 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - | - | - | - |
| | | | Pa | - | - | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 9.52 | 9.52 | 12.7 |
| | | | Φ, inch | 3/8 | 3/8 | 3/8 | 3/8 | 1/2 |
| | Drain Pipe | | Φ, mm | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 33 / 29 / 24 | 33 / 29 / 24 | 34 / 30 / 25 | 36 / 33 / 29 | 40 / 36 / 32 |
| Dimensions | Net Weight | | kg | 11.0 | 11.0 | 11.0 | 11.0 | 11.7 |
| | Shipping Weight | | kg | 13.0 | 13.0 | 13.0 | 13.0 | 13.7 |
| | Net Dimensions (W×H×D) | | mm | 575 x 250 x 575 | 575 x 250 x 575 | 575 x 250 x 575 | 575 x 250 x 575 | 575 x 250 x 575 |
| | Shipping Dimensions (W×H×D) | | mm | 623 x 298 x 653 | 623 x 298 x 653 | 623 x 298 x 653 | 623 x 298 x 653 | 623 x 298 x 653 |
| Panel Size | Panel Model | | - | PC4SUSMA | PC4SUSMA | PC4SUSMA | PC4SUSMA | PC4SUSMA |
| | Panel Net Weight | | kg | 2.7 | 2.7 | 2.7 | 2.7 | 2.7 |
| | Shipping Weight | | kg | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 |
| | Net Dimensions (W×H×D) | | mm | 670 x 45 x 670 | 670 x 45 x 670 | 670 x 45 x 670 | 670 x 45 x 670 | 670 x 45 x 670 |
| | Shipping Dimensions (W×H×D) | | mm | 714 x 106 x 724 | 714 x 106 x 724 | 714 x 106 x 724 | 714 x 106 x 724 | 714 x 106 x 724 |
| Additional Accessories | Drain Pump | Drain Pump | - | Built-in | Built-in | Built-in | Built-in | Built-in |
| | | Max. Lifting Height / Displacement | mm / liter/h | 750 / 24 | 750 / 24 | 750 / 24 | 750 / 24 | 750 / 24 |
| | Air Filter | | - | Long life filter | Long life filter | Long life filter | Long life filter | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

## Optional Accessories

**Individual Controllers**

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

**Panel**

PC4SUSMA

PC4SUSME

# FJM Specification - Indoor Units

## Mini 4Way Cassette

- Ideal Compact Size
- Fan Speed Adjustment
- Auto Surround Swing
- Self-diagnosis mode

High Lift-UP

| Model | | | | MH030FMEA | MH035FMEA | MH052FMEA |
|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 3.0 | 3.5 | 5.2 |
| | | | Btu/h | 10,200 | 11,900 | 17,700 |
| | | Heating | kW | 3.4 | 3.8 | 5.6 |
| | | | Btu/h | 11,600 | 13,000 | 19,100 |
| Power | Power Input (Nominal) | Cooling | W | 85 | 85 | 120 |
| | | Heating | | 85 | 85 | 120 |
| | Current Input (Nominal) | Cooling | A | 0.37 | 0.37 | 0.52 |
| | | Heating | | 0.37 | 0.37 | 0.52 |
| Fan | Motor | Type | - | Turbo Fan / SSR | Turbo Fan / SSR | Turbo Fan / SSR |
| | | Output | W | 80 | 80 | 80 |
| | Air Flow Rate | High / Mid / Low | CMM | 10.8 / 9.8 / 8.8 | 10.8 / 9.8 / 8.8 | 12.1 / 11.1 / 10.1 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - | - |
| | | | Pa | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 12.7 |
| | | | Φ, inch | 3/8 | 3/8 | 1/2 |
| | Drain Pipe | | Φ, mm | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 30 / 28 / 25 | 34 / 31 / 27 | 41 / 37 / 33 |
| Dimensions | Net Weight | | kg | 17 | 17 | 17 |
| | Shipping Weight | | kg | 20 | 20 | 20 |
| | Net Dimensions (W×H×D) | | mm | 575 x 260 x 575 | 575 x 260 x 575 | 575 x 260 x 575 |
| | Shipping Dimensions (W×H×D) | | mm | 660 x 310 x 635 | 660 x 310 x 635 | 660 x 310 x 635 |
| Panel Size | Panel Model | | - | PMSMA | PMSMA | PMSMA |
| | Panel Net Weight | | kg | 3.5 | 3.5 | 3.5 |
| | Shipping Weight | | kg | 6.2 | 6.2 | 6.2 |
| | Net Dimensions (W×H×D) | | mm | 670 x 35 x 670 | 670 x 35 x 670 | 670 x 35 x 670 |
| | Shipping Dimensions (W×H×D) | | mm | 717 x 93 x 717 | 717 x 93 x 717 | 717 x 93 x 717 |
| Additional Accessories | | Drain Pump | - | Built-in | Built-in | Built-in |
| | | Max. Lifting Height / Displacement | mm / liter/h | 750 / 24 | 750 / 24 | 750 / 24 |
| | Air Filter | | - | Long life filter | Long life filter | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

Panel

PMSMA

## Slim 1Way Cassette

- Slim and Compact Design
- Quiet Operation
- No Overflowing Drain Water

Wide Blade NO! Dust High Lift-UP

| Model | | | | MH026FSEA | MH035FSEA |
|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.6 | 3.5 |
| | | | Btu/h | 8,900 | 11,900 |
| | | Heating | kW | 2.9 | 3.8 |
| | | | Btu/h | 9,900 | 13,000 |
| Power | Power Input (Nominal) | Cooling | W | 45 | 50 |
| | | Heating | | 45 | 50 |
| | Current Input (Nominal) | Cooling | A | 0.23 | 0.25 |
| | | Heating | | 0.23 | 0.25 |
| Fan | Motor | Type | - | Crossflow Fan / SSR | Crossflow Fan / SSR |
| | | Output | W | 80 | - |
| | Air Flow Rate | High / Mid / Low | CMM | 6.2 / 5.2 / 4.2 | 7.6 / 6.6 / 5.6 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - |
| | | | Pa | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 |
| | | | Φ, inch | 3/8 | 3/8 |
| | Drain Pipe | | Φ, mm | VP20 (OD 25, ID 20) | VP20 (OD 25, ID 20) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 30 / 28 / 25 | 32 / 30 / 27 |
| Dimensions | Net Weight | | kg | 10.5 | 11 |
| | Shipping Weight | | kg | 13.5 | 14 |
| | Net Dimensions (W×H×D) | | mm | 970 x 135 x 410 | 970 x 135 x 410 |
| | Shipping Dimensions (W×H×D) | | mm | 1,164 x 212 x 478 | 1,164 x 212 x 478 |
| Panel Size | Panel Model | | - | PSSMA / PC1NUPMA | PSSMA / PC1NUPMA |
| | Panel Net Weight | | kg | 3.0 | 3.0 |
| | Shipping Weight | | kg | 5.0 | 5.0 |
| | Net Dimensions (W×H×D) | | mm | 1.180 x 25 x 460 | 1.180 x 25 x 460 |
| | Shipping Dimensions (W×H×D) | | mm | 1.259 x 144 x 539 | 1.259 x 144 x 539 |
| Additional Accessories | | Drain Pump | - | Built-in | Built-in |
| | | Max. Lifting Height / Displacement | mm / liter/h | 750 / 24 | 750 / 24 |
| | Air Filter | | - | Long life filter | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

Panel

PSSMA

# FJM Specification - Indoor Units

## MSP Duct

- Narrow Width
- Strong and Large Coverage Area
- Silent Operation with the Static Pressure Control
- Easy to Maintain

| Model | | | | MH052FUEA |
|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 |
| Mode | | | - | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 5.2 |
| | | | Btu/h | 17,700 |
| | | Heating | kW | 6.0 |
| | | | Btu/h | 20,500 |
| Power | Power Input (Nominal) | Cooling | W | 170 |
| | | Heating | | 170 |
| | Current Input (Nominal) | Cooling | A | 1.04 |
| | | Heating | | 1.04 |
| Fan | Motor | Type | - | Sirroco Fan / SSR |
| | | Output | W | 124 |
| | Air Flow Rate | High / Mid / Low | CMM | 16.3 / 15.0 / 13.5 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | 0 / 4 / 8 |
| | | | Pa | 0 / 39.2 / 78.5 |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 |
| | | | Φ, inch | 1/4 |
| | Gas Pipe | | Φ, mm | 12.7 |
| | | | Φ, inch | 1/2 |
| | Drain Pipe | | Φ, mm | VP25 (OD 32, ID 25) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A |
| | Control Method | | - | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 37 / 35 / 33 |
| Dimensions | Net Weight | | kg | 29 |
| | Shipping Weight | | kg | 34 |
| | Net Dimensions (WxHxD) | | mm | 900 x 260 x 480 |
| | Shipping Dimensions (WxHxD) | | mm | 1,146 x 345 x 584 |
| Panel Size | Panel Model | | - | - |
| | Panel Net Weight | | kg | - |
| | | | | |
| | Net Dimensions (WxHxD) | | mm | - |
| | Shipping Dimensions (WxHxD) | | mm | - |
| Additional Accessories | Drain Pump | Drain Pump | - | Optional / MDP-M075SGU3 |
| | | Max. Lifting Height / Displacement | mm / liter/h | 750 / 24 |
| | Air Filter | | - | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10 MWR-WH0* MWR-SH00 MR-DH00 MRK-A00 MRW-10A

Drain Pump

MDP-M075SGU3

### Standard Accessories

Individual Controllers

## Slim Duct

- Flexible Installation
- Easier Drain Pump Installation
- Slim Design
- Easy to Maintain

| Model | | | | NJ026LHXEA | NJ035LHXEA |
|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.6 | 3.5 |
| | | | Btu/h | 8,900 | 11,900 |
| | | Heating | kW | 2.9 | 3.8 |
| | | | Btu/h | 9,900 | 13,000 |
| Power | Power Input (Nominal) | Cooling | W | 80 | 80 |
| | | Heating | | 80 | 80 |
| | Current Input (Nominal) | Cooling | A | 0.40 | 0.40 |
| | | Heating | | 0.40 | 0.40 |
| Fan | Motor | Type | - | Sirroco Fan / SSR | Sirroco Fan / SSR |
| | | Output | W | - | - |
| | Air Flow Rate | High / Mid / Low | CMM | 8.6 / 7.6 / 6.6 | 9.8 / 8.8 / 7.8 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | 0 / 2 / 4 | 0 / 2 / 4 |
| | | | Pa | 0 / 19.6 / 39.2 | 0 / 19.6 / 39.2 |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 |
| | | | Φ, inch | 3/8 | 3/8 |
| | Drain Pipe | | Φ, mm | VP25 (OD 32, ID 25) | VP25 (OD 32, ID 25) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 30 / 28 / 25 | 32 / 30 / 27 |
| Dimensions | Net Weight | | kg | 26 | 26 |
| | Shipping Weight | | kg | 31 | 31 |
| | Net Dimensions (WxHxD) | | mm | 900 x 199 x 600 | 900 x 199 x 600 |
| | Shipping Dimensions (WxHxD) | | mm | 1,133 x 330 x 730 | 1,133 x 330 x 730 |
| Panel Size | Panel Model | | - | - | - |
| | Panel Net Weight | | kg | - | - |
| | Shipping Weight | | kg | - | - |
| | Net Dimensions (WxHxD) | | mm | - | - |
| | Shipping Dimensions (WxHxD) | | mm | - | - |
| Additional Accessories | | Drain Pump | - | Optional / MDP-E075SEE3 | Optional / MDP-E075SEE3 |
| | | Max. Lifting Height / Displacement | mm / liter/h | 750 / 24 | 750 / 24 |
| | Air Filter | | - | Long life filter | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10 MWR-WH0* MWR-SH00 MR-DH00 MRK-A00

Drain Pump

MDP-E075SEE3

### Standard Accessories

Individual Controllers

# FJM Specification - Indoor Units

## Y Series (Jungfrau Premium)

- S-Plasma ion
- Smart Inverter
- good' sleep
- Wide Twin Blade
- Full HD Filter
- d'light cool
- 3D Wind
- Turbo Cooling

| Model | | | | AQV12YWAN | AQV18YWAN |
|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.5 | 5.0 |
| | | | Btu/h | 8,500 | 17,100 |
| | | Heating | kW | 3.2 | 5.0 |
| | | | Btu/h | 10,900 | 13,600 | 20,500 |
| Power | Power Input (Nominal) | Cooling | W | 30 | 50 |
| | | Heating | | 30 | 50 |
| | Current Input (Nominal) | Cooling | A | 0.18 | 0.25 |
| | | Heating | | 0.18 | 0.25 |
| Fan | Motor | Type | - | Crossflow Fan / BLDC | Crossflow Fan / BLDC |
| | | Output | W | - | - |
| | Air Flow Rate | High / Mid / Low | CMM | 11.6 / 10.3 / 9.0 | 13.8 / 11.4 / 9.0 | 14.5 / 12.8 / 11.0 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - |
| | | | Pa | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 12.7 |
| | | | Φ, inch | 3/8 | 3/8 | 1/2 |
| | Drain Pipe | | Φ, mm | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 39 / 30 / 21 | 41 / 31 / 21 | 43 / 35 / 26 |
| Dimensions | Net Weight | | kg | 10.5 | 10.5 | 11.2 |
| | Shipping Weight | | kg | 13.0 | 13.0 | 13.8 |
| | Net Dimensions (W×H×D) | | mm | 880 x 313 x 237 | 880 x 313 x 237 |
| | Shipping Dimensions (W×H×D) | | mm | 954 x 381 x 317 | 954 x 381 x 317 |
| Panel Size | Panel Model | | - | - |
| | Panel Net Weight | | kg | - |
| | Shipping Weight | | kg | - |
| | Net Dimensions (W×H×D) | | mm | - |
| | Shipping Dimensions (W×H×D) | | mm | - |
| Additional Accessories | Drain Pump | Drain Pump | - | - |
| | | Max. Lifting Height / Displacement | mm / liter/h | - |
| | Air Filter | | - | Full HD Filter 90 | Full HD Filter 90 |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

MIM-A00

### Standard Accessories

Wireless Remote Controller

# FJM Specification - Indoor Units

## P Series (Maldives)

- Full HD Filter
- Smart Saver
- Turbo Cooling
- Triple Protector (Optional)
- Smart Inverter
- good' sleep
- Quiet Mode
- S-Plasma ion

| Model | | | | AQV07PSBN | AQV09PSBN | AQV12PSBN | AQV18PSBN | AQV24PSBN |
|---|---|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.0 | 2.5 | 3.5 | 5.0 | 6.8 |
| | | | Btu/h | 6,800 | 8,500 | 11,900 | 17,100 | 23,200 |
| | | Heating | kW | 2.2 | 3.3 | 4.0 | 6.0 | 7.8 |
| | | | Btu/h | 7,500 | 11,300 | 13,600 | 20,500 | 26,600 |
| Power | Power Input (Nominal) | Cooling | W | 30 | 35 | 40 | 35 | 53 |
| | | Heating | | 30 | 35 | 40 | 35 | 53 |
| | Current Input (Nominal) | Cooling | A | 0.18 | 0.19 | 0.20 | 0.30 | 0.46 |
| | | Heating | | 0.18 | 0.19 | 0.20 | 0.30 | 0.46 |
| Fan | Motor | Type | - | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / BLDC | Crossflow Fan / BLDC |
| | | Output | W | 23 | 23 | 23 | 27 | 27 |
| | Air Flow Rate | High / Mid / Low | CMM | 7.9 / 7.0 / 6.1 | 9.4 / 8.7 / 7.9 | 10.1 / 9.0 / 7.9 | 14.2 / 12.3 / 11.2 | 17.8 / 14.3 / 10.6 |
| | External Static Pressure | Min. / Std. / Max | mmAq | - | - | - | - | - |
| | | | Pa | - | - | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 9.52 | 12.7 | 15.88 |
| | | | Φ, inch | 3/8 | 3/8 | 3/8 | 1/2 | 5/8 |
| | Drain Pipe | | Φ, mm | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 36 / 29 / 21 | 36 / 29 / 21 | 38 / 30 / 21 | 40 / 35 / 30 | 41 / 36 / 30 |
| Dimensions | Net Weight | | kg | 9 | 9 | 9 | 13 | 13 |
| | Shipping Weight | | kg | 11 | 11 | 11 | 16 | 16 |
| | Net Dimensions (WxHxD) | | mm | 820 x 286 x 205 | 820 x 286 x 205 | 820 x 286 x 205 | 1,065 x 230 x 298 | 1,065 x 230 x 298 |
| | Shipping Dimensions (WxHxD) | | mm | 892 x 355 x 263 | 892 x 355 x 263 | 892 x 355 x 263 | 1,137 x 377 x 299 | 1,137 x 377 x 299 |
| Panel Size | Panel Model | | - | - | - | - | - | - |
| | Panel Net Weight | | kg | - | - | - | - | - |
| | Shipping Weight | | kg | - | - | - | - | - |
| | Net Dimensions (WxHxD) | | mm | - | - | - | - | - |
| | Shipping Dimensions (WxHxD) | | mm | - | - | - | - | - |
| Additional Accessories | | Drain Pump | - | - | - | - | - | - |
| | | Max. Lifting Height / Displacement | mm / liter/h | - | - | - | - | - |
| | Air Filter | | - | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

MIM-A00

### Standard Accessories

Wireless Remote Controller

# FJM Specification - Indoor Units

## P Plus Series

- Full HD Filter
- Smart Saver
- Turbo Cooling
- Triple Protector (Optional)
- Smart Inverter
- good' sleep
- Quiet Mode
- S-Plasma ion

| Model | | | | AQV07PMEN | AQV09PMEN | AQV12PMEN | AQV18PMBN | AQV24PMBN |
|---|---|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.0 | 2.5 | 3.5 | 5.0 | 6.8 |
| | | | Btu/h | 6,800 | 8,500 | 11,900 | 17,100 | 23,200 |
| | | Heating | kW | 2.2 | 3.3 | 4.0 | 6.0 | 7.8 |
| | | | Btu/h | 7,500 | 11,300 | 13,600 | 20,500 | 26,600 |
| Power | Power Input (Nominal) | Cooling | W | 30 | 50 | 50 | 40 | 60 |
| | | Heating | | 30 | 50 | 50 | 40 | 60 |
| | Current Input (Nominal) | Cooling | A | 0.18 | 0.4 | 0.4 | 0.3 | 0.45 |
| | | Heating | | 0.18 | 0.4 | 0.4 | 0.3 | 0.45 |
| Fan | Motor | Type | - | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / BLDC | Crossflow Fan / BLDC |
| | | Output | W | 23 | 23 | 23 | 27 | 27 |
| | Air Flow Rate | High / Mid / Low | CMM | 7.9 / 7.0 / 6.1 | 9.4 / 8.7 / 7.9 | 10.1 / 9.0 / 7.9 | 14.2 / 12.3 / 11.2 | 17.8 / 14.3 / 10.6 |
| | External Static Pressure | Min. / Std. / Max | mmAq | - | - | - | - | - |
| | | | Pa | - | - | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 9.52 | 12.7 | 15.88 |
| | | | Φ, inch | 3/8 | 3/8 | 3/8 | 1/2 | 5/8 |
| | Drain Pipe | | Φ, mm | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 36 / 29 / 21 | 36 / 29 / 21 | 38 / 30 / 21 | 40 / 35 / 30 | 41 / 36 / 30 |
| Dimensions | Net Weight | | kg | 9 | 9 | 9 | 13 | 13 |
| | Shipping Weight | | kg | 11 | 11 | 11 | 16 | 16 |
| | Net Dimensions (WxHxD) | | mm | 820 x 286 x 205 | 820 x 286 x 205 | 820 x 286 x 205 | 1,065 x 230 x 298 | 1,065 x 230 x 298 |
| | Shipping Dimensions (WxHxD) | | mm | 892 x 355 x 263 | 892 x 355 x 263 | 892 x 355 x 263 | 1,137 x 377 x 299 | 1,137 x 377 x 299 |
| Panel Size | Panel Model | | - | - | - | - | - | - |
| | Panel Net Weight | | kg | - | - | - | - | - |
| | Shipping Weight | | kg | - | - | - | - | - |
| | Net Dimensions (WxHxD) | | mm | - | - | - | - | - |
| | Shipping Dimensions (WxHxD) | | mm | - | - | - | - | - |
| Additional Accessories | | Drain Pump | - | - | - | - | - | - |
| | | Max. Lifting Height / Displacement | mm / liter/h | - | - | - | - | - |
| | Air Filter | | - | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

MIM-A00

### Standard Accessories

Wireless Remote Controller

# FJM Specification - Indoor Units

## Crystal

- S-Plasma ion
- Catechin Filter
- good'sleep
- Filter Cleaning Indicator
- Full HD Filter
- Smart Inverter
- Turbo Cooling
- Deodorizing Filter
- Smart Saver

| Model | | | | MH020FAEA | MH026FAEA | MH035FAEA | MH052FAEA |
|---|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.0 | 2.6 | 3.5 | 5.2 |
| | | | Btu/h | 6,800 | 8,900 | 11,900 | 17,700 |
| | | Heating | kW | 2.2 | 2.9 | 3.8 | 5.6 |
| | | | Btu/h | 7,500 | 9,900 | 13,000 | 19,100 |
| Power | Power Input (Nominal) | Cooling | W | 30 | 30 | 35 | 50 |
| | | Heating | | 30 | 30 | 35 | 50 |
| | Current Input (Nominal) | Cooling | A | 0.18 | 0.18 | 0.19 | 0.30 |
| | | Heating | | 0.18 | 0.18 | 0.19 | 0.30 |
| Fan | Motor | Type | - | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / SSR |
| | | Output | W | 23 | 23 | 23 | 40 |
| | Air Flow Rate | High / Mid / Low | CMM | 7.9 / 6.9 / 5.9 | 9.1 / 8.1 / 7.1 | 9.8 / 8.8 / 7.8 | 14.2 / 12.5 / 10.7 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - | - | - |
| | | | Pa | - | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 9.52 | 12.7 |
| | | | Φ, inch | 3/8 | 3/8 | 3/8 | 1/2 |
| | Drain Pipe | | Φ, mm | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 31 / 26 / 21 | 31 / 26 / 21 | 35 / 28 / 21 | 40 / 35 / 30 |
| Dimensions | Net Weight | | kg | 9 | 9 | 9 | 13 |
| | Shipping Weight | | kg | 11 | 11 | 11 | 16 |
| | Net Dimensions (W×H×D) | | mm | 820 x 286 x 190 | 820 x 286 x 190 | 820 x 286 x 190 | 1,099 x 315 x 217 |
| | Shipping Dimensions (W×H×D) | | mm | 892 x 355 x 263 | 892 x 355 x 263 | 892 x 355 x 263 | 1,137 x 377 x 299 |
| Panel Size | Panel Model | | - | - | - | - | - |
| | Panel Net Weight | | kg | - | - | - | - |
| | Shipping Weight | | kg | - | - | - | - |
| | Net Dimensions (W×H×D) | | mm | - | - | - | - |
| | Shipping Dimensions (W×H×D) | | mm | - | - | - | - |
| Additional Accessories | Drain Pump | Drain Pump | - | - | - | - | - |
| | | Max. Lifting Height / Displacement | mm / liter/h | - | - | - | - |
| | Air Filter | | - | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 | Full HD Filter 80 |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

### Standard Accessories

Wireless Remote Controller

# FJM Specification - Indoor Units

## Neo Forte

- Clean-cut Front Panel
- Silver Accent Line
- Bottom Opening Front Panel

| Model | | | | MH020FNEA | MH026FNEA | MH035FNEA | MH052FNEA |
|---|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.0 | 2.6 | 3.5 | 5.2 |
| | | | Btu/h | 6,800 | 8,900 | 11,900 | 17,700 |
| | | Heating | kW | 2.2 | 2.9 | 3.8 | 5.6 |
| | | | Btu/h | 7,500 | 9,900 | 13,000 | 19,100 |
| Power | Power Input (Nominal) | Cooling | W | 30 | 30 | 35 | 50 |
| | | Heating | | 30 | 30 | 35 | 50 |
| | Current Input (Nominal) | Cooling | A | 0.18 | 0.18 | 0.19 | 0.30 |
| | | Heating | | 0.18 | 0.18 | 0.19 | 0.30 |
| Fan | Motor | Type | - | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / SSR | Crossflow Fan / SSR |
| | | Output | W | 23 | 23 | 23 | 40 |
| | Air Flow Rate | High / Mid / Low | CMM | 7.7 / 6.7 / 5.7 | 8.3 / 7.3 / 6.3 | 9.5 / 8.5 / 7.5 | 13.2 / 11.6 / 9.9 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - | - | - |
| | | | Pa | - | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 9.52 | 12.7 |
| | | | Φ, inch | 3/8 | 3/8 | 3/8 | 1/2 |
| | Drain Pipe | | Φ, mm | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 32 / 28 / 23 | 32 / 28 / 23 | 36 / 30 / 23 | 40 / 35 / 30 |
| Dimensions | Net Weight | | kg | 7.8 | 7.8 | 7.8 | 13 |
| | Shipping Weight | | kg | 9.4 | 9.4 | 9.4 | 16 |
| | Net Dimensions (WxHxD) | | mm | 825 x 285 x 189 | 825 x 285 x 189 | 825 x 285 x 189 | 1,099 x 315 x 217 |
| | Shipping Dimensions (WxHxD) | | mm | 900 x 349 x 252 | 900 x 349 x 252 | 900 x 349 x 252 | 1,137 x 377 x 299 |
| Panel Size | Panel Model | | - | - | - | - | - |
| | Panel Net Weight | | kg | - | - | - | - |
| | Shipping Weight | | kg | - | - | - | - |
| | Net Dimensions (WxHxD) | | mm | - | - | - | - |
| | Shipping Dimensions (WxHxD) | | mm | - | - | - | - |
| Additional Accessories | | Drain Pump | - | - | - | - | - |
| | | Max. Lifting Height / Displacement | mm / liter/h | - | - | - | - |
| | Air Filter | | - | Long life filter | Long life filter | Long life filter | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

MWR-WE10

MWR-WH0*

MWR-SH00

MR-DH00

### Standard Accessories

Wireless Remote Controller

## Console

- Slim & Smart Design
- 2Way Outlets
- Silent Operation

| Model | | | | MH026FJEA | MH035FJEA | MH052FJEA |
|---|---|---|---|---|---|---|
| Power Supply | | | Φ, #, V, Hz | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 | 1, 2, 220~240, 50 |
| Mode | | | - | HP | HP | HP |
| Performance | Capacity (Nominal) | Cooling | kW | 2.6 | 3.5 | 5.2 |
| | | | Btu/h | 8,900 | 11,900 | 17,700 |
| | | Heating | kW | 2.9 | 3.8 | 5.6 |
| | | | Btu/h | 9,900 | 13,000 | 19,100 |
| Power | Power Input (Nominal) | Cooling | W | 30 | 35 | 50 |
| | | Heating | | 30 | 35 | 50 |
| | Current Input (Nominal) | Cooling | A | 0.25 | 0.29 | 0.35 |
| | | Heating | | 0.25 | 0.29 | 0.35 |
| Fan | Motor | Type | - | Turbo Fan / BLDC | Turbo Fan / BLDC | Turbo Fan / BLDC |
| | | Output | W | 37 | 37 | 37 |
| | Air Flow Rate | High / Mid / Low | CMM | 9 / 7.8 / 6.7 | 10.5 / 9.3 / 8.2 | 11.2 / 9.9 / 8.6 |
| | External Static Pressure | Min. / Std. / Max. | mmAq | - | - | - |
| | | | Pa | - | - | - |
| Piping Connections | Liquid Pipe | | Φ, mm | 6.35 | 6.35 | 6.35 |
| | | | Φ, inch | 1/4 | 1/4 | 1/4 |
| | Gas Pipe | | Φ, mm | 9.52 | 9.52 | 12.7 |
| | | | Φ, inch | 3/8 | 3/8 | 1/2 |
| | Drain Pipe | | Φ, mm | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) | VP18 (OD 19, ID 16) |
| Field Wiring | Power Source Wire | | $mm^2$ | 1.0 | 1.0 | 1.0 |
| | Transmission Cable | | $mm^2$ | 0.75 ~ 1.0 | 0.75 ~ 1.0 | 0.75 ~ 1.0 |
| Refrigerant | Type | | - | R410A | R410A | R410A |
| | Control Method | | - | EEV (External) | EEV (External) | EEV (External) |
| Sound | Sound Pressure | High / Mid / Low | dBA | 28 / 26 / 23 | 39 / 32 / 24 | 44 / 34 / 25 |
| Dimensions | Net Weight | | kg | 15 | 15 | 15 |
| | Shipping Weight | | kg | 19 | 19 | 19 |
| | Net Dimensions (WxHxD) | | mm | 720 x 620 x 199 | 720 x 620 x 199 | 720 x 620 x 199 |
| | Shipping Dimensions (WxHxD) | | mm | 810 x 710 x 295 | 810 x 710 x 295 | 810 x 710 x 295 |
| Panel Size | Panel Model | | - | - | - | - |
| | Panel Net Weight | | kg | - | - | - |
| | Shipping Weight | | kg | - | - | - |
| | Net Dimensions (WxHxD) | | mm | - | - | - |
| | Shipping Dimensions (WxHxD) | | mm | - | - | - |
| Additional Accessories | | Drain Pump | - | - | - | - |
| | | Max. Lifting Height / Displacement | mm / liter/h | - | - | - |
| | Air Filter | | - | Long life filter | Long life filter | Long life filter |

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

### Optional Accessories

Individual Controllers

### Standard Accessories

Wireless Remote Controller

5.2kW

# FJM Capacity Combination

## RJ040F2HXEB

### Neo Forte & Crystal

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2600 | - | - | - | 65% | 2600 | 2600 | - | - | - | 2600 | 1250 | 2600 | 3120 | 300 | 750 | 880 | 1.7 | 3.4 | 4.0 | 3.47 | A |
| | 3500 | - | - | - | 88% | 3500 | 3500 | - | - | - | 3500 | 1250 | 3500 | 4200 | 300 | 1060 | 1240 | 1.7 | 4.9 | 5.7 | 3.30 | A |
| 2 Unit | 2000 | 2000 | - | - | 100% | 4000 | 2000 | 2000 | - | - | 4000 | 1250 | 4000 | 4500 | 300 | 1180 | 1330 | 1.7 | 5.4 | 6.1 | 3.39 | A |
| | 2000 | 2600 | - | - | 115% | 4600 | 1740 | 2260 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2000 | 3500 | - | - | 138% | 5500 | 1450 | 2550 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2600 | 2600 | - | - | 130% | 5200 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2600 | 3500 | - | - | 153% | 6100 | 1700 | 2300 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1110 | 1330 | 1.9 | 5.1 | 6.1 | 3.60 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2600, 3500W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 6.1 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 50% | 2200 | 2400 | - | - | - | 2400 | 1000 | 2400 | 2990 | 260 | 780 | 910 | 1.3 | 3.6 | 4.2 | 3.08 | D |
| | 3800 | - | - | - | 95% | 3800 | 3800 | - | - | - | 3800 | 1000 | 3800 | 4370 | 260 | 1100 | 1280 | 1.3 | 5.0 | 6.3 | 3.45 | B |
| 2 Unit | 2200 | 2200 | - | - | 100% | 4400 | 2200 | 2200 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1390 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 2200 | 2900 | - | - | 116% | 5100 | 1900 | 2500 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 2200 | 3800 | - | - | 136% | 6000 | 1610 | 2790 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 2900 | 2900 | - | - | 132% | 5800 | 2200 | 2200 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 2900 | 3800 | - | - | 152% | 6700 | 1900 | 2500 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1020 | 1400 | 1.4 | 4.7 | 6.4 | 4.31 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 6.7 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Maldives P Series & Deluxe

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 50% | 2000 | 2100 | - | - | - | 2100 | 1250 | 2100 | 2520 | 300 | 540 | 630 | 1.7 | 2.5 | 2.9 | 3.89 | A |
| | 2500 | - | - | - | 63% | 2500 | 2500 | - | - | - | 2500 | 1250 | 2500 | 3120 | 300 | 750 | 880 | 1.7 | 3.4 | 4.0 | 3.33 | A |
| | 3500 | - | - | - | 88% | 3500 | 3500 | - | - | - | 3500 | 1250 | 3500 | 4200 | 300 | 1060 | 1240 | 1.7 | 4.9 | 5.7 | 3.30 | A |
| 2 Unit | 2000 | 2000 | - | - | 100% | 4000 | 2000 | 2000 | - | - | 4000 | 1250 | 4000 | 4500 | 300 | 1180 | 1330 | 1.7 | 5.4 | 6.1 | 3.39 | A |
| | 2000 | 2500 | - | - | 113% | 4500 | 1780 | 2220 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2000 | 3500 | - | - | 138% | 5500 | 1450 | 2550 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2500 | 2500 | - | - | 125% | 5000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2500 | 3500 | - | MAX | 150% | 6000 | 1670 | 2330 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1020 | 1330 | 1.9 | 4.7 | 6.1 | 3.92 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 6.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 3300 | - | - | - | 75% | 3300 | 3100 | - | - | - | 3100 | 1000 | 3100 | 3450 | 260 | 850 | 1050 | 1.3 | 3.9 | 4.9 | 3.65 | A |
| | 4000 | - | - | - | 91% | 4000 | 3800 | - | - | - | 3800 | 1000 | 3800 | 4370 | 260 | 1100 | 1380 | 1.3 | 5.0 | 6.3 | 3.45 | B |
| 2 Unit | 2200 | 2200 | - | - | 100% | 4400 | 2200 | 2200 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1390 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 2200 | 3300 | - | - | 125% | 5500 | 1760 | 2640 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 2200 | 4000 | - | - | 141% | 6200 | 1560 | 2840 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 3300 | 3300 | - | - | 150% | 6600 | 2200 | 2200 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 3300 | 4000 | - | - | 166% | 7300 | 1990 | 2410 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 990 | 1400 | 1.4 | 4.5 | 6.4 | 4.44 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 7.3 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Jungfrau Y-series

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2500 | - | - | - | 63% | 2500 | 2500 | - | - | - | 2500 | 1250 | 2500 | 3120 | 300 | 750 | 880 | 1.7 | 3.4 | 4.0 | 3.33 | A |
| | 3500 | - | - | - | 88% | 3500 | 3500 | - | - | - | 3500 | 1250 | 3500 | 4200 | 300 | 1060 | 1240 | 1.7 | 4.9 | 5.7 | 3.30 | A |
| 2 Unit | 2500 | 2500 | - | - | 125% | 5000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1180 | 1330 | 1.9 | 5.4 | 6.1 | 3.39 | A |
| | 2500 | 3500 | - | - | 150% | 6000 | 1670 | 2330 | - | - | 4000 | 1300 | 4000 | 4500 | 350 | 1020 | 1330 | 1.9 | 4.7 | 6.1 | 3.92 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2500, 3500W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 6.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 3200 | - | - | - | 73% | 3200 | 3100 | - | - | - | 3100 | 1000 | 3100 | 3450 | 260 | 850 | 1080 | 1.3 | 3.9 | 4.9 | 3.65 | A |
| | 4000 | - | - | - | 91% | 4000 | 3800 | - | - | - | 3800 | 1000 | 3800 | 4370 | 260 | 1100 | 1380 | 1.3 | 5.0 | 6.3 | 3.45 | B |
| 2 Unit | 3200 | 3200 | - | - | 145% | 6400 | 2200 | 2200 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 1160 | 1400 | 1.4 | 5.3 | 6.4 | 3.79 | A |
| | 3200 | 4000 | - | - | 164% | 7200 | 1960 | 2440 | - | - | 4400 | 1000 | 4400 | 4700 | 280 | 990 | 1400 | 1.4 | 4.5 | 6.4 | 4.44 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 3200, 4000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 7.2 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ050F2HXEB

### Neo Forte & Crystal

#### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2600 | - | - | - | 52% | 2600 | 2600 | - | - | - | 2600 | 1250 | 2600 | 3120 | 300 | 800 | 960 | 1.7 | 3.7 | 4.4 | 3.25 | A |
| | 5200 | - | - | - | 104% | 5200 | 5000 | - | - | - | 5000 | 1250 | 5000 | 5200 | 300 | 1600 | 1740 | 1.7 | 7.3 | 8.0 | 3.13 | B |
| 2 Unit | 2000 | 2000 | - | - | 80% | 4000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4800 | 350 | 1245 | 1490 | 1.9 | 5.7 | 6.8 | 3.21 | A |
| | 2000 | 2600 | - | - | 92% | 4600 | 2000 | 2600 | - | - | 4600 | 1300 | 4600 | 5200 | 350 | 1430 | 1720 | 1.9 | 6.5 | 7.9 | 3.22 | A |
| | 2000 | 3500 | - | - | 110% | 5500 | 1820 | 3180 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1490 | 1780 | 1.9 | 6.8 | 8.1 | 3.36 | A |
| | 2000 | 5200 | - | - | 144% | 7200 | 1390 | 3610 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1450 | 1800 | 1.9 | 6.6 | 8.2 | 3.45 | A |
| | 2600 | 2600 | - | - | 104% | 5200 | 2500 | 2500 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 2600 | 3500 | - | - | 122% | 6100 | 2130 | 2870 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 2600 | 5200 | - | - | 156% | 7800 | 1670 | 3330 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1450 | 1700 | 1.9 | 6.6 | 7.8 | 3.45 | A |
| | 3500 | 3500 | - | - | 140% | 7000 | 2500 | 2500 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 3500 | 5200 | - | - | 174% | 8700 | 2010 | 2990 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1425 | 1700 | 1.9 | 6.5 | 7.8 | 3.51 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2600, 3500, 5200W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.7 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

#### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 39% | 2200 | 2500 | - | - | - | 2500 | 1050 | 2500 | 2990 | 260 | 880 | 1010 | 1.3 | 4.0 | 4.6 | 2.84 | D |
| | 3800 | - | - | - | 67% | 3800 | 3800 | - | - | - | 3800 | 1050 | 3800 | 4470 | 280 | 1200 | 1620 | 1.3 | 5.5 | 7.4 | 3.17 | D |
| | 5600 | - | - | - | 98% | 5600 | 5400 | - | - | - | 5400 | 1050 | 5400 | 5600 | 260 | 1650 | 2060 | 1.3 | 7.6 | 9.4 | 3.27 | C |
| 2 Unit | 2200 | 2200 | - | - | 77% | 4400 | 2200 | 2200 | - | - | 4400 | 1100 | 4400 | 4750 | 280 | 1220 | 1390 | 1.4 | 5.6 | 6.4 | 3.61 | A |
| | 2200 | 2900 | - | - | 89% | 5100 | 2200 | 2900 | - | - | 5100 | 1100 | 5100 | 5460 | 280 | 1410 | 1610 | 1.4 | 6.5 | 7.4 | 3.62 | A |
| | 2200 | 3800 | - | - | 105% | 6000 | 2090 | 3610 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1520 | 1900 | 1.4 | 7.0 | 8.7 | 3.75 | A |
| | 2200 | 5600 | - | - | 137% | 7800 | 1610 | 4090 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1440 | 1800 | 1.4 | 6.6 | 8.2 | 3.96 | A |
| | 2900 | 2900 | - | - | 102% | 5800 | 2850 | 2850 | - | - | 5700 | 1100 | 5700 | 6300 | 208 | 1550 | 1940 | 1.4 | 7.1 | 8.9 | 3.68 | A |
| | 2900 | 3800 | - | - | 118% | 6700 | 2470 | 3230 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1550 | 1850 | 1.4 | 7.1 | 8.5 | 3.68 | A |
| | 2900 | 5600 | - | - | 149% | 8500 | 1940 | 3760 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1440 | 1750 | 1.4 | 6.6 | 8.0 | 3.96 | A |
| | 3800 | 3800 | - | - | 133% | 7600 | 2850 | 2850 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1470 | 1840 | 1.4 | 6.7 | 8.4 | 3.88 | A |
| | 3800 | 5600 | - | - | 165% | 9400 | 2300 | 3400 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1360 | 1750 | 1.4 | 6.2 | 8.0 | 4.19 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800, 5600W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 9.4 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Maldives P Series & Deluxe

#### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 40% | 2000 | 2400 | - | - | - | 2400 | 1250 | 2400 | 2880 | 300 | 730 | 880 | 1.7 | 3.3 | 4.0 | 3.29 | A |
| | 2500 | - | - | - | 50% | 2500 | 2500 | - | - | - | 2500 | 1250 | 2500 | 3120 | 300 | 800 | 960 | 1.7 | 3.7 | 4.4 | 3.13 | B |
| | 5000 | - | - | - | 100% | 5000 | 5000 | - | - | - | 5000 | 1250 | 5000 | 5200 | 300 | 1600 | 1740 | 1.7 | 7.3 | 8.0 | 3.13 | B |
| 2 Unit | 2000 | 2000 | - | - | 80% | 4000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4800 | 350 | 1245 | 1490 | 1.9 | 5.7 | 6.8 | 3.21 | A |
| | 2000 | 2500 | - | - | 90% | 4500 | 2040 | 2560 | - | - | 4600 | 1300 | 4600 | 5200 | 350 | 1430 | 1720 | 1.9 | 6.5 | 7.9 | 3.22 | A |
| | 2000 | 3500 | - | - | 110% | 5500 | 1820 | 3180 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1490 | 1780 | 1.9 | 6.8 | 8.1 | 3.36 | A |
| | 2000 | 5000 | - | - | 140% | 7000 | 1430 | 3570 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1450 | 1800 | 1.9 | 6.6 | 8.2 | 3.45 | A |
| | 2500 | 2500 | - | - | 100% | 5000 | 2500 | 2500 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 2500 | 3500 | - | - | 120% | 6000 | 2080 | 2920 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 2500 | 5000 | - | - | 150% | 7500 | 1670 | 3330 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1450 | 1700 | 1.9 | 6.6 | 7.8 | 3.45 | A |
| | 3500 | 3500 | - | - | 140% | 7000 | 2500 | 2500 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 3500 | 5000 | - | MAX | 170% | 8500 | 2060 | 2940 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1320 | 1700 | 1.9 | 6.0 | 7.8 | 3.79 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500, 5000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.5 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

#### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 3300 | - | - | - | 58% | 3300 | 3300 | - | - | - | 3300 | 1050 | 3300 | 3340 | 260 | 1050 | 1290 | 1.3 | 4.8 | 5.9 | 3.14 | D |
| | 5400 | - | - | - | 105% | 5400 | 5400 | - | - | - | 5400 | 1050 | 5400 | 5900 | 260 | 1650 | 2060 | 1.3 | 7.8 | 9.4 | 3.27 | C |
| 2 Unit | 2200 | 2200 | - | - | 77% | 4400 | 2200 | 2200 | - | - | 4400 | 1100 | 4400 | 4750 | 280 | 1220 | 1390 | 1.4 | 5.6 | 6.4 | 3.61 | A |
| | 2200 | 3300 | - | - | 96% | 5500 | 2040 | 3060 | - | - | 5100 | 1100 | 5100 | 5460 | 280 | 1410 | 1610 | 1.4 | 6.5 | 7.4 | 3.62 | A |
| | 2200 | 4000 | - | - | 109% | 6200 | 2020 | 3680 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1520 | 1900 | 1.4 | 7.0 | 8.7 | 3.75 | A |
| | 2200 | 6000 | - | - | 144% | 8200 | 1530 | 4170 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1440 | 1800 | 1.4 | 6.6 | 8.2 | 3.96 | A |
| | 3300 | 3300 | - | - | 116% | 6600 | 2850 | 2850 | - | - | 5700 | 1100 | 5700 | 6300 | 208 | 1550 | 1940 | 1.4 | 7.1 | 8.9 | 3.68 | A |
| | 3300 | 4000 | - | - | 128% | 7300 | 2580 | 3120 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1550 | 1850 | 1.4 | 7.1 | 8.5 | 3.68 | A |
| | 3300 | 6000 | - | - | 163% | 9300 | 2020 | 3680 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1440 | 1750 | 1.4 | 6.6 | 8.0 | 3.96 | A |
| | 4000 | 4000 | - | - | 140% | 8000 | 2850 | 2850 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1470 | 1840 | 1.4 | 6.7 | 8.4 | 3.88 | A |
| | 4000 | 6000 | - | - | 175% | 10000 | 2280 | 3420 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1350 | 1750 | 1.4 | 6.2 | 8.0 | 4.22 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000, 6000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.0 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## Jungfrau Y-series

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2500 | - | - | - | 50% | 2500 | 2500 | - | - | - | 2500 | 1250 | 2500 | 3120 | 300 | 800 | 960 | 1.7 | 3.7 | 4.4 | 3.13 | B |
| | 3500 | - | - | - | 70% | 3500 | 3500 | - | - | - | 3500 | 1250 | 3500 | 4200 | 300 | 1090 | 1310 | 1.7 | 5.0 | 6.0 | 3.21 | A |
| | 5000 | - | - | - | 100% | 5000 | 5000 | - | - | - | 5000 | 1250 | 5000 | 5200 | 300 | 1600 | 1740 | 1.7 | 7.3 | 8.0 | 3.13 | B |
| 2 Unit | 2500 | 2500 | - | - | 100% | 5000 | 2500 | 2500 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 2500 | 3500 | - | - | 120% | 6000 | 2080 | 2920 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 2500 | 5000 | - | - | 150% | 7500 | 1670 | 3330 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1450 | 1700 | 1.9 | 6.6 | 7.8 | 3.45 | A |
| | 3500 | 3500 | - | - | 140% | 7000 | 2500 | 2500 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1500 | 1780 | 1.9 | 6.9 | 8.1 | 3.33 | A |
| | 3500 | 5000 | - | - | 170% | 8500 | 2060 | 2940 | - | - | 5000 | 1400 | 5000 | 5400 | 350 | 1320 | 1700 | 1.9 | 6.0 | 7.8 | 3.79 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2500, 3500, 5000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.5 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 4000 | - | - | - | 70% | 4000 | 4000 | - | - | - | 4000 | 1050 | 4000 | 4470 | 260 | 1390 | 1620 | 1.3 | 5.9 | 7.4 | 3.09 | D |
| | 6000 | - | - | - | 105% | 6000 | 5400 | - | - | - | 5400 | 1050 | 5400 | 5600 | 260 | 1650 | 2060 | 1.3 | 7.6 | 9.4 | 3.27 | C |
| 2 Unit | 3200 | 3200 | - | - | 112% | 6400 | 2850 | 2850 | - | - | 5700 | 1100 | 5700 | 6300 | 208 | 1550 | 1940 | 1.4 | 7.1 | 8.9 | 3.68 | A |
| | 3200 | 4000 | - | - | 126% | 7200 | 2530 | 3170 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1550 | 1850 | 1.4 | 7.1 | 8.5 | 3.68 | A |
| | 3200 | 6000 | - | - | 161% | 9200 | 1980 | 3720 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1440 | 1750 | 1.4 | 6.6 | 8.0 | 3.96 | A |
| | 4000 | 4000 | - | - | 140% | 8000 | 2850 | 2850 | - | - | 5700 | 1100 | 5700 | 6300 | 280 | 1470 | 1840 | 1.4 | 6.7 | 8.4 | 3.88 | A |
| | 4000 | 6000 | - | - | 175% | 10000 | 2280 | 3420 | - | - | 5700 | 1100 | 5700 | 6400 | 280 | 1350 | 1750 | 1.4 | 6.2 | 8.0 | 4.22 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 3200, 4000, 6000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.0 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.





# RJ052F3HXEA

## Neo Forte & Crystal

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 38% | 2000 | 2000 | - | - | - | 2000 | 1280 | 2000 | 2880 | 400 | 630 | 930 | 2.2 | 2.9 | 4.3 | 3.17 | B |
| | 2600 | - | - | - | 50% | 2600 | 2600 | - | - | - | 2600 | 1280 | 2600 | 3120 | 400 | 790 | 1010 | 2.2 | 3.6 | 4.6 | 3.29 | A |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5200 | - | - | - | 100% | 5200 | 5200 | - | - | - | 5200 | 1300 | 5200 | 5800 | 400 | 1620 | 1980 | 2.2 | 7.4 | 8.7 | 3.21 | A |
| 2 Unit | 2000 | 2000 | - | - | 77% | 4000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4800 | 440 | 1240 | 1630 | 2.3 | 5.7 | 7.5 | 3.23 | A |
| | 2000 | 2600 | - | - | 88% | 4600 | 2000 | 2600 | - | - | 4600 | 1300 | 4600 | 5520 | 440 | 1410 | 1850 | 2.3 | 6.5 | 8.5 | 3.26 | A |
| | 2000 | 3500 | - | - | 106% | 5500 | 1820 | 3180 | - | - | 5000 | 1300 | 5000 | 6290 | 450 | 1520 | 2000 | 2.3 | 7.0 | 9.2 | 3.29 | A |
| | 2000 | 5200 | - | - | 138% | 7200 | 1440 | 3760 | - | - | 5200 | 1380 | 5200 | 6600 | 450 | 1540 | 2040 | 2.3 | 7.0 | 9.3 | 3.38 | A |
| | 2600 | 2600 | - | - | 100% | 5200 | 2500 | 2500 | - | - | 5000 | 1300 | 5000 | 5800 | 440 | 1550 | 1980 | 2.3 | 7.1 | 9.1 | 3.23 | A |
| | 2600 | 3500 | - | - | 117% | 6100 | 2130 | 2870 | - | - | 5000 | 1300 | 5000 | 6400 | 450 | 1510 | 2020 | 2.3 | 6.9 | 9.2 | 3.31 | A |
| | 2600 | 5200 | - | - | 150% | 7800 | 1730 | 3470 | - | - | 5200 | 1380 | 5200 | 6800 | 450 | 1540 | 2070 | 2.3 | 7.0 | 9.5 | 3.38 | A |
| | 3500 | 3500 | - | - | 135% | 7000 | 2600 | 2600 | - | - | 5200 | 1300 | 5200 | 6560 | 450 | 1540 | 2040 | 2.3 | 7.0 | 9.3 | 3.38 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 115% | 6000 | 1730 | 1730 | 1740 | - | 5200 | 1700 | 5200 | 6380 | 450 | 1500 | 2020 | 2.3 | 6.9 | 9.2 | 3.47 | A |
| | 2000 | 2000 | 2600 | - | 127% | 6600 | 1580 | 1580 | 2040 | - | 5200 | 1700 | 5200 | 6490 | 450 | 1530 | 2040 | 2.3 | 7.0 | 9.3 | 3.40 | A |
| | 2000 | 2000 | 3500 | - | 144% | 7500 | 1390 | 1390 | 2420 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1420 | 2070 | 2.4 | 6.5 | 9.5 | 3.66 | A |
| | 2000 | 2600 | 2600 | - | 138% | 7200 | 1440 | 1880 | 1880 | - | 5200 | 1700 | 5200 | 6600 | 450 | 1390 | 2040 | 2.3 | 6.4 | 9.3 | 3.74 | A |
| | 2000 | 2600 | 3500 | - | 156% | 8100 | 1280 | 1670 | 2250 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1420 | 2070 | 2.4 | 6.5 | 9.5 | 3.66 | A |
| | 2600 | 2600 | 2600 | - | 150% | 7800 | 1730 | 1730 | 1740 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1350 | 2070 | 2.4 | 6.2 | 9.5 | 3.85 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2600, 3500, 5200W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.1 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | | | | | | | | | | | | | | | | | | | | | | |
| | 2500 | - | - | - | 46% | 2500 | 2500 | - | - | - | 2500 | 1300 | 2500 | 3240 | 350 | 1150 | 1270 | 1.9 | 5.3 | 5.8 | 2.52 | F |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5500 | - | - | - | 89% | 5500 | 5500 | - | - | - | 5500 | 1350 | 5500 | 6300 | 350 | 1520 | 1920 | 1.9 | 8.3 | 8.3 | 3.08 | D |
| 2 Unit | 2200 | 2200 | - | - | 70% | 4400 | 2200 | 2200 | - | - | 4400 | 1400 | 4400 | 5060 | 350 | 1220 | 1510 | 1.9 | 5.6 | 6.9 | 3.61 | A |
| | 2200 | 2900 | - | - | 81% | 5100 | 2200 | 2900 | - | - | 5100 | 1400 | 5100 | 5870 | 350 | 1410 | 1830 | 1.9 | 6.5 | 8.4 | 3.62 | A |
| | 2200 | 3800 | - | - | 95% | 6000 | 2050 | 3550 | - | - | 5600 | 1400 | 5600 | 6440 | 350 | 1540 | 1860 | 1.9 | 7.0 | 8.5 | 3.64 | A |
| | 2200 | 5600 | - | - | 124% | 7800 | 1690 | 4310 | - | - | 6000 | 1400 | 6000 | 6900 | 350 | 1660 | 1860 | 1.9 | 7.6 | 8.5 | 3.61 | A |
| | 2900 | 2900 | - | - | 92% | 5800 | 2900 | 2900 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1600 | 1910 | 1.9 | 7.3 | 8.7 | 3.63 | A |
| | 2900 | 3800 | - | - | 106% | 6700 | 2510 | 3290 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1600 | 1910 | 1.9 | 7.3 | 8.7 | 3.63 | A |
| | 2900 | 5600 | - | - | 135% | 8500 | 2150 | 4150 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1830 | 1.9 | 8.0 | 8.4 | 3.62 | A |
| | 3800 | 3800 | - | - | 121% | 7600 | 2950 | 2950 | - | - | 5900 | 1400 | 5900 | 6880 | 350 | 1630 | 1860 | 1.9 | 7.5 | 8.5 | 3.62 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 105% | 6600 | 1930 | 1930 | 1940 | - | 5800 | 1400 | 5800 | 6760 | 350 | 1590 | 1840 | 1.9 | 7.3 | 8.4 | 3.65 | A |
| | 2200 | 2200 | 2900 | - | 116% | 7300 | 1780 | 1780 | 2340 | - | 5900 | 1400 | 5900 | 6840 | 350 | 1650 | 1840 | 1.9 | 7.6 | 8.4 | 3.58 | B |
| | 2200 | 2200 | 3800 | - | 130% | 8200 | 1690 | 1690 | 2920 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1660 | 1830 | 1.9 | 7.6 | 8.4 | 3.80 | A |
| | 2200 | 2900 | 2900 | - | 127% | 8000 | 1660 | 2170 | 2170 | - | 6000 | 1400 | 6000 | 6920 | 350 | 1590 | 1840 | 1.9 | 7.3 | 8.4 | 3.77 | A |
| | 2200 | 2900 | 3800 | - | 141% | 8900 | 1560 | 2050 | 2690 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1630 | 1830 | 1.9 | 7.5 | 8.4 | 3.87 | A |
| | 2900 | 2900 | 2900 | - | 138% | 8700 | 2100 | 2100 | 2100 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1400 | 1830 | 1.9 | 6.4 | 8.4 | 4.50 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800, 5600W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.9 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ052F3HXEA

### Maldives P Series & Deluxe

**COOLING**

| Outdoor Unit | Indoor Unit Combination A | B | C | D | % | Total | Cooling Capacity (W) A | B | C | D | Total | Capacity W MIN | NOM | MAX | Power Consumption W MIN | NOM | MAX | Current A MIN | NOM | MAX | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 Unit | 2000 | - | - | - | 38% | 2000 | 2000 | - | - | - | 2000 | 1280 | 2000 | 2880 | 420 | 630 | 1020 | 2.2 | 2.9 | 4.7 | 3.17 | B |
| | 2500 | - | - | - | 48% | 2500 | 2500 | - | - | - | 2500 | 1280 | 2500 | 3120 | 420 | 790 | 1110 | 2.2 | 3.6 | 5.1 | 3.16 | B |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5000 | - | - | - | 96% | 5000 | 5000 | - | - | - | 5000 | 1300 | 5000 | 5800 | 420 | 620 | 2090 | 2.2 | 7.4 | 9.6 | 3.09 | B |
| 2 Unit | 2000 | 2000 | - | - | 77% | 4000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4800 | 440 | 1240 | 1630 | 2.3 | 5.7 | 7.5 | 3.23 | A |
| | 2000 | 2500 | - | - | 87% | 4500 | 2040 | 2560 | - | - | 4600 | 1300 | 4600 | 5520 | 440 | 1410 | 1850 | 2.3 | 6.5 | 8.5 | 3.26 | A |
| | 2000 | 3500 | - | - | 106% | 5500 | 1820 | 3180 | - | - | 5000 | 1300 | 5000 | 6290 | 450 | 1520 | 2000 | 2.3 | 7.0 | 9.2 | 3.29 | A |
| | 2000 | 5000 | - | - | 135% | 7000 | 1490 | 3710 | - | - | 5200 | 1380 | 5200 | 6600 | 450 | 1540 | 2040 | 2.3 | 7.0 | 9.3 | 3.38 | A |
| | 2500 | 2500 | - | - | 96% | 5000 | 2500 | 2500 | - | - | 5000 | 1300 | 5000 | 5800 | 440 | 1550 | 1980 | 2.3 | 7.1 | 9.1 | 3.23 | A |
| | 2500 | 3500 | - | - | 115% | 6000 | 2080 | 2920 | - | - | 5000 | 1300 | 5000 | 6400 | 450 | 1510 | 2020 | 2.3 | 6.9 | 9.2 | 3.31 | A |
| | 2500 | 5000 | - | - | 144% | 7500 | 1730 | 3470 | - | - | 5200 | 1380 | 5200 | 6800 | 450 | 1540 | 2070 | 2.3 | 7.0 | 9.5 | 3.38 | A |
| | 3500 | 3500 | - | - | 135% | 7000 | 2600 | 2600 | - | - | 5200 | 1300 | 5200 | 6560 | 450 | 1540 | 2040 | 2.3 | 7.0 | 9.3 | 3.38 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 115% | 6000 | 1730 | 1730 | 1740 | - | 5200 | 1700 | 5200 | 6380 | 450 | 1500 | 2020 | 2.3 | 6.9 | 9.2 | 3.47 | A |
| | 2000 | 2000 | 2500 | - | 125% | 6500 | 1600 | 1600 | 2000 | - | 5200 | 1700 | 5200 | 6490 | 450 | 1530 | 2040 | 2.3 | 7.0 | 9.3 | 3.40 | A |
| | 2000 | 2000 | 3500 | - | 144% | 7500 | 1390 | 1390 | 2420 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1420 | 2070 | 2.4 | 6.5 | 9.5 | 3.66 | A |
| | 2000 | 2500 | 2500 | - | 135% | 7000 | 1480 | 1860 | 1860 | - | 5200 | 1700 | 5200 | 6600 | 450 | 1390 | 2040 | 2.3 | 6.4 | 9.3 | 3.74 | A |
| | 2000 | 2500 | 3500 | - | 154% | 8000 | 1300 | 1630 | 2270 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1420 | 2070 | 2.4 | 6.5 | 9.5 | 3.66 | A |
| | 2500 | 2500 | 2500 | - | 144% | 7500 | 1730 | 1730 | 1740 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1350 | 2070 | 2.4 | 6.2 | 9.5 | 3.85 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500, 5000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination A | B | C | D | % | Total | Heating Capacity (W) A | B | C | D | Total | Capacity W MIN | NOM | MAX | Power Consumption W MIN | NOM | MAX | Current A MIN | NOM | MAX | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | | | | |
| 1 Unit | 3300 | | | | 52% | 3300 | 3300 | - | - | - | 3300 | 1300 | 3300 | 3340 | 350 | 1150 | 1270 | 1.9 | 5.3 | 5.8 | 2.97 | D |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 9000 | | | | 95% | 9000 | 5600 | - | - | - | 5600 | 1350 | 5600 | 6300 | 350 | 1820 | 1920 | 1.9 | 8.3 | 8.8 | 3.08 | D |
| 2 Unit | 2200 | 2200 | - | - | 70% | 4400 | 2200 | 2200 | - | - | 4400 | 1400 | 4400 | 5060 | 350 | 1220 | 1510 | 1.9 | 5.6 | 6.9 | 3.61 | A |
| | 2200 | 3300 | - | - | 87% | 5500 | 2040 | 3060 | - | - | 5100 | 1400 | 5100 | 5870 | 350 | 1410 | 1830 | 1.9 | 6.5 | 8.4 | 3.62 | A |
| | 2200 | 4000 | - | - | 98% | 6200 | 1990 | 3610 | - | - | 5600 | 1400 | 5600 | 6440 | 350 | 1540 | 1860 | 1.9 | 7.0 | 8.5 | 3.64 | A |
| | 2200 | 6000 | - | - | 130% | 8200 | 1610 | 4390 | - | - | 6000 | 1400 | 6000 | 6900 | 350 | 1660 | 1860 | 1.9 | 7.6 | 8.5 | 3.61 | A |
| | 3300 | 3300 | - | - | 105% | 6600 | 2900 | 2900 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1600 | 1910 | 1.9 | 7.3 | 8.7 | 3.63 | A |
| | 3300 | 4000 | - | - | 116% | 7300 | 2620 | 3180 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1600 | 1910 | 1.9 | 7.3 | 8.7 | 3.63 | A |
| | 3300 | 6000 | - | - | 148% | 9300 | 2240 | 4060 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1830 | 1.9 | 8.0 | 8.4 | 3.62 | A |
| | 4000 | 4000 | - | - | 127% | 8000 | 2950 | 2950 | - | - | 5900 | 1400 | 5900 | 6880 | 350 | 1630 | 1860 | 1.9 | 7.5 | 8.5 | 3.62 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 105% | 6600 | 1930 | 1930 | 1940 | - | 5800 | 1400 | 5800 | 6760 | 350 | 1590 | 1840 | 1.9 | 7.3 | 8.4 | 3.65 | A |
| | 2200 | 2200 | 3300 | - | 122% | 7700 | 1690 | 1690 | 2520 | - | 5900 | 1400 | 5900 | 6840 | 350 | 1650 | 1840 | 1.9 | 7.6 | 8.4 | 3.58 | B |
| | 2200 | 2200 | 4000 | - | 133% | 8400 | 1650 | 1650 | 3000 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1660 | 1830 | 1.9 | 7.6 | 8.4 | 3.80 | A |
| | 2200 | 3300 | 3300 | - | 140% | 8800 | 1500 | 2250 | 2250 | - | 6000 | 1400 | 6000 | 6920 | 350 | 1590 | 1840 | 1.9 | 7.3 | 8.4 | 3.77 | A |
| | 2200 | 3300 | 4000 | - | 151% | 9500 | 1460 | 2190 | 2650 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1630 | 1830 | 1.9 | 7.5 | 8.4 | 3.87 | A |
| | 3300 | 3300 | 3300 | - | 157% | 9900 | 2100 | 2100 | 2100 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1400 | 1830 | 1.9 | 6.4 | 8.4 | 4.50 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000, 6000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 9.9 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Jungfrau Y-series

**COOLING**

| Outdoor Unit | Indoor Unit Combination A | B | C | D | % | Total | Cooling Capacity (W) A | B | C | D | Total | Capacity W MIN | NOM | MAX | Power Consumption W MIN | NOM | MAX | Current A MIN | NOM | MAX | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 Unit | 2500 | - | - | - | 48% | 2500 | 2500 | - | - | - | 2500 | 1280 | 2500 | 3120 | 420 | 790 | 1110 | 2.2 | 3.6 | 5.1 | 3.16 | B |
| | 3500 | - | - | - | 67% | 3500 | 3500 | - | - | - | 3500 | 1280 | 3500 | 4200 | 420 | 1150 | 1510 | 2.2 | 5.3 | 6.9 | 3.04 | B |
| | 5000 | - | - | - | 96% | 5000 | 4900 | - | - | - | 4900 | 1300 | 4900 | 5500 | 420 | 1620 | 2090 | 2.2 | 7.4 | 9.6 | 3.09 | B |
| 2 Unit | 2500 | 2500 | - | - | 96% | 5000 | 2500 | 2500 | - | - | 5000 | 1300 | 5000 | 5800 | 440 | 1550 | 1980 | 2.3 | 7.1 | 9.1 | 3.23 | A |
| | 2500 | 3500 | - | - | 115% | 6000 | 2080 | 2920 | - | - | 5000 | 1300 | 5000 | 6400 | 450 | 1510 | 2020 | 2.3 | 6.9 | 9.2 | 3.31 | A |
| | 2500 | 5000 | - | - | 144% | 7500 | 1730 | 3470 | - | - | 5200 | 1380 | 5200 | 6800 | 450 | 1540 | 2070 | 2.3 | 7.0 | 9.5 | 3.38 | A |
| | 3500 | 3500 | - | - | 135% | 7000 | 2600 | 2600 | - | - | 5200 | 1300 | 5200 | 6560 | 450 | 1540 | 2040 | 2.3 | 7.0 | 9.3 | 3.38 | A |
| 3 Unit | 2500 | 2500 | 2500 | - | 144% | 7500 | 1730 | 1730 | 1740 | - | 5200 | 1700 | 5200 | 6800 | 460 | 1350 | 2070 | 2.4 | 6.2 | 9.5 | 3.85 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2500, 3500, 5000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 7.5 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination A | B | C | D | % | Total | Heating Capacity (W) A | B | C | D | Total | Capacity W MIN | NOM | MAX | Power Consumption W MIN | NOM | MAX | Current A MIN | NOM | MAX | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 Unit | 3200 | - | - | - | 51% | 3200 | 3300 | - | - | - | 3300 | 1300 | 3300 | 3340 | 350 | 1150 | 1270 | 1.9 | 5.3 | 5.8 | 2.87 | D |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 9000 | - | - | - | 95% | 9000 | 5500 | - | - | - | 5500 | 1350 | 5500 | 6300 | 350 | 1820 | 1920 | 1.9 | 8.3 | 8.8 | 3.08 | D |
| 2 Unit | 3200 | 3200 | - | - | 102% | 6400 | 2900 | 2900 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1600 | 1910 | 1.9 | 7.3 | 8.7 | 3.63 | A |
| | 3200 | 4000 | - | - | 114% | 7200 | 2580 | 3220 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1600 | 1910 | 1.9 | 7.3 | 8.7 | 3.63 | A |
| | 3200 | 6000 | - | - | 146% | 9200 | 2190 | 4110 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1830 | 1.9 | 8.0 | 8.4 | 3.62 | A |
| | 4000 | 4000 | - | - | 127% | 8000 | 2950 | 2950 | - | - | 5900 | 1400 | 5900 | 6880 | 350 | 1630 | 1860 | 1.9 | 7.5 | 8.5 | 3.62 | A |
| 3 Unit | 3200 | 3200 | 3200 | - | 152% | 9600 | 2100 | 2100 | 2100 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1400 | 1830 | 1.9 | 6.4 | 8.4 | 4.50 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 3200, 4000, 6000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 9.6 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ060F3HXEB

### Neo Forte & Crystal

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 34% | 2000 | 2400 | - | - | - | 2400 | 1280 | 2400 | 2880 | 400 | 630 | 930 | 2.2 | 2.9 | 4.3 | 3.81 | A |
| | 2600 | - | - | - | 44% | 2600 | 2600 | - | - | - | 2600 | 1280 | 2600 | 3120 | 400 | 790 | 1010 | 2.2 | 3.6 | 4.6 | 3.29 | A |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5200 | - | - | - | 88% | 5200 | 5200 | - | - | - | 5200 | 1300 | 5200 | 5800 | 400 | 1820 | 1800 | 2.2 | 7.4 | 8.7 | 3.21 | A |
| 2 Unit | 2000 | 2000 | - | - | 68% | 4000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4800 | 420 | 1240 | 1480 | 2.3 | 5.7 | 6.8 | 3.23 | A |
| | 2000 | 2600 | - | - | 78% | 4600 | 2000 | 2600 | - | - | 4600 | 1300 | 4600 | 5520 | 420 | 1410 | 1680 | 2.3 | 6.5 | 7.7 | 3.26 | A |
| | 2000 | 3500 | - | - | 93% | 5500 | 1910 | 3340 | - | - | 5250 | 1300 | 5250 | 6290 | 430 | 1550 | 1820 | 2.3 | 7.1 | 8.3 | 3.39 | A |
| | 2000 | 5200 | - | - | 122% | 7200 | 1530 | 3970 | - | - | 5500 | 1380 | 5500 | 6600 | 430 | 1580 | 1850 | 2.3 | 7.2 | 8.5 | 3.48 | A |
| | 2600 | 2600 | - | - | 88% | 5200 | 2600 | 2600 | - | - | 5200 | 1300 | 5200 | 5800 | 420 | 1620 | 1800 | 2.3 | 7.4 | 8.2 | 3.21 | A |
| | 2600 | 3500 | - | - | 103% | 6100 | 2260 | 3040 | - | - | 5300 | 1300 | 5300 | 6400 | 430 | 1550 | 1840 | 2.3 | 7.1 | 8.4 | 3.42 | A |
| | 2600 | 5200 | - | - | 132% | 7800 | 1970 | 3930 | - | - | 5900 | 1380 | 5900 | 6800 | 430 | 1700 | 1880 | 2.3 | 7.8 | 8.6 | 3.47 | A |
| | 3500 | 3500 | - | - | 119% | 7000 | 2725 | 2725 | - | - | 5450 | 1300 | 5450 | 6560 | 430 | 1570 | 1850 | 2.3 | 7.2 | 8.5 | 3.47 | A |
| | 3500 | 5200 | - | - | 147% | 8700 | 2370 | 3530 | - | - | 5900 | 1380 | 5900 | 6800 | 440 | 1700 | 1880 | 2.4 | 7.8 | 8.6 | 3.47 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 102% | 6000 | 1760 | 1760 | 1760 | - | 5280 | 1700 | 5280 | 6380 | 430 | 1550 | 1840 | 2.3 | 7.1 | 8.4 | 3.41 | A |
| | 2000 | 2000 | 2600 | - | 112% | 6600 | 1640 | 1640 | 2120 | - | 5400 | 1700 | 5400 | 6490 | 430 | 1560 | 1850 | 2.3 | 7.1 | 8.5 | 3.46 | A |
| | 2000 | 2000 | 3500 | - | 127% | 7500 | 1580 | 1580 | 2740 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1610 | 1880 | 2.4 | 7.4 | 8.6 | 3.66 | A |
| | 2000 | 2600 | 2600 | - | 122% | 7200 | 1520 | 1990 | 1990 | - | 5500 | 1700 | 5500 | 6600 | 430 | 1580 | 1850 | 2.3 | 7.2 | 8.5 | 3.48 | A |
| | 2000 | 2600 | 3500 | - | 137% | 8100 | 1460 | 1890 | 2550 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1610 | 1880 | 2.4 | 7.4 | 8.6 | 3.66 | A |
| | 2000 | 3500 | 3500 | - | 153% | 9000 | 1320 | 2290 | 2290 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1610 | 1880 | 2.4 | 7.4 | 8.6 | 3.66 | A |
| | 2600 | 2600 | 2600 | - | 132% | 7800 | 1960 | 1970 | 1970 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1600 | 1880 | 2.4 | 7.3 | 8.6 | 3.69 | A |
| | 2600 | 2600 | 3500 | - | 147% | 8700 | 1770 | 1770 | 2360 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1600 | 1880 | 2.4 | 7.3 | 8.6 | 3.69 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2600, 3500, 5200W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 9.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 35% | 2200 | 2500 | - | - | - | 2500 | 1300 | 2500 | 2990 | 350 | 880 | 1190 | 2.2 | 4.0 | 5.4 | 2.84 | D |
| | 2900 | - | - | - | 46% | 2900 | 2900 | - | - | - | 2900 | 1300 | 2900 | 3340 | 350 | 1150 | 1360 | 2.2 | 5.3 | 6.2 | 2.52 | F |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5800 | - | - | - | 82% | 5800 | 5800 | - | - | - | 5800 | 1350 | 5800 | 6500 | 350 | 1820 | 2050 | 2.2 | 8.3 | 9.4 | 3.08 | D |
| 2 Unit | 2200 | 2200 | - | - | 70% | 4400 | 2200 | 2200 | - | - | 4400 | 1400 | 4400 | 5060 | 350 | 1220 | 1620 | 2.3 | 5.6 | 7.4 | 3.61 | A |
| | 2200 | 2900 | - | - | 81% | 5100 | 2200 | 2900 | - | - | 5100 | 1400 | 5100 | 5870 | 350 | 1490 | 1960 | 2.3 | 6.8 | 9.0 | 3.42 | B |
| | 2200 | 3800 | - | - | 95% | 6000 | 2050 | 3550 | - | - | 5600 | 1400 | 5600 | 6440 | 350 | 1640 | 1990 | 2.3 | 7.5 | 9.1 | 3.41 | B |
| | 2200 | 5600 | - | - | 124% | 7800 | 1690 | 4310 | - | - | 6000 | 1400 | 6000 | 6900 | 350 | 1660 | 1990 | 2.3 | 7.6 | 9.1 | 3.61 | A |
| | 2900 | 2900 | - | - | 92% | 5800 | 2900 | 2900 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1700 | 2040 | 2.3 | 7.8 | 9.3 | 3.41 | B |
| | 2900 | 3800 | - | - | 106% | 6700 | 2510 | 3290 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1700 | 2040 | 2.3 | 7.8 | 9.3 | 3.41 | B |
| | 2900 | 5600 | - | - | 135% | 8500 | 2150 | 4150 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1960 | 2.3 | 8.0 | 9.0 | 3.62 | A |
| | 3800 | 3800 | - | - | 121% | 7600 | 2950 | 2950 | - | - | 5900 | 1400 | 5900 | 6880 | 350 | 1730 | 1990 | 2.3 | 7.9 | 9.1 | 3.41 | B |
| | 3800 | 5600 | - | - | 149% | 9400 | 2550 | 3750 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1960 | 2.4 | 8.0 | 9.0 | 3.62 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 105% | 6600 | 1930 | 1930 | 1940 | - | 5800 | 1400 | 5800 | 6760 | 350 | 1590 | 1970 | 2.3 | 7.3 | 9.0 | 3.65 | A |
| | 2200 | 2200 | 2900 | - | 116% | 7300 | 1780 | 1780 | 2340 | - | 5900 | 1400 | 5900 | 6840 | 350 | 1610 | 1970 | 2.3 | 7.4 | 9.0 | 3.66 | A |
| | 2200 | 2200 | 3800 | - | 130% | 8200 | 1690 | 1690 | 2920 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1660 | 1960 | 2.4 | 7.6 | 9.0 | 3.80 | A |
| | 2200 | 2900 | 2900 | - | 127% | 8000 | 1660 | 2170 | 2170 | - | 6000 | 1400 | 6000 | 6920 | 350 | 1590 | 1970 | 2.3 | 7.3 | 9.0 | 3.77 | A |
| | 2200 | 2900 | 3800 | - | 141% | 8900 | 1560 | 2050 | 2690 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1630 | 1960 | 2.4 | 7.5 | 9.0 | 3.87 | A |
| | 2200 | 3800 | 3800 | - | 156% | 9800 | 1420 | 2440 | 2440 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1560 | 1960 | 2.4 | 7.1 | 9.0 | 4.04 | A |
| | 2900 | 2900 | 2900 | - | 138% | 8700 | 2100 | 2100 | 2100 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1650 | 1960 | 2.4 | 7.6 | 9.0 | 3.82 | A |
| | 2900 | 2900 | 3800 | - | 152% | 9600 | 1910 | 1910 | 2480 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1400 | 1960 | 2.4 | 6.4 | 9.0 | 4.50 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800, 5600W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 9.8 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Maldives P Series & Deluxe

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 34% | 2000 | 2000 | - | - | - | 2000 | 1280 | 2000 | 2880 | 400 | 630 | 930 | 2.2 | 2.9 | 4.3 | 3.17 | B |
| | 2500 | - | - | - | 42% | 2500 | 2500 | - | - | - | 2500 | 1280 | 2500 | 3120 | 400 | 790 | 1010 | 2.2 | 3.6 | 4.6 | 3.16 | B |
| | 3500 | - | - | - | 59% | 3500 | 3500 | - | - | - | 3500 | 1280 | 3500 | 4200 | 400 | 1070 | 1370 | 2.2 | 4.9 | 6.3 | 3.27 | A |
| | 5000 | - | - | - | 85% | 5000 | 5000 | - | - | - | 5000 | 1300 | 5000 | 5800 | 400 | 1620 | 1900 | 2.2 | 7.4 | 8.7 | 3.09 | B |
| 2 Unit | 2000 | 2000 | - | - | 68% | 4000 | 2000 | 2000 | - | - | 4000 | 1300 | 4000 | 4800 | 420 | 1240 | 1480 | 2.3 | 5.7 | 6.8 | 3.23 | A |
| | 2000 | 2500 | - | - | 76% | 4500 | 2040 | 2560 | - | - | 4600 | 1300 | 4600 | 5520 | 420 | 1410 | 1680 | 2.3 | 6.5 | 7.7 | 3.26 | A |
| | 2000 | 3500 | - | - | 93% | 5500 | 1910 | 3340 | - | - | 5250 | 1300 | 5250 | 6290 | 430 | 1550 | 1820 | 2.3 | 7.1 | 8.3 | 3.39 | A |
| | 2000 | 5000 | - | - | 119% | 7000 | 1570 | 3930 | - | - | 5500 | 1380 | 5500 | 6600 | 430 | 1580 | 1850 | 2.3 | 7.2 | 8.5 | 3.48 | A |
| | 2500 | 2500 | - | - | 85% | 5000 | 2600 | 2600 | - | - | 5200 | 1300 | 5200 | 5800 | 420 | 1620 | 1800 | 2.3 | 7.4 | 8.2 | 3.21 | A |
| | 2500 | 3500 | - | - | 102% | 6000 | 2210 | 3090 | - | - | 5300 | 1300 | 5300 | 6400 | 430 | 1550 | 1840 | 2.3 | 7.1 | 8.4 | 3.42 | A |
| | 2500 | 5000 | - | - | 127% | 7500 | 1970 | 3930 | - | - | 5900 | 1380 | 5900 | 6800 | 430 | 1700 | 1880 | 2.3 | 7.8 | 8.6 | 3.47 | A |
| | 3500 | 3500 | - | - | 119% | 7000 | 2725 | 2725 | - | - | 5450 | 1300 | 5450 | 6560 | 430 | 1570 | 1850 | 2.3 | 7.2 | 8.5 | 3.47 | A |
| | 3500 | 5000 | - | - | 144% | 8500 | 2430 | 3470 | - | - | 5900 | 1380 | 5900 | 6800 | 440 | 1700 | 1880 | 2.4 | 7.8 | 8.6 | 3.47 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 102% | 6000 | 1760 | 1760 | 1760 | - | 5280 | 1700 | 5280 | 6380 | 430 | 1550 | 1840 | 2.3 | 7.1 | 8.4 | 3.41 | A |
| | 2000 | 2000 | 2500 | - | 110% | 6500 | 1660 | 1660 | 2080 | - | 5400 | 1700 | 5400 | 6490 | 430 | 1560 | 1850 | 2.3 | 7.1 | 8.5 | 3.46 | A |
| | 2000 | 2000 | 3500 | - | 127% | 7500 | 1580 | 1580 | 2740 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1610 | 1880 | 2.4 | 7.4 | 8.6 | 3.66 | A |
| | 2000 | 2500 | 2500 | - | 119% | 7000 | 1580 | 1960 | 1960 | - | 5500 | 1700 | 5500 | 6600 | 430 | 1580 | 1850 | 2.3 | 7.2 | 8.5 | 3.48 | A |
| | 2000 | 2500 | 3500 | - | 136% | 8000 | 1480 | 1840 | 2580 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1610 | 1880 | 2.4 | 7.4 | 8.6 | 3.66 | A |
| | 2000 | 3500 | 3500 | - | 153% | 9000 | 1320 | 2290 | 2290 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1610 | 1880 | 2.4 | 7.4 | 8.6 | 3.66 | A |
| | 2500 | 2500 | 2500 | - | 127% | 7500 | 1960 | 1970 | 1970 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1600 | 1880 | 2.4 | 7.3 | 8.6 | 3.69 | A |
| | 2500 | 2500 | 3500 | - | 144% | 8500 | 1740 | 1740 | 2420 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1600 | 1880 | 2.4 | 7.3 | 8.6 | 3.69 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500, 5000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 9.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 35% | 2200 | 2200 | - | - | - | 2200 | 1300 | 2200 | 2990 | 350 | 880 | 1190 | 1.9 | 4.0 | 5.4 | 2.50 | F |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 4000 | - | - | - | 63% | 4000 | 4000 | - | - | - | 4000 | 1300 | 4000 | 4670 | 350 | 1360 | 1720 | 1.9 | 6.2 | 8.1 | 2.96 | D |
| | 6000 | - | - | - | 95% | 6000 | 5600 | - | - | - | 5600 | 1350 | 5600 | 6300 | 350 | 1820 | 2050 | 1.9 | 8.3 | 9.4 | 3.08 | D |
| 2 Unit | 2200 | 2200 | - | - | 70% | 4400 | 2200 | 2200 | - | - | 4400 | 1400 | 4400 | 5060 | 350 | 1220 | 1620 | 1.9 | 5.6 | 7.4 | 3.61 | A |
| | 2200 | 3300 | - | - | 87% | 5500 | 2040 | 3060 | - | - | 5100 | 1400 | 5100 | 5870 | 350 | 1490 | 1960 | 1.9 | 6.8 | 9.0 | 3.42 | B |
| | 2200 | 4000 | - | - | 98% | 6200 | 1990 | 3610 | - | - | 5600 | 1400 | 5600 | 6440 | 350 | 1640 | 1990 | 1.9 | 7.5 | 9.1 | 3.41 | B |
| | 2200 | 6000 | - | - | 130% | 8200 | 1610 | 4390 | - | - | 6000 | 1400 | 6000 | 6900 | 350 | 1660 | 1990 | 1.9 | 7.6 | 9.1 | 3.61 | A |
| | 3300 | 3300 | - | - | 105% | 6600 | 2900 | 2900 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1700 | 2040 | 1.9 | 7.8 | 9.3 | 3.41 | B |
| | 3300 | 4000 | - | - | 116% | 7300 | 2620 | 3180 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1700 | 2040 | 1.9 | 7.8 | 9.3 | 3.41 | B |
| | 3300 | 6000 | - | - | 148% | 9300 | 2240 | 4060 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1960 | 1.9 | 8.0 | 9.0 | 3.62 | A |
| | 4000 | 4000 | - | - | 127% | 8000 | 2950 | 2950 | - | - | 5900 | 1400 | 5900 | 6880 | 350 | 1730 | 1990 | 1.9 | 7.9 | 9.1 | 3.41 | B |
| | 4000 | 6000 | - | - | 159% | 10000 | 2520 | 3780 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1960 | 1.9 | 8.0 | 9.0 | 3.62 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 105% | 6600 | 1930 | 1930 | 1940 | - | 5800 | 1400 | 5800 | 6760 | 350 | 1590 | 1970 | 1.9 | 7.3 | 9.0 | 3.65 | A |
| | 2200 | 2200 | 3300 | - | 122% | 7700 | 1690 | 1690 | 2520 | - | 5900 | 1400 | 5900 | 6840 | 350 | 1610 | 1970 | 1.9 | 7.4 | 9.0 | 3.66 | A |
| | 2200 | 2200 | 4000 | - | 133% | 8400 | 1650 | 1650 | 3000 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1660 | 1960 | 1.9 | 7.6 | 9.0 | 3.80 | A |
| | 2200 | 3300 | 3300 | - | 140% | 8800 | 1500 | 2250 | 2250 | - | 6000 | 1400 | 6000 | 6920 | 350 | 1590 | 1970 | 1.9 | 7.3 | 9.0 | 3.77 | A |
| | 2200 | 3300 | 4000 | - | 151% | 9500 | 1460 | 2190 | 2650 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1630 | 1960 | 1.9 | 7.5 | 9.0 | 3.87 | A |
| | 2200 | 4000 | 4000 | - | 162% | 10200 | 1360 | 2470 | 2470 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1560 | 1960 | 1.9 | 7.1 | 9.0 | 4.04 | A |
| | 3300 | 3300 | 3300 | - | 157% | 9900 | 2100 | 2100 | 2100 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1650 | 1960 | 1.9 | 7.6 | 9.0 | 3.82 | A |
| | 3300 | 3300 | 4000 | - | 168% | 10600 | 1960 | 1960 | 2380 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1400 | 1960 | 1.9 | 6.4 | 9.0 | 4.50 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000, 6000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.6 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ060F3HXEB

### Jungfrau Y-series

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2500 | - | - | - | 42% | 2500 | 2500 | - | - | - | 2500 | 1280 | 2500 | 3120 | 400 | 790 | 1010 | 2.2 | 3.6 | 4.6 | 3.16 | B |
| | 3500 | - | - | - | 59% | 3500 | 3500 | - | - | - | 3500 | 1280 | 3500 | 4200 | 400 | 1070 | 1370 | 2.2 | 4.9 | 6.3 | 3.27 | A |
| | 5000 | - | - | - | 85% | 5000 | 5000 | - | - | - | 5000 | 1300 | 5000 | 5800 | 400 | 1620 | 1900 | 2.2 | 7.4 | 8.7 | 3.09 | B |
| 2 Unit | 2500 | 2500 | - | - | 85% | 5000 | 2600 | 2600 | - | - | 5200 | 1300 | 5200 | 5800 | 420 | 1620 | 1800 | 2.3 | 7.4 | 8.2 | 3.21 | A |
| | 2500 | 3500 | - | - | 102% | 6000 | 2210 | 3090 | - | - | 5300 | 1300 | 5300 | 6400 | 430 | 1550 | 1840 | 2.3 | 7.1 | 8.4 | 3.42 | A |
| | 2500 | 5000 | - | - | 127% | 7500 | 1970 | 3930 | - | - | 5900 | 1380 | 5900 | 6800 | 430 | 1700 | 1880 | 2.3 | 7.8 | 8.6 | 3.47 | A |
| | 3500 | 3500 | - | - | 119% | 7000 | 2725 | 2725 | - | - | 5450 | 1300 | 5450 | 6560 | 430 | 1570 | 1850 | 2.3 | 7.2 | 8.5 | 3.47 | A |
| | 3500 | 5000 | - | - | 144% | 8500 | 2430 | 3470 | - | - | 5900 | 1380 | 5900 | 6800 | 440 | 1700 | 1880 | 2.4 | 7.8 | 8.6 | 3.47 | A |
| 3 Unit | 2500 | 2500 | 2500 | - | 127% | 7500 | 1960 | 1970 | 1970 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1600 | 1880 | 2.4 | 7.3 | 8.6 | 3.69 | A |
| | 2500 | 2500 | 3500 | - | 144% | 8500 | 1740 | 1740 | 2420 | - | 5900 | 1700 | 5900 | 6800 | 440 | 1600 | 1880 | 2.4 | 7.3 | 8.6 | 3.69 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
 - 2500, 3500, 5000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 8.5 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 3200 | - | - | - | 51% | 3200 | 3300 | - | - | - | 3300 | 1300 | 3300 | 3340 | 350 | 1150 | 1360 | 1.9 | 5.3 | 6.2 | 2.87 | D |
| | 4000 | - | - | - | 63% | 4000 | 4000 | - | - | - | 4000 | 1300 | 4000 | 4370 | 350 | 1350 | 1780 | 1.9 | 6.2 | 8.1 | 2.96 | D |
| | 6000 | - | - | - | 95% | 6000 | 5600 | - | - | - | 5600 | 1350 | 5600 | 6300 | 350 | 1820 | 2050 | 1.9 | 8.3 | 9.4 | 3.08 | D |
| 2 Unit | 3200 | 3200 | - | - | 102% | 6400 | 2900 | 2900 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1700 | 2040 | 1.9 | 7.8 | 9.3 | 3.41 | B |
| | 3200 | 4000 | - | - | 114% | 7200 | 2580 | 3220 | - | - | 5800 | 1400 | 5800 | 6300 | 350 | 1700 | 2040 | 1.9 | 7.8 | 9.3 | 3.41 | B |
| | 3200 | 6000 | - | - | 146% | 9200 | 2190 | 4110 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1960 | 1.9 | 8.0 | 9.0 | 3.62 | A |
| | 4000 | 4000 | - | - | 127% | 8000 | 2950 | 2950 | - | - | 5900 | 1400 | 5900 | 6880 | 350 | 1730 | 1990 | 1.9 | 7.9 | 9.1 | 3.41 | B |
| | 4000 | 6000 | - | - | 159% | 10000 | 2520 | 3780 | - | - | 6300 | 1400 | 6300 | 7300 | 350 | 1740 | 1960 | 1.9 | 8.0 | 9.0 | 3.62 | A |
| 3 Unit | 3200 | 3200 | 3200 | - | 152% | 9600 | 2100 | 2100 | 2100 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1650 | 1960 | 1.9 | 7.6 | 9.0 | 3.82 | A |
| | 3200 | 3200 | 4000 | - | 165% | 10400 | 1940 | 1940 | 2420 | - | 6300 | 1400 | 6300 | 7300 | 350 | 1400 | 1960 | 1.9 | 6.4 | 9.0 | 4.50 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
 - 3200, 4000, 6000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.4 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Neo Forte & Crystal

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 29% | 2000 | 2400 | - | - | - | 2400 | 1350 | 2400 | 3000 | 380 | 780 | 950 | 1.7 | 3.6 | 4.3 | 3.08 | B |
| | 2600 | - | - | - | 37% | 2600 | 2600 | - | - | - | 2600 | 1350 | 2600 | 3480 | 390 | 840 | 1100 | 1.8 | 3.8 | 5.0 | 3.10 | B |
| | 3500 | - | - | - | 50% | 3500 | 3500 | - | - | - | 3500 | 1350 | 3500 | 4200 | 400 | 1130 | 1580 | 1.8 | 5.2 | 7.2 | 3.10 | B |
| | 5200 | - | - | - | 74% | 5200 | 5200 | - | - | - | 5200 | 1400 | 5200 | 6240 | 420 | 1520 | 2160 | 1.9 | 7.0 | 9.9 | 3.42 | A |
| 2 Unit | 2000 | 2000 | - | - | 57% | 4000 | 2000 | 2000 | - | - | 4000 | 1500 | 4000 | 4800 | 410 | 1240 | 1490 | 1.9 | 5.7 | 6.8 | 3.23 | A |
| | 2000 | 2600 | - | - | 66% | 4600 | 2000 | 2600 | - | - | 4600 | 1690 | 4600 | 5520 | 420 | 1430 | 1720 | 1.9 | 6.5 | 7.9 | 3.22 | A |
| | 2000 | 3500 | - | - | 79% | 5500 | 2000 | 3500 | - | - | 5500 | 1770 | 5500 | 6600 | 430 | 1710 | 2050 | 2 | 7.8 | 9.4 | 3.22 | A |
| | 2000 | 5200 | - | - | 103% | 7200 | 1940 | 5060 | - | - | 7000 | 1900 | 7000 | 8400 | 580 | 2180 | 2520 | 2.7 | 10.0 | 11.5 | 3.21 | A |
| | 2600 | 2600 | - | - | 74% | 5200 | 2600 | 2600 | - | - | 5200 | 1750 | 5200 | 6240 | 420 | 1660 | 2000 | 1.9 | 7.6 | 9.2 | 3.13 | B |
| | 2600 | 3500 | - | - | 87% | 6100 | 2600 | 3500 | - | - | 6100 | 1820 | 6100 | 7320 | 440 | 1880 | 2260 | 2 | 8.6 | 10.3 | 3.24 | A |
| | 2600 | 5200 | - | - | 111% | 7800 | 2330 | 4670 | - | - | 7000 | 1900 | 7000 | 8400 | 580 | 2180 | 2540 | 2.7 | 10.0 | 11.6 | 3.21 | A |
| | 3500 | 3500 | - | - | 100% | 7000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8000 | 580 | 2490 | 2620 | 2.7 | 11.4 | 12.0 | 2.81 | C |
| | 3500 | 5200 | - | - | 124% | 8700 | 2820 | 4180 | - | - | 7000 | 1900 | 7000 | 8900 | 580 | 2110 | 2540 | 2.7 | 9.7 | 11.6 | 3.32 | A |
| | 5200 | 5200 | - | - | 149% | 10400 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8900 | 580 | 2000 | 2540 | 2.7 | 9.2 | 11.6 | 3.50 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 86% | 6000 | 2000 | 2000 | 2000 | - | 6000 | 1810 | 6000 | 7200 | 440 | 1800 | 2280 | 2 | 8.2 | 10.4 | 3.33 | A |
| | 2000 | 2000 | 2600 | - | 94% | 6600 | 2000 | 2000 | 2600 | - | 6600 | 1870 | 6600 | 7920 | 440 | 1830 | 2460 | 2 | 8.4 | 11.3 | 3.61 | A |
| | 2000 | 2000 | 3500 | - | 107% | 7500 | 1780 | 1780 | 3120 | - | 6680 | 1900 | 6680 | 8020 | 580 | 1835 | 2410 | 2.7 | 8.4 | 11.0 | 3.64 | A |
| | 2000 | 2000 | 5200 | - | 131% | 9200 | 1520 | 1520 | 3960 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.78 | A |
| | 2000 | 2600 | 2600 | - | 103% | 7200 | 1850 | 2400 | 2400 | - | 6650 | 1900 | 6650 | 7980 | 580 | 1830 | 2410 | 2.7 | 8.4 | 11.0 | 3.63 | A |
| | 2000 | 2600 | 3500 | - | 116% | 8100 | 1670 | 2170 | 2900 | - | 6740 | 1900 | 6740 | 8080 | 580 | 1840 | 2460 | 2.7 | 8.4 | 11.3 | 3.66 | A |
| | 2000 | 2600 | 5200 | - | 140% | 9800 | 1430 | 1860 | 3710 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 2000 | 3500 | 3500 | - | 129% | 9000 | 1520 | 2650 | 2650 | - | 6820 | 1900 | 6820 | 8180 | 580 | 1850 | 2510 | 2.7 | 8.5 | 11.5 | 3.69 | A |
| | 2000 | 3500 | 5200 | - | 153% | 10700 | 1310 | 2290 | 3400 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1930 | 2510 | 2.7 | 8.8 | 11.5 | 3.63 | A |
| | 2600 | 2600 | 2600 | - | 111% | 7800 | 2240 | 2240 | 2240 | - | 6720 | 1900 | 6720 | 8050 | 580 | 1840 | 2420 | 2.7 | 8.4 | 11.1 | 3.65 | A |
| | 2600 | 2600 | 3500 | - | 124% | 8700 | 2030 | 2030 | 2730 | - | 6790 | 1900 | 6790 | 8150 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.67 | A |
| | 2600 | 2600 | 5200 | - | 149% | 10400 | 1750 | 1750 | 3500 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2510 | 2.7 | 8.6 | 11.5 | 3.72 | A |
| | 2600 | 3500 | 3500 | - | 137% | 9600 | 1900 | 2550 | 2550 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 3500 | 3500 | 3500 | - | 150% | 10500 | 2330 | 2330 | 2330 | - | 6990 | 1900 | 6990 | 8900 | 580 | 1900 | 2510 | 2.7 | 8.7 | 11.5 | 3.68 | A |
| 4 Unit | 2000 | 2000 | 2000 | 2000 | 114% | 8000 | 1680 | 1680 | 1680 | 1680 | 6720 | 1900 | 6720 | 8070 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.63 | A |
| | 2000 | 2000 | 2000 | 2600 | 123% | 8600 | 1580 | 1580 | 1580 | 2040 | 6780 | 1900 | 6780 | 8140 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.61 | A |
| | 2000 | 2000 | 2000 | 3500 | 136% | 9500 | 1470 | 1470 | 1470 | 2590 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2460 | 2.7 | 8.7 | 11.3 | 3.68 | A |
| | 2000 | 2000 | 2600 | 2600 | 131% | 9200 | 1520 | 1520 | 1980 | 1980 | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 2000 | 2000 | 2600 | 3500 | 144% | 10100 | 1390 | 1390 | 1800 | 2420 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2510 | 2.7 | 8.7 | 11.5 | 3.68 | A |
| | 2000 | 2600 | 2600 | 2600 | 140% | 9800 | 1420 | 1860 | 1860 | 1860 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2460 | 2.7 | 8.7 | 11.3 | 3.68 | A |
| | 2000 | 2600 | 2600 | 3500 | 153% | 10700 | 1310 | 1700 | 1700 | 2290 | 7000 | 1900 | 7000 | 8900 | 580 | 1930 | 2550 | 2.7 | 8.8 | 11.7 | 3.63 | A |
| | 2600 | 2600 | 2600 | 2600 | 149% | 10400 | 1750 | 1750 | 1750 | 1750 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2550 | 2.7 | 8.7 | 11.7 | 3.68 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
 - 2000, 2600, 3500, 5200W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.7 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ070F4HXEA

### Neo Forte & Crystal

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 26% | 2200 | 2500 | - | - | - | 2500 | 1790 | 2500 | 3220 | 580 | 950 | 1330 | 2.7 | 4.3 | 6.1 | 2.63 | E |
| | 2600 | - | - | - | 30% | 2600 | 2900 | - | - | - | 2900 | 1820 | 2900 | 3680 | 590 | 1100 | 1500 | 2.7 | 5.0 | 6.9 | 2.64 | E |
| | 3800 | - | - | - | 44% | 3800 | 3800 | - | - | - | 3800 | 1930 | 3800 | 4600 | 600 | 1250 | 1810 | 2.7 | 5.7 | 8.3 | 3.04 | D |
| | 5600 | - | - | - | 65% | 5600 | 5600 | - | - | - | 5600 | 2080 | 5600 | 6440 | 610 | 1670 | 2370 | 2.8 | 7.6 | 10.8 | 3.35 | C |
| 2 Unit | 2200 | 2200 | - | - | 51% | 4400 | 2200 | 2200 | - | - | 4400 | 1980 | 4400 | 5060 | 600 | 1220 | 1530 | 2.7 | 5.6 | 7.0 | 3.61 | A |
| | 2200 | 2900 | - | - | 59% | 5100 | 2200 | 2900 | - | - | 5100 | 2040 | 5100 | 5870 | 610 | 1410 | 1700 | 2.8 | 6.5 | 7.8 | 3.62 | A |
| | 2200 | 3800 | - | - | 70% | 6000 | 2200 | 3800 | - | - | 6000 | 2110 | 6000 | 6900 | 610 | 1760 | 2110 | 2.8 | 8.1 | 9.7 | 3.41 | B |
| | 2200 | 5600 | - | - | 91% | 7800 | 2200 | 5600 | - | - | 7800 | 2200 | 7800 | 9130 | 620 | 2160 | 2700 | 2.8 | 9.9 | 12.4 | 3.61 | A |
| | 2900 | 2900 | - | - | 67% | 5800 | 2900 | 2900 | - | - | 5800 | 2100 | 5800 | 6670 | 610 | 1600 | 1930 | 2.8 | 7.3 | 8.8 | 3.63 | A |
| | 2900 | 3800 | - | - | 78% | 6700 | 2900 | 3800 | - | - | 6700 | 2170 | 6700 | 8040 | 610 | 1940 | 2330 | 2.8 | 8.9 | 10.7 | 3.45 | B |
| | 2900 | 5600 | - | - | 99% | 8500 | 2660 | 5140 | - | - | 7800 | 2200 | 7800 | 9600 | 620 | 2160 | 2650 | 2.8 | 9.9 | 12.1 | 3.61 | A |
| | 3800 | 3800 | - | - | 88% | 7600 | 3800 | 3800 | - | - | 7600 | 2200 | 7600 | 9120 | 620 | 2180 | 2510 | 2.8 | 10.0 | 11.5 | 3.49 | B |
| | 3800 | 5600 | - | - | 109% | 9400 | 3280 | 4840 | - | - | 8120 | 2200 | 8120 | 9740 | 620 | 2250 | 2700 | 2.8 | 10.3 | 12.4 | 3.61 | A |
| | 5600 | 5600 | - | - | 130% | 11200 | 4250 | 4250 | - | - | 8500 | 2200 | 8500 | 10200 | 620 | 2250 | 2740 | 2.8 | 10.3 | 12.5 | 3.78 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 77% | 6600 | 2200 | 2200 | 2200 | - | 6600 | 2170 | 6600 | 7590 | 610 | 1830 | 2530 | 2.8 | 8.4 | 11.6 | 3.61 | A |
| | 2200 | 2200 | 2900 | - | 85% | 7300 | 2200 | 2200 | 2900 | - | 7300 | 2200 | 7300 | 8400 | 620 | 1880 | 2590 | 2.8 | 8.6 | 11.9 | 3.88 | A |
| | 2200 | 2200 | 3800 | - | 95% | 8200 | 2200 | 2200 | 3800 | - | 8200 | 2200 | 8200 | 9590 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.25 | A |
| | 2200 | 2200 | 5600 | - | 116% | 10000 | 1890 | 1890 | 4820 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1960 | 2700 | 2.8 | 9.0 | 12.4 | 4.39 | A |
| | 2200 | 2900 | 2900 | - | 93% | 8000 | 2200 | 2900 | 2900 | - | 8000 | 2200 | 8000 | 9360 | 620 | 1900 | 2620 | 2.8 | 8.7 | 12.0 | 4.21 | A |
| | 2200 | 2900 | 3800 | - | 103% | 8900 | 2040 | 2690 | 3530 | - | 8260 | 2200 | 8260 | 9670 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.28 | A |
| | 2200 | 2900 | 5600 | - | 124% | 10700 | 1770 | 2330 | 4500 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1970 | 2720 | 2.8 | 9.0 | 12.4 | 4.37 | A |
| | 2200 | 3800 | 3800 | - | 114% | 9800 | 1880 | 3230 | 3230 | - | 8340 | 2200 | 8340 | 9760 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.28 | A |
| | 2200 | 3800 | 5600 | - | 135% | 11600 | 1630 | 2820 | 4150 | - | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2900 | 2900 | 2900 | - | 101% | 8700 | 2750 | 2750 | 2750 | - | 8250 | 2200 | 8250 | 9650 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.27 | A |
| | 2900 | 2900 | 3800 | - | 112% | 9600 | 2520 | 2520 | 3290 | - | 8330 | 2200 | 8330 | 9740 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.27 | A |
| | 2900 | 2900 | 5600 | - | 133% | 11400 | 2190 | 2190 | 4220 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1980 | 2730 | 2.8 | 9.1 | 12.5 | 4.34 | A |
| | 2900 | 3800 | 3800 | - | 122% | 10500 | 2380 | 3110 | 3110 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1980 | 2730 | 2.8 | 9.1 | 12.5 | 4.34 | A |
| | 3800 | 3800 | 3800 | - | 133% | 11400 | 2860 | 2870 | 2870 | - | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| 4 Unit | 2200 | 2200 | 2200 | 2200 | 102% | 8800 | 2060 | 2060 | 2060 | 2070 | 8250 | 2200 | 8250 | 9660 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.27 | A |
| | 2200 | 2200 | 2200 | 2900 | 110% | 9500 | 1930 | 1930 | 1930 | 2530 | 8320 | 2200 | 8320 | 9730 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.27 | A |
| | 2200 | 2200 | 2200 | 3800 | 121% | 10400 | 1820 | 1820 | 1820 | 3140 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2200 | 2200 | 2900 | 2900 | 119% | 10200 | 1850 | 1850 | 2450 | 2450 | 8600 | 2200 | 8600 | 10300 | 620 | 1970 | 2720 | 2.8 | 9.0 | 12.4 | 4.37 | A |
| | 2200 | 2200 | 2900 | 3800 | 129% | 11100 | 1710 | 1710 | 2250 | 2930 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2200 | 2900 | 2900 | 2900 | 127% | 10900 | 1730 | 2290 | 2290 | 2290 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2200 | 2900 | 2900 | 3800 | 137% | 11800 | 1610 | 2110 | 2110 | 2770 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2900 | 2900 | 2900 | 2900 | 135% | 11600 | 2150 | 2150 | 2150 | 2150 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800, 5600W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 11.8 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Maldives P Series & Deluxe

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 29% | 2000 | 2200 | - | - | - | 2200 | 1350 | 2200 | 3000 | 380 | 780 | 950 | 1.7 | 3.6 | 4.3 | 2.82 | C |
| | 2500 | - | - | - | 36% | 2500 | 2500 | - | - | - | 2500 | 1350 | 2500 | 3480 | 390 | 840 | 1100 | 1.8 | 3.8 | 5.0 | 2.98 | C |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5000 | - | - | - | 71% | 5000 | 4500 | - | - | - | 4500 | 1400 | 4500 | 6240 | 420 | 1520 | 2180 | 1.9 | 7.0 | 9.9 | 3.22 | A |
| 2 Unit | 2000 | 2000 | - | - | 57% | 4000 | 2000 | 2000 | - | - | 4000 | 1500 | 4000 | 4800 | 410 | 1240 | 1490 | 1.9 | 5.7 | 6.8 | 3.23 | A |
| | 2000 | 2500 | - | - | 64% | 4500 | 2040 | 2560 | - | - | 4600 | 1690 | 4600 | 5520 | 420 | 1430 | 1720 | 1.9 | 6.5 | 7.9 | 3.22 | A |
| | 2000 | 3500 | - | - | 79% | 5500 | 2000 | 3500 | - | - | 5500 | 1770 | 5500 | 6600 | 430 | 1710 | 2050 | 2 | 7.8 | 9.4 | 3.22 | A |
| | 2000 | 5000 | - | - | 100% | 7000 | 2000 | 5000 | - | - | 7000 | 1900 | 7000 | 8400 | 580 | 2180 | 2520 | 2.7 | 10.0 | 11.5 | 3.21 | A |
| | 2500 | 2500 | - | - | 71% | 5000 | 2600 | 2600 | - | - | 5200 | 1750 | 5200 | 6240 | 420 | 1660 | 2000 | 1.9 | 7.6 | 9.2 | 3.13 | B |
| | 2500 | 3500 | - | - | 86% | 6000 | 2540 | 3560 | - | - | 6100 | 1820 | 6100 | 7320 | 440 | 1880 | 2260 | 2 | 8.6 | 10.3 | 3.24 | A |
| | 2500 | 5000 | - | - | 107% | 7500 | 2330 | 4670 | - | - | 7000 | 1900 | 7000 | 8400 | 580 | 2180 | 2540 | 2.7 | 10.0 | 11.6 | 3.21 | A |
| | 3500 | 3500 | - | - | 100% | 7000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8000 | 580 | 2490 | 2620 | 2.7 | 11.4 | 12.0 | 2.81 | C |
| | 3500 | 5000 | - | - | 121% | 8500 | 2880 | 4120 | - | - | 7000 | 1900 | 7000 | 8900 | 580 | 2110 | 2540 | 2.7 | 9.7 | 11.6 | 3.32 | A |
| | 5000 | 5000 | - | - | 143% | 10000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8900 | 580 | 2000 | 2540 | 2.7 | 9.2 | 11.6 | 3.50 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 86% | 6000 | 2000 | 2000 | 2000 | - | 6000 | 1810 | 6000 | 7200 | 440 | 1800 | 2280 | 2 | 8.2 | 10.4 | 3.33 | A |
| | 2000 | 2000 | 2500 | - | 93% | 6500 | 2030 | 2030 | 2540 | - | 6600 | 1870 | 6600 | 7920 | 440 | 1830 | 2460 | 2 | 8.4 | 11.3 | 3.61 | A |
| | 2000 | 2000 | 3500 | - | 107% | 7500 | 1780 | 1780 | 3120 | - | 6680 | 1900 | 6680 | 8020 | 580 | 1835 | 2410 | 2.7 | 8.4 | 11.0 | 3.64 | A |
| | 2000 | 2000 | 5000 | - | 129% | 9000 | 1560 | 1560 | 3880 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.78 | A |
| | 2000 | 2500 | 2500 | - | 100% | 7000 | 1910 | 2370 | 2370 | - | 6650 | 1900 | 6650 | 7980 | 580 | 1830 | 2410 | 2.7 | 8.4 | 11.0 | 3.63 | A |
| | 2000 | 2500 | 3500 | - | 114% | 8000 | 1690 | 2110 | 2940 | - | 6740 | 1900 | 6740 | 8080 | 580 | 1840 | 2460 | 2.7 | 8.4 | 11.3 | 3.66 | A |
| | 2000 | 2500 | 5000 | - | 136% | 9500 | 1480 | 1840 | 3680 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 2000 | 3500 | 3500 | - | 129% | 9000 | 1520 | 2650 | 2650 | - | 6820 | 1900 | 6820 | 8180 | 580 | 1850 | 2510 | 2.7 | 8.5 | 11.5 | 3.69 | A |
| | 2000 | 3500 | 5000 | - | 150% | 10500 | 1340 | 2330 | 3330 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1930 | 2510 | 2.7 | 8.8 | 11.5 | 3.63 | A |
| | 2500 | 2500 | 2500 | - | 107% | 7500 | 2240 | 2240 | 2240 | - | 6720 | 1900 | 6720 | 8050 | 580 | 1840 | 2420 | 2.7 | 8.4 | 11.1 | 3.65 | A |
| | 2500 | 2500 | 3500 | - | 121% | 8500 | 2000 | 2000 | 2790 | - | 6790 | 1900 | 6790 | 8150 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.67 | A |
| | 2500 | 2500 | 5000 | - | 143% | 10000 | 1750 | 1750 | 3500 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2510 | 2.7 | 8.6 | 11.5 | 3.72 | A |
| | 2500 | 3500 | 3500 | - | 136% | 9500 | 1840 | 2580 | 2580 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 3500 | 3500 | 3500 | - | 150% | 10500 | 2330 | 2330 | 2330 | - | 6990 | 1900 | 6990 | 8900 | 580 | 1900 | 2510 | 2.7 | 8.7 | 11.5 | 3.68 | A |
| 4 Unit | 2000 | 2000 | 2000 | 2000 | 114% | 8000 | 1680 | 1680 | 1680 | 1680 | 6720 | 1900 | 6720 | 8070 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.63 | A |
| | 2000 | 2000 | 2000 | 2500 | 121% | 8500 | 1600 | 1600 | 1600 | 1980 | 6780 | 1900 | 6780 | 8140 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.61 | A |
| | 2000 | 2000 | 2000 | 3500 | 136% | 9500 | 1470 | 1470 | 1470 | 2590 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2460 | 2.7 | 8.7 | 11.3 | 3.68 | A |
| | 2000 | 2000 | 2500 | 2500 | 129% | 9000 | 1560 | 1560 | 1940 | 1940 | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 2000 | 2000 | 2500 | 3500 | 143% | 10000 | 1400 | 1400 | 1750 | 2450 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2510 | 2.7 | 8.7 | 11.5 | 3.68 | A |
| | 2000 | 2500 | 2500 | 2500 | 136% | 9500 | 1480 | 1840 | 1840 | 1840 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2460 | 2.7 | 8.7 | 11.3 | 3.68 | A |
| | 2000 | 2500 | 2500 | 3500 | 150% | 10500 | 1330 | 1670 | 1670 | 2330 | 7000 | 1900 | 7000 | 8900 | 580 | 1930 | 2550 | 2.7 | 8.8 | 11.7 | 3.63 | A |
| | 2500 | 2500 | 2500 | 2500 | 143% | 10000 | 1750 | 1750 | 1750 | 1750 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2550 | 2.7 | 8.7 | 11.7 | 3.68 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500, 5000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.5 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ070F4HXEA

### Maldives P Series & Deluxe

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 26% | 2200 | 2200 | - | - | - | 2200 | 1790 | 2200 | 3220 | 580 | 950 | 1330 | 2.7 | 4.3 | 6.1 | 2.32 | G |
| | 3300 | - | - | - | 38% | 3300 | 3300 | - | - | - | 3300 | 1820 | 3300 | 3680 | 590 | 1150 | 1500 | 2.7 | 5.3 | 6.9 | 2.87 | D |
| | 4000 | - | - | - | 47% | 4000 | 4000 | - | - | - | 4000 | 1930 | 4000 | 4600 | 600 | 1300 | 1810 | 2.7 | 5.9 | 8.3 | 3.08 | D |
| | 6000 | - | - | - | 70% | 6000 | 6000 | - | - | - | 6000 | 2080 | 6000 | 6440 | 610 | 1750 | 2370 | 2.8 | 8.0 | 10.8 | 3.43 | B |
| 2 Unit | 2200 | 2200 | - | - | 51% | 4400 | 2200 | 2200 | - | - | 4400 | 1980 | 4400 | 5060 | 600 | 1220 | 1530 | 2.7 | 5.6 | 7.0 | 3.61 | A |
| | 2200 | 3300 | - | - | 64% | 5500 | 2040 | 3060 | - | - | 5100 | 2040 | 5100 | 5870 | 610 | 1410 | 1700 | 2.8 | 6.5 | 7.8 | 3.62 | A |
| | 2200 | 4000 | - | - | 72% | 6200 | 2130 | 3870 | - | - | 6000 | 2110 | 6000 | 6900 | 610 | 1760 | 2110 | 2.8 | 8.1 | 9.7 | 3.41 | B |
| | 2200 | 6000 | - | - | 95% | 8200 | 2090 | 5710 | - | - | 7800 | 2200 | 7800 | 9130 | 620 | 2160 | 2700 | 2.8 | 9.9 | 12.4 | 3.61 | A |
| | 3300 | 3300 | - | - | 77% | 6600 | 2900 | 2900 | - | - | 5800 | 2100 | 5800 | 6670 | 610 | 1600 | 1930 | 2.8 | 7.3 | 8.8 | 3.63 | A |
| | 3300 | 4000 | - | - | 85% | 7300 | 3030 | 3670 | - | - | 6700 | 2170 | 6700 | 8040 | 610 | 1940 | 2330 | 2.8 | 8.9 | 10.7 | 3.45 | B |
| | 3300 | 6000 | - | - | 108% | 9300 | 2770 | 5030 | - | - | 7800 | 2200 | 7800 | 9600 | 620 | 2160 | 2650 | 2.8 | 9.9 | 12.1 | 3.61 | A |
| | 4000 | 4000 | - | - | 93% | 8000 | 3800 | 3800 | - | - | 7600 | 2200 | 7600 | 9120 | 620 | 2180 | 2510 | 2.8 | 10.0 | 11.5 | 3.49 | B |
| | 4000 | 6000 | - | - | 116% | 10000 | 3250 | 4870 | - | - | 8120 | 2200 | 8120 | 9740 | 620 | 2250 | 2700 | 2.8 | 10.3 | 12.4 | 3.61 | A |
| | 6000 | 6000 | - | - | 140% | 12000 | 4250 | 4250 | - | - | 8500 | 2200 | 8500 | 10200 | 620 | 2250 | 2740 | 2.8 | 10.3 | 12.5 | 3.78 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 77% | 6600 | 2200 | 2200 | 2200 | - | 6600 | 2170 | 6600 | 7590 | 610 | 1830 | 2530 | 2.8 | 8.4 | 11.6 | 3.61 | A |
| | 2200 | 2200 | 3300 | - | 90% | 7700 | 2090 | 2090 | 3120 | - | 7300 | 2200 | 7300 | 8400 | 620 | 1880 | 2590 | 2.8 | 8.6 | 11.9 | 3.88 | A |
| | 2200 | 2200 | 4000 | - | 98% | 8400 | 2150 | 2150 | 3900 | - | 8200 | 2200 | 8200 | 9590 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.25 | A |
| | 2200 | 2200 | 6000 | - | 121% | 10400 | 1820 | 1820 | 4960 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1960 | 2700 | 2.8 | 9.0 | 12.4 | 4.39 | A |
| | 2200 | 3300 | 3300 | - | 102% | 8800 | 2000 | 3000 | 3000 | - | 8000 | 2200 | 8000 | 9360 | 620 | 1900 | 2620 | 2.8 | 8.7 | 12.0 | 4.21 | A |
| | 2200 | 3300 | 4000 | - | 110% | 9500 | 1910 | 2870 | 3480 | - | 8260 | 2200 | 8260 | 9670 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.28 | A |
| | 2200 | 3300 | 6000 | - | 134% | 11500 | 1650 | 2470 | 4480 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1970 | 2720 | 2.8 | 9.0 | 12.4 | 4.37 | A |
| | 2200 | 4000 | 4000 | - | 119% | 10200 | 1800 | 3270 | 3270 | - | 8340 | 2200 | 8340 | 9760 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.28 | A |
| | 2200 | 4000 | 6000 | - | 142% | 12200 | 1550 | 2820 | 4230 | - | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 3300 | 3300 | 3300 | - | 115% | 9900 | 2750 | 2750 | 2750 | - | 8250 | 2200 | 8250 | 9650 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.27 | A |
| | 3300 | 3300 | 4000 | - | 123% | 10600 | 2600 | 2600 | 3130 | - | 8330 | 2200 | 8330 | 9740 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.27 | A |
| | 3300 | 3300 | 6000 | - | 147% | 12600 | 2250 | 2250 | 4100 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1980 | 2730 | 2.8 | 9.1 | 12.5 | 4.34 | A |
| | 3300 | 4000 | 4000 | - | 131% | 11300 | 2520 | 3040 | 3040 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1980 | 2730 | 2.8 | 9.1 | 12.5 | 4.34 | A |
| | 4000 | 4000 | 4000 | - | 140% | 12000 | 2860 | 2870 | 2870 | - | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| 4 Unit | 2200 | 2200 | 2200 | 2200 | 102% | 8800 | 2060 | 2060 | 2060 | 2070 | 8250 | 2200 | 8250 | 9660 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.27 | A |
| | 2200 | 2200 | 2200 | 3300 | 115% | 9900 | 1850 | 1850 | 1850 | 2770 | 8320 | 2200 | 8320 | 9730 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.27 | A |
| | 2200 | 2200 | 2200 | 4000 | 123% | 10600 | 1790 | 1790 | 1790 | 3230 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2200 | 2200 | 3300 | 3300 | 128% | 11000 | 1720 | 1720 | 2580 | 2580 | 8600 | 2200 | 8600 | 10300 | 620 | 1970 | 2720 | 2.8 | 9.0 | 12.4 | 4.37 | A |
| | 2200 | 2200 | 3300 | 4000 | 136% | 11700 | 1620 | 1620 | 2430 | 2930 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2200 | 3300 | 3300 | 3300 | 141% | 12100 | 1550 | 2350 | 2350 | 2350 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 2200 | 3300 | 3300 | 4000 | 149% | 12800 | 1480 | 2220 | 2220 | 2680 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| | 3300 | 3300 | 3300 | 3300 | 153% | 13200 | 2150 | 2150 | 2150 | 2150 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000, 6000W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 13.2 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Jungfrau Y-series

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2500 | - | - | - | 36% | 2500 | 2500 | - | - | - | 2500 | 1350 | 2500 | 3480 | 390 | 840 | 1100 | 1.8 | 3.8 | 5.0 | 2.98 | C |
| | 3500 | - | - | - | 50% | 3500 | 3500 | - | - | - | 3500 | 1350 | 3500 | 4200 | 400 | 1130 | 1580 | 1.8 | 5.2 | 7.2 | 3.10 | B |
| | 5000 | - | - | - | 71% | 5000 | 4900 | - | - | - | 4900 | 1400 | 4900 | 6240 | 420 | 1520 | 2160 | 1.9 | 7.0 | 9.9 | 3.22 | A |
| 2 Unit | 2500 | 2500 | - | - | 71% | 5000 | 2600 | 2600 | - | - | 5200 | 1750 | 5200 | 6240 | 420 | 1660 | 2000 | 1.9 | 7.6 | 9.2 | 3.13 | B |
| | 2500 | 3500 | - | - | 86% | 6000 | 2540 | 3560 | - | - | 6100 | 1820 | 6100 | 7320 | 440 | 1880 | 2260 | 2 | 8.6 | 10.3 | 3.24 | A |
| | 2500 | 5000 | - | - | 107% | 7500 | 2330 | 4670 | - | - | 7000 | 1900 | 7000 | 8400 | 580 | 2180 | 2540 | 2.7 | 10.0 | 11.6 | 3.21 | A |
| | 3500 | 3500 | - | - | 100% | 7000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8000 | 580 | 2490 | 2620 | 2.7 | 11.4 | 12.0 | 2.81 | C |
| | 3500 | 5000 | - | - | 121% | 8500 | 2880 | 4120 | - | - | 7000 | 1900 | 7000 | 8900 | 580 | 2110 | 2540 | 2.7 | 9.7 | 11.6 | 3.32 | A |
| | 5000 | 5000 | - | - | 143% | 10000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8900 | 580 | 2080 | 2540 | 2.7 | 9.5 | 11.6 | 3.37 | A |
| 3 Unit | 2500 | 2500 | 2500 | - | 107% | 7500 | 2240 | 2240 | 2240 | - | 6720 | 1900 | 6720 | 8050 | 580 | 1840 | 2420 | 2.7 | 8.4 | 11.1 | 3.65 | A |
| | 2500 | 2500 | 3500 | - | 121% | 8500 | 2000 | 2000 | 2790 | - | 6790 | 1900 | 6790 | 8150 | 580 | 1850 | 2460 | 2.7 | 8.5 | 11.3 | 3.67 | A |
| | 2500 | 2500 | 5000 | - | 143% | 10000 | 1750 | 1750 | 3500 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2510 | 2.7 | 8.6 | 11.5 | 3.72 | A |
| | 2500 | 3500 | 3500 | - | 136% | 9500 | 1840 | 2580 | 2580 | - | 7000 | 1900 | 7000 | 8900 | 580 | 1880 | 2460 | 2.7 | 8.6 | 11.3 | 3.72 | A |
| | 3500 | 3500 | 3500 | - | 150% | 10500 | 2330 | 2330 | 2330 | - | 6990 | 1900 | 6990 | 8900 | 580 | 1900 | 2510 | 2.7 | 8.7 | 11.5 | 3.68 | A |
| 4 Unit | 2500 | 2500 | 2500 | 2500 | 143% | 10000 | 1750 | 1750 | 1750 | 1750 | 7000 | 1900 | 7000 | 8900 | 580 | 1900 | 2550 | 2.7 | 8.7 | 11.7 | 3.68 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2500, 3500, 5000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 10.5 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 4000 | - | - | - | 47% | 4000 | 4000 | - | - | - | 4000 | 1860 | 4000 | 4900 | 600 | 1300 | 1810 | 2.7 | 5.9 | 8.3 | 3.08 | D |
| | 6000 | - | - | - | 70% | 6000 | 6000 | - | - | - | 6000 | 2080 | 6000 | 6440 | 610 | 1750 | 2370 | 2.8 | 8.0 | 10.8 | 3.43 | B |
| 2 Unit | 3200 | 3200 | - | - | 74% | 6400 | 2900 | 2900 | - | - | 5800 | 2100 | 5800 | 6670 | 610 | 1600 | 1930 | 2.8 | 7.3 | 8.8 | 3.63 | A |
| | 3200 | 4000 | - | - | 84% | 7200 | 2980 | 3720 | - | - | 6700 | 2170 | 6700 | 8040 | 610 | 1940 | 2330 | 2.8 | 8.9 | 10.7 | 3.45 | B |
| | 3200 | 6000 | - | - | 107% | 9200 | 2710 | 5090 | - | - | 7800 | 2200 | 7800 | 9600 | 620 | 2160 | 2650 | 2.8 | 9.9 | 12.1 | 3.61 | A |
| | 4000 | 4000 | - | - | 93% | 8000 | 3800 | 3800 | - | - | 7600 | 2200 | 7600 | 9120 | 620 | 2180 | 2510 | 2.8 | 10.0 | 11.5 | 3.49 | B |
| | 4000 | 6000 | - | - | 116% | 10000 | 3250 | 4870 | - | - | 8120 | 2200 | 8120 | 9740 | 620 | 2250 | 2700 | 2.8 | 10.3 | 12.4 | 3.61 | A |
| | 6000 | 6000 | - | - | 140% | 12000 | 4250 | 4250 | - | - | 8500 | 2200 | 8500 | 10200 | 620 | 2340 | 2740 | 2.8 | 10.7 | 12.5 | 3.63 | A |
| 3 Unit | 3200 | 3200 | 3200 | - | 112% | 9600 | 2750 | 2750 | 2750 | - | 8250 | 2200 | 8250 | 9650 | 620 | 1930 | 2660 | 2.8 | 8.8 | 12.2 | 4.27 | A |
| | 3200 | 3200 | 4000 | - | 121% | 10400 | 2570 | 2570 | 3190 | - | 8330 | 2200 | 8330 | 9740 | 620 | 1950 | 2690 | 2.8 | 8.9 | 12.3 | 4.27 | A |
| | 3200 | 3200 | 6000 | - | 144% | 12400 | 2220 | 2220 | 4160 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1980 | 2730 | 2.8 | 9.1 | 12.5 | 4.34 | A |
| | 3200 | 4000 | 4000 | - | 130% | 11200 | 2460 | 3070 | 3070 | - | 8600 | 2200 | 8600 | 10300 | 620 | 1980 | 2730 | 2.8 | 9.1 | 12.5 | 4.34 | A |
| | 4000 | 4000 | 4000 | - | 140% | 12000 | 2860 | 2870 | 2870 | - | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |
| 4 Unit | 3200 | 3200 | 3200 | 3200 | 149% | 12800 | 2150 | 2150 | 2150 | 2150 | 8600 | 2200 | 8600 | 10300 | 620 | 2000 | 2760 | 2.8 | 9.2 | 12.6 | 4.30 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 3200, 4000, 6000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 12.8 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ080F4HXEA

### Neo Forte & Crystal

**COOLING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 25% | 2000 | 2400 | - | - | - | 2400 | 1470 | 2400 | 3000 | 380 | 780 | 950 | 1.7 | 3.6 | 4.3 | 3.08 | B |
| | 2600 | - | - | - | 33% | 2600 | 2600 | - | - | - | 2600 | 1520 | 2600 | 3480 | 390 | 840 | 1100 | 1.8 | 3.8 | 5.0 | 3.10 | B |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5200 | - | - | - | 65% | 5200 | 5200 | - | - | - | 5200 | 1750 | 5200 | 6940 | 420 | 1520 | 2190 | 1.9 | 7.0 | 9.9 | 3.42 | A |
| 2 Unit | 2000 | 2000 | - | - | 50% | 4000 | 2000 | 2000 | - | - | 4000 | 1640 | 4000 | 4800 | 410 | 1240 | 1490 | 1.9 | 5.7 | 6.8 | 3.23 | A |
| | 2000 | 2600 | - | - | 58% | 4600 | 2000 | 2600 | - | - | 4600 | 1690 | 4600 | 5520 | 420 | 1430 | 1720 | 1.9 | 6.5 | 7.9 | 3.22 | A |
| | 2000 | 3500 | - | - | 69% | 5500 | 2000 | 3500 | - | - | 5500 | 1770 | 5500 | 6600 | 430 | 1710 | 2050 | 2 | 7.8 | 9.4 | 3.22 | A |
| | 2000 | 5200 | - | - | 90% | 7200 | 2000 | 5200 | - | - | 7200 | 1900 | 7200 | 8640 | 580 | 2240 | 2690 | 2.7 | 10.3 | 12.3 | 3.21 | A |
| | 2600 | 2600 | - | - | 65% | 5200 | 2600 | 2600 | - | - | 5200 | 1750 | 5200 | 6240 | 420 | 1660 | 2000 | 1.9 | 7.6 | 9.2 | 3.13 | B |
| | 2600 | 3500 | - | - | 76% | 6100 | 2600 | 3500 | - | - | 6100 | 1820 | 6100 | 7320 | 440 | 1900 | 2260 | 2 | 8.7 | 10.3 | 3.21 | A |
| | 2600 | 5200 | - | - | 98% | 7800 | 2400 | 4800 | - | - | 7200 | 1900 | 7200 | 8640 | 580 | 2240 | 2690 | 2.7 | 10.3 | 12.3 | 3.21 | A |
| | 3500 | 3500 | - | - | 88% | 7000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8000 | 580 | 2490 | 2620 | 2.7 | 11.4 | 12.0 | 2.81 | C |
| | 3500 | 5200 | - | - | 109% | 8700 | 2960 | 4390 | - | - | 7350 | 1900 | 7350 | 8820 | 580 | 2290 | 2750 | 2.7 | 10.5 | 12.6 | 3.21 | A |
| | 5200 | 5200 | - | - | 130% | 10400 | 3825 | 3825 | - | - | 7650 | 1900 | 7650 | 9180 | 580 | 2380 | 2860 | 2.7 | 10.9 | 13.1 | 3.21 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 75% | 6000 | 2000 | 2000 | 2000 | - | 6000 | 1810 | 6000 | 7200 | 440 | 1850 | 2310 | 2 | 8.5 | 10.6 | 3.24 | A |
| | 2000 | 2000 | 2600 | - | 83% | 6600 | 2000 | 2000 | 2600 | - | 6600 | 1870 | 6600 | 7920 | 440 | 2000 | 2500 | 2 | 9.2 | 11.4 | 3.30 | A |
| | 2000 | 2000 | 3500 | - | 94% | 7500 | 2000 | 2000 | 3500 | - | 7500 | 1900 | 7500 | 9000 | 580 | 2220 | 2780 | 2.7 | 10.2 | 12.7 | 3.38 | A |
| | 2000 | 2000 | 5200 | - | 115% | 9200 | 1670 | 1670 | 4310 | - | 7650 | 1900 | 7650 | 9180 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.49 | A |
| | 2000 | 2600 | 2600 | - | 90% | 7200 | 2000 | 2600 | 2600 | - | 7200 | 1900 | 7200 | 8640 | 580 | 2150 | 2680 | 2.7 | 9.8 | 12.3 | 3.35 | A |
| | 2000 | 2600 | 3500 | - | 101% | 8100 | 1870 | 2420 | 3260 | - | 7550 | 1900 | 7550 | 9060 | 580 | 2150 | 2690 | 2.7 | 9.8 | 12.3 | 3.51 | A |
| | 2000 | 2600 | 5200 | - | 123% | 9800 | 1570 | 2050 | 4090 | - | 7710 | 1900 | 7710 | 9250 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.52 | A |
| | 2000 | 3500 | 3500 | - | 113% | 9000 | 1700 | 2970 | 2970 | - | 7640 | 1900 | 7640 | 9160 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.49 | A |
| | 2000 | 3500 | 5200 | - | 134% | 10700 | 1500 | 2620 | 3880 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 2600 | 2600 | 2600 | - | 98% | 7800 | 2510 | 2510 | 2510 | - | 7530 | 1900 | 7530 | 9030 | 580 | 2110 | 2640 | 2.7 | 9.7 | 12.1 | 3.57 | A |
| | 2600 | 2600 | 3500 | - | 109% | 8700 | 2280 | 2280 | 3050 | - | 7610 | 1900 | 7610 | 9130 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.56 | A |
| | 2600 | 2600 | 5200 | - | 130% | 10400 | 1940 | 1940 | 3880 | - | 7760 | 1900 | 7760 | 9300 | 580 | 2210 | 2780 | 2.7 | 10.1 | 12.7 | 3.51 | A |
| | 2600 | 3500 | 3500 | - | 120% | 9600 | 2090 | 2800 | 2800 | - | 7690 | 1900 | 7690 | 9230 | 580 | 2180 | 2730 | 2.7 | 10.0 | 12.5 | 3.53 | A |
| | 2600 | 3500 | 5200 | - | 141% | 11300 | 1840 | 2480 | 3680 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2870 | 2.7 | 10.3 | 13.1 | 3.54 | A |
| | 3500 | 3500 | 3500 | - | 131% | 10500 | 2660 | 2670 | 2670 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 3500 | 3500 | 5200 | - | 153% | 12200 | 2300 | 2300 | 3400 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |
| 4 Unit | 2000 | 2000 | 2000 | 2000 | 100% | 8000 | 1885 | 1890 | 1885 | 1890 | 7550 | 1900 | 7550 | 9050 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.53 | A |
| | 2000 | 2000 | 2000 | 2600 | 108% | 8600 | 1770 | 1770 | 1770 | 2290 | 7600 | 1900 | 7600 | 9120 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.55 | A |
| | 2000 | 2000 | 2000 | 3500 | 119% | 9500 | 1620 | 1620 | 1620 | 2820 | 7680 | 1900 | 7680 | 9220 | 580 | 2180 | 2730 | 2.7 | 10.0 | 12.5 | 3.52 | A |
| | 2000 | 2000 | 2000 | 5200 | 140% | 11200 | 1430 | 1430 | 1430 | 3710 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2000 | 2000 | 2600 | 2600 | 115% | 9200 | 1665 | 1665 | 2160 | 2160 | 7650 | 1900 | 7650 | 9180 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.49 | A |
| | 2000 | 2000 | 2600 | 3500 | 126% | 10100 | 1530 | 1530 | 1990 | 2680 | 7730 | 1900 | 7730 | 9280 | 580 | 2200 | 2780 | 2.7 | 10.1 | 12.7 | 3.51 | A |
| | 2000 | 2000 | 2600 | 5200 | 148% | 11800 | 1360 | 1360 | 1760 | 3520 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2000 | 2000 | 3500 | 3500 | 138% | 11000 | 1450 | 1450 | 2550 | 2550 | 8000 | 1900 | 8000 | 9300 | 580 | 2280 | 2870 | 2.7 | 10.4 | 13.1 | 3.51 | A |
| | 2000 | 2600 | 2600 | 2600 | 123% | 9800 | 1560 | 2050 | 2050 | 2050 | 7710 | 1900 | 7710 | 9250 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.52 | A |
| | 2000 | 2600 | 2600 | 3500 | 134% | 10700 | 1500 | 1940 | 1940 | 2620 | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 2000 | 2600 | 3500 | 3500 | 145% | 11600 | 1390 | 1790 | 2410 | 2410 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2600 | 2600 | 2600 | 2600 | 130% | 10400 | 1940 | 1940 | 1940 | 1940 | 7760 | 1900 | 7760 | 9300 | 580 | 2220 | 2780 | 2.7 | 10.2 | 12.7 | 3.50 | A |
| | 2600 | 2600 | 2600 | 3500 | 141% | 11300 | 1840 | 1840 | 1840 | 2480 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2600 | 2600 | 3500 | 3500 | 153% | 12200 | 1700 | 1700 | 2300 | 2300 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2600, 3500, 5200W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 12.2 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### Neo Forte & Crystal

**HEATING**

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 24% | 2200 | 2500 | - | - | - | 2500 | 1790 | 2500 | 3220 | 580 | 950 | 1330 | 2.7 | 4.3 | 6.1 | 2.63 | E |
| | 2900 | - | - | - | 31% | 2900 | 2900 | - | - | - | 2900 | 1820 | 2900 | 3680 | 590 | 1110 | 1500 | 2.7 | 5.1 | 6.9 | 2.61 | E |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 5800 | - | - | - | 60% | 5800 | 5800 | - | - | - | 5800 | 2090 | 5800 | 6440 | 610 | 1670 | 2370 | 2.8 | 7.6 | 10.8 | 3.35 | C |
| 2 Unit | 2200 | 2200 | - | - | 47% | 4400 | 2200 | 2200 | - | - | 4400 | 1980 | 4400 | 5060 | 600 | 1220 | 1530 | 2.7 | 5.6 | 7.0 | 3.61 | A |
| | 2200 | 2900 | - | - | 55% | 5100 | 2200 | 2900 | - | - | 5100 | 2040 | 5100 | 5870 | 610 | 1410 | 1700 | 2.8 | 6.5 | 7.8 | 3.62 | A |
| | 2200 | 3800 | - | - | 65% | 6000 | 2200 | 3800 | - | - | 6000 | 2110 | 6000 | 6900 | 610 | 1760 | 2110 | 2.8 | 8.1 | 9.7 | 3.41 | B |
| | 2200 | 5600 | - | - | 84% | 7800 | 2200 | 5600 | - | - | 7800 | 2200 | 7800 | 9130 | 620 | 2160 | 2580 | 2.8 | 9.9 | 11.8 | 3.61 | A |
| | 2900 | 2900 | - | - | 62% | 5800 | 2900 | 2900 | - | - | 5800 | 2100 | 5800 | 6670 | 610 | 1600 | 1930 | 2.8 | 7.3 | 8.8 | 3.63 | A |
| | 2900 | 3800 | - | - | 72% | 6700 | 2900 | 3800 | - | - | 6700 | 2170 | 6700 | 7710 | 610 | 1940 | 2330 | 2.8 | 8.9 | 10.7 | 3.45 | B |
| | 2900 | 5600 | - | - | 91% | 8500 | 2660 | 5140 | - | - | 7800 | 2200 | 7800 | 9360 | 620 | 2160 | 2600 | 2.8 | 9.9 | 11.9 | 3.61 | A |
| | 3800 | 3800 | - | - | 82% | 7600 | 3800 | 3800 | - | - | 7600 | 2200 | 7600 | 8740 | 620 | 2180 | 2510 | 2.8 | 10.0 | 11.5 | 3.49 | B |
| | 3800 | 5600 | - | - | 101% | 9400 | 3280 | 4840 | - | - | 8120 | 2200 | 8120 | 9500 | 620 | 2250 | 2650 | 2.8 | 10.3 | 12.1 | 3.61 | A |
| | 5600 | 5600 | - | - | 120% | 11200 | 4250 | 4250 | - | - | 8500 | 2200 | 8500 | 9950 | 620 | 2340 | 2750 | 2.8 | 10.7 | 12.6 | 3.63 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | 71% | 6600 | 2200 | 2200 | 2200 | - | 6600 | 2170 | 6600 | 7590 | 610 | 1830 | 2220 | 2.8 | 8.4 | 10.2 | 3.61 | A |
| | 2200 | 2200 | 2900 | - | 78% | 7300 | 2200 | 2200 | 2900 | - | 7300 | 2200 | 7300 | 8400 | 620 | 1950 | 2340 | 2.8 | 8.9 | 10.7 | 3.74 | A |
| | 2200 | 2200 | 3800 | - | 88% | 8200 | 2200 | 2200 | 3800 | - | 8200 | 2200 | 8200 | 9590 | 620 | 2150 | 2570 | 2.8 | 9.8 | 11.8 | 3.81 | A |
| | 2200 | 2200 | 5600 | - | 108% | 10000 | 1900 | 1900 | 4820 | - | 8620 | 2200 | 8620 | 10090 | 620 | 2140 | 2610 | 2.8 | 9.8 | 11.9 | 4.03 | A |
| | 2200 | 2900 | 2900 | - | 86% | 8000 | 2200 | 2900 | 2900 | - | 8000 | 2200 | 8000 | 9360 | 620 | 2080 | 2500 | 2.8 | 9.5 | 11.4 | 3.85 | A |
| | 2200 | 2900 | 3800 | - | 96% | 8900 | 2110 | 2780 | 3640 | - | 8530 | 2200 | 8530 | 9980 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.06 | A |
| | 2200 | 2900 | 5600 | - | 115% | 10700 | 1790 | 2350 | 4540 | - | 8680 | 2200 | 8680 | 10150 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.06 | A |
| | 2200 | 3800 | 3800 | - | 105% | 9800 | 1940 | 3330 | 3330 | - | 8600 | 2200 | 8600 | 10070 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.02 | A |
| | 2200 | 3800 | 5600 | - | 125% | 11600 | 1760 | 3050 | 4490 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.33 | A |
| | 2900 | 2900 | 2900 | - | 94% | 8700 | 2840 | 2840 | 2840 | - | 8520 | 2200 | 8520 | 9960 | 620 | 2090 | 2680 | 2.8 | 9.6 | 12.3 | 4.08 | A |
| | 2900 | 2900 | 3800 | - | 103% | 9600 | 2600 | 2600 | 3390 | - | 8590 | 2200 | 8590 | 10050 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.09 | A |
| | 2900 | 2900 | 5600 | - | 123% | 11400 | 2230 | 2230 | 4290 | - | 8750 | 2200 | 8750 | 10900 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.09 | A |
| | 2900 | 3800 | 3800 | - | 113% | 10500 | 2400 | 3130 | 3130 | - | 8660 | 2200 | 8660 | 10130 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.05 | A |
| | 2900 | 3800 | 5600 | - | 132% | 12300 | 2200 | 2870 | 4230 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.33 | A |
| | 3800 | 3800 | 3800 | - | 123% | 11400 | 2910 | 2910 | 2910 | - | 8730 | 2200 | 8730 | 10220 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.06 | A |
| | 3800 | 3800 | 5600 | - | 142% | 13200 | 2680 | 2680 | 3940 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.27 | A |
| 4 Unit | 2200 | 2200 | 2200 | 2200 | 95% | 8800 | 2130 | 2130 | 2130 | 2130 | 8520 | 2200 | 8520 | 9970 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.06 | A |
| | 2200 | 2200 | 2200 | 2900 | 102% | 9500 | 1990 | 1990 | 1990 | 2610 | 8580 | 2200 | 8580 | 10040 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.09 | A |
| | 2200 | 2200 | 2200 | 3800 | 112% | 10400 | 1830 | 1830 | 1830 | 3160 | 8650 | 2200 | 8650 | 10120 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.04 | A |
| | 2200 | 2200 | 2200 | 5600 | 131% | 12200 | 1680 | 1680 | 1680 | 4260 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |
| | 2200 | 2200 | 2900 | 2900 | 110% | 10200 | 1860 | 1860 | 2460 | 2460 | 8640 | 2200 | 8640 | 10100 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.04 | A |
| | 2200 | 2200 | 2900 | 3800 | 119% | 11100 | 1730 | 1730 | 2280 | 2970 | 8710 | 2200 | 8710 | 10190 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.07 | A |
| | 2200 | 2200 | 2900 | 5600 | 139% | 12900 | 1590 | 1590 | 2090 | 4030 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |
| | 2200 | 2200 | 3800 | 3800 | 129% | 12000 | 1610 | 1610 | 2780 | 2780 | 8780 | 2200 | 8780 | 10270 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.03 | A |
| | 2200 | 2900 | 2900 | 2900 | 117% | 10900 | 1760 | 2310 | 2310 | 2310 | 8690 | 2200 | 8690 | 10170 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.06 | A |
| | 2200 | 2900 | 2900 | 3800 | 127% | 11800 | 1640 | 2150 | 2150 | 2820 | 8760 | 2200 | 8760 | 10250 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.02 | A |
| | 2200 | 2900 | 3800 | 3800 | 137% | 12700 | 1620 | 2120 | 2780 | 2780 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |
| | 2900 | 2900 | 2900 | 2900 | 125% | 11600 | 2185 | 2190 | 2185 | 2190 | 8750 | 2200 | 8750 | 10240 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.09 | A |
| | 2900 | 2900 | 2900 | 3800 | 134% | 12500 | 2160 | 2160 | 2160 | 2820 | 9300 | 2200 | 9300 | 10900 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.27 | A |
| | 2900 | 2900 | 3800 | 3800 | 144% | 13400 | 2010 | 2010 | 2640 | 2640 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800, 5600W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 13.4 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## Maldives P Series & Deluxe

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | 25% | 2000 | 2200 | - | - | - | 2200 | 1470 | 2200 | 3000 | 380 | 780 | 950 | 1.7 | 3.6 | 4.3 | 2.82 | C |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 3500 | - | - | - | 44% | 3500 | 3500 | - | - | - | 3500 | 1650 | 3500 | 4200 | 400 | 1130 | 1590 | 1.8 | 5.2 | 7.2 | 3.10 | B |
| | | | | | | | | | | | | | | | | | | | | | | |
| | 6500 | - | - | - | 85% | 6500 | 6000 | - | - | - | 6000 | 1900 | 5000 | 6000 | 540 | 1990 | 2800 | 2.7 | 9.1 | 12.8 | 3.02 | B |
| 2 Unit | 2000 | 2000 | - | - | 50% | 4000 | 2000 | 2000 | - | - | 4000 | 1640 | 4000 | 4800 | 410 | 1240 | 1490 | 1.9 | 5.7 | 6.8 | 3.23 | A |
| | 2000 | 2500 | - | - | 56% | 4500 | 2040 | 2560 | - | - | 4600 | 1690 | 4600 | 5520 | 420 | 1430 | 1720 | 1.9 | 6.5 | 7.9 | 3.22 | A |
| | 2000 | 3500 | - | - | 69% | 5500 | 2000 | 3500 | - | - | 5500 | 1770 | 5500 | 6600 | 430 | 1710 | 2050 | 2 | 7.8 | 9.4 | 3.22 | A |
| | 2000 | 5000 | - | - | 88% | 7000 | 2060 | 5140 | - | - | 7200 | 1900 | 7200 | 8640 | 580 | 2240 | 2690 | 2.7 | 10.3 | 12.3 | 3.21 | A |
| | 2000 | 6800 | - | - | 110% | 8800 | 1690 | 5760 | - | - | 7450 | 1900 | 7450 | 8640 | 580 | 2350 | 2730 | 2.7 | 10.8 | 12.5 | 3.17 | B |
| | 2500 | 2500 | - | - | 63% | 5000 | 2600 | 2600 | - | - | 5200 | 1750 | 5200 | 6240 | 420 | 1660 | 2000 | 1.9 | 7.6 | 9.2 | 3.13 | B |
| | 2500 | 3500 | - | - | 75% | 6000 | 2540 | 3560 | - | - | 6100 | 1820 | 6100 | 7320 | 440 | 1900 | 2260 | 2 | 8.7 | 10.3 | 3.21 | A |
| | 2500 | 5000 | - | - | 94% | 7500 | 2400 | 4800 | - | - | 7200 | 1900 | 7200 | 8640 | 580 | 2240 | 2690 | 2.7 | 10.3 | 12.3 | 3.21 | A |
| | 2500 | 6800 | - | - | 116% | 9300 | 2030 | 5520 | - | - | 7550 | 1900 | 7550 | 8760 | 580 | 2380 | 2760 | 2.7 | 10.9 | 12.6 | 3.17 | B |
| | 3500 | 3500 | - | - | 88% | 7000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8000 | 580 | 2490 | 2620 | 2.7 | 11.4 | 12.0 | 2.81 | C |
| | 3500 | 5000 | - | - | 106% | 8500 | 3030 | 4320 | - | - | 7350 | 1900 | 7350 | 8820 | 580 | 2290 | 2750 | 2.7 | 10.5 | 12.6 | 3.21 | A |
| | 3500 | 6800 | - | - | 129% | 10300 | 2620 | 5080 | - | - | 7700 | 1900 | 7700 | 8930 | 580 | 2400 | 2780 | 2.7 | 11.0 | 12.7 | 3.21 | A |
| | 5000 | 5000 | - | - | 125% | 10000 | 3830 | 3830 | - | - | 7660 | 1900 | 7660 | 9180 | 580 | 2380 | 2860 | 2.7 | 10.9 | 13.1 | 3.22 | A |
| | 5000 | 6800 | - | - | 148% | 11800 | 3310 | 4490 | - | - | 7800 | 1900 | 7800 | 8970 | 580 | 2430 | 2820 | 2.7 | 11.1 | 12.9 | 3.21 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | 75% | 6000 | 2000 | 2000 | 2000 | - | 6000 | 1810 | 6000 | 7200 | 440 | 1850 | 2310 | 2 | 8.5 | 10.6 | 3.24 | A |
| | 2000 | 2000 | 2500 | - | 81% | 6500 | 2030 | 2030 | 2540 | - | 6600 | 1870 | 6600 | 7920 | 440 | 2000 | 2500 | 2 | 9.2 | 11.4 | 3.30 | A |
| | 2000 | 2000 | 3500 | - | 94% | 7500 | 2000 | 2000 | 3500 | - | 7500 | 1900 | 7500 | 9000 | 580 | 2220 | 2780 | 2.7 | 10.2 | 12.7 | 3.38 | A |
| | 2000 | 2000 | 5000 | - | 113% | 9000 | 1700 | 1700 | 4250 | - | 7650 | 1900 | 7650 | 9180 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.49 | A |
| | 2000 | 2000 | 6800 | - | 135% | 10800 | 1480 | 1480 | 5040 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2270 | 2870 | 2.7 | 10.4 | 13.1 | 3.52 | A |
| | 2000 | 2500 | 2500 | - | 88% | 7000 | 2060 | 2570 | 2570 | - | 7200 | 1900 | 7200 | 8640 | 580 | 2150 | 2680 | 2.7 | 9.8 | 12.3 | 3.35 | A |
| | 2000 | 2500 | 3500 | - | 100% | 8000 | 1890 | 2360 | 3300 | - | 7550 | 1900 | 7550 | 9060 | 580 | 2150 | 2690 | 2.7 | 9.8 | 12.3 | 3.51 | A |
| | 2000 | 2500 | 5000 | - | 119% | 9500 | 1620 | 2030 | 4060 | - | 7710 | 1900 | 7710 | 9250 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.52 | A |
| | 2000 | 2500 | 6800 | - | 141% | 11300 | 1420 | 1770 | 4810 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2270 | 2870 | 2.7 | 10.4 | 13.1 | 3.52 | A |
| | 2000 | 3500 | 3500 | - | 113% | 9000 | 1700 | 2970 | 2970 | - | 7640 | 1900 | 7640 | 9160 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.49 | A |
| | 2000 | 3500 | 5000 | - | 131% | 10500 | 1520 | 2670 | 3810 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 2000 | 5000 | 5000 | - | 150% | 12000 | 1340 | 3330 | 3330 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |
| | 2500 | 2500 | 2500 | - | 94% | 7500 | 2510 | 2510 | 2510 | - | 7530 | 1900 | 7530 | 9030 | 580 | 2110 | 2640 | 2.7 | 9.7 | 12.1 | 3.57 | A |
| | 2500 | 2500 | 3500 | - | 106% | 8500 | 2240 | 2240 | 3130 | - | 7610 | 1900 | 7610 | 9130 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.56 | A |
| | 2500 | 2500 | 5000 | - | 125% | 10000 | 1940 | 1940 | 3880 | - | 7760 | 1900 | 7760 | 9300 | 580 | 2210 | 2780 | 2.7 | 10.1 | 12.7 | 3.51 | A |
| | 2500 | 2500 | 6800 | - | 148% | 11800 | 1690 | 1690 | 4620 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |
| | 2500 | 3500 | 3500 | - | 119% | 9500 | 2030 | 2830 | 2830 | - | 7690 | 1900 | 7690 | 9230 | 580 | 2180 | 2730 | 2.7 | 10.0 | 12.5 | 3.53 | A |
| | 2500 | 3500 | 5000 | - | 138% | 11000 | 1820 | 2550 | 3630 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2870 | 2.7 | 10.3 | 13.1 | 3.54 | A |
| | 3500 | 3500 | 3500 | - | 131% | 10500 | 2670 | 2670 | 2660 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 3500 | 3500 | 5000 | - | 150% | 12000 | 2340 | 2340 | 3320 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |
| 4 Unit | 2000 | 2000 | 2000 | 2000 | 100% | 8000 | 1890 | 1890 | 1890 | 1890 | 7560 | 1900 | 7560 | 9050 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.53 | A |
| | 2000 | 2000 | 2000 | 2500 | 106% | 8500 | 1790 | 1790 | 1790 | 2230 | 7600 | 1900 | 7600 | 9120 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.55 | A |
| | 2000 | 2000 | 2000 | 3500 | 119% | 9500 | 1620 | 1620 | 1620 | 2820 | 7680 | 1900 | 7680 | 9220 | 580 | 2180 | 2730 | 2.7 | 10.0 | 12.5 | 3.52 | A |
| | 2000 | 2000 | 2000 | 5000 | 138% | 11000 | 1450 | 1450 | 1450 | 3650 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2000 | 2000 | 2500 | 2500 | 113% | 9000 | 1700 | 1700 | 2130 | 2130 | 7660 | 1900 | 7660 | 9180 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.50 | A |
| | 2000 | 2000 | 2500 | 3500 | 125% | 10000 | 1550 | 1550 | 1930 | 2700 | 7730 | 1900 | 7730 | 9280 | 580 | 2200 | 2780 | 2.7 | 10.1 | 12.7 | 3.51 | A |
| | 2000 | 2000 | 2500 | 5000 | 144% | 11500 | 1390 | 1390 | 1740 | 3480 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2000 | 2000 | 3500 | 3500 | 138% | 11000 | 1450 | 1450 | 2550 | 2550 | 8000 | 1900 | 8000 | 9300 | 580 | 2280 | 2870 | 2.7 | 10.4 | 13.1 | 3.51 | A |
| | 2000 | 2500 | 2500 | 2500 | 119% | 9500 | 1620 | 2030 | 2030 | 2030 | 7710 | 1900 | 7710 | 9250 | 580 | 2190 | 2730 | 2.7 | 10.0 | 12.5 | 3.52 | A |
| | 2000 | 2500 | 2500 | 3500 | 131% | 10500 | 1530 | 1900 | 1900 | 2670 | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 2000 | 2500 | 2500 | 5000 | 150% | 12000 | 1330 | 1670 | 1670 | 3330 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |
| | 2000 | 2500 | 3500 | 3500 | 144% | 11500 | 1400 | 1740 | 2430 | 2430 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2500 | 2500 | 2500 | 2500 | 125% | 10000 | 1940 | 1940 | 1940 | 1940 | 7760 | 1900 | 7760 | 9300 | 580 | 2220 | 2780 | 2.7 | 10.2 | 12.7 | 3.50 | A |
| | 2500 | 2500 | 2500 | 3500 | 138% | 11000 | 1820 | 1820 | 1820 | 2540 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2500 | 2500 | 3500 | 3500 | 150% | 12000 | 1670 | 1670 | 2330 | 2330 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500, 5000, 6800W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 12.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.



## Maldives P Series & Deluxe

### HEATING

| Outdoor unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | 24% | 2200 | 2200 | - | - | - | 2200 | 1790 | 2200 | 3220 | 580 | 950 | 1330 | 2.7 | 4.3 | 6.1 | 2.32 | G |
| | 3300 | - | - | - | 35% | 3300 | 3300 | - | - | - | 3300 | 1820 | 3300 | 3680 | 590 | 1150 | 1500 | 2.7 | 5.3 | 6.9 | 2.87 | D |
| | 4000 | - | - | - | 43% | 4000 | 4000 | - | - | - | 4000 | 1930 | 4000 | 4600 | 600 | 1300 | 1810 | 2.7 | 5.9 | 8.3 | 3.08 | D |
| | 6000 | - | - | - | 65% | 6000 | 6000 | - | - | - | 6000 | 2080 | 6000 | 6440 | 610 | 1750 | 2370 | 2.8 | 8.0 | 10.8 | 3.43 | B |
| | 7800 | - | - | - | 84% | 7800 | 7800 | - | - | - | 7800 | 2200 | 7800 | 8450 | 620 | 2250 | 2550 | 2.8 | 10.3 | 11.7 | 3.47 | B |
| 2 Unit | 2200 | 2200 | - | - | 47% | 4400 | 2200 | 2200 | - | - | 4400 | 1980 | 4400 | 5060 | 600 | 1220 | 1530 | 2.7 | 5.6 | 7.0 | 3.61 | A |
| | 2200 | 3300 | - | - | 59% | 5500 | 2040 | 3060 | - | - | 5100 | 2040 | 5100 | 5870 | 610 | 1410 | 1700 | 2.8 | 6.5 | 7.8 | 3.62 | A |
| | 2200 | 4000 | - | - | 67% | 6200 | 2130 | 3870 | - | - | 6000 | 2110 | 6000 | 6900 | 610 | 1760 | 2110 | 2.8 | 8.1 | 9.7 | 3.41 | B |
| | 2200 | 6000 | - | - | 88% | 8200 | 2090 | 5710 | - | - | 7800 | 2200 | 7800 | 9130 | 620 | 2160 | 2580 | 2.8 | 9.9 | 11.8 | 3.61 | A |
| | 2200 | 7800 | - | - | 108% | 10000 | 1790 | 6330 | - | - | 8120 | 2200 | 8120 | 9300 | 620 | 2250 | 2600 | 2.8 | 10.3 | 11.9 | 3.61 | A |
| | 3300 | 3300 | - | - | 71% | 6600 | 2900 | 2900 | - | - | 5800 | 2100 | 5800 | 6670 | 610 | 1600 | 1930 | 2.8 | 7.3 | 8.8 | 3.63 | A |
| | 3300 | 4000 | - | - | 78% | 7300 | 3030 | 3670 | - | - | 6700 | 2170 | 6700 | 7710 | 610 | 1940 | 2330 | 2.8 | 8.9 | 10.7 | 3.45 | B |
| | 3300 | 6000 | - | - | 100% | 9300 | 2770 | 5030 | - | - | 7800 | 2200 | 7800 | 9360 | 620 | 2160 | 2600 | 2.8 | 9.9 | 11.9 | 3.61 | A |
| | 3300 | 7800 | - | - | 119% | 11100 | 2480 | 5870 | - | - | 8350 | 2200 | 8350 | 9600 | 620 | 2340 | 2700 | 2.8 | 10.7 | 12.4 | 3.57 | B |
| | 4000 | 4000 | - | - | 86% | 8000 | 3800 | 3800 | - | - | 7600 | 2200 | 7600 | 8740 | 620 | 2180 | 2510 | 2.8 | 10.0 | 11.5 | 3.49 | B |
| | 4000 | 6000 | - | - | 108% | 10000 | 3250 | 4870 | - | - | 8120 | 2200 | 8120 | 9500 | 620 | 2250 | 2650 | 2.8 | 10.3 | 12.1 | 3.61 | A |
| | 4000 | 7800 | - | - | 127% | 11800 | 2860 | 5590 | - | - | 8450 | 2200 | 8450 | 9700 | 620 | 2380 | 2700 | 2.8 | 10.9 | 12.4 | 3.55 | B |
| | 6000 | 6000 | - | - | 129% | 12000 | 4250 | 4250 | - | - | 8500 | 2200 | 8500 | 9950 | 620 | 2340 | 2750 | 2.8 | 10.7 | 12.6 | 3.63 | A |
| | 6000 | 7800 | - | - | 148% | 13800 | 3760 | 4890 | - | - | 8650 | 2200 | 8650 | 9900 | 620 | 2420 | 2800 | 2.8 | 11.1 | 12.8 | 3.57 | B |
| 3 Unit | 2200 | 2200 | 2200 | - | 71% | 6600 | 2200 | 2200 | 2200 | - | 6600 | 2170 | 6600 | 7590 | 610 | 1830 | 2220 | 2.8 | 8.4 | 10.2 | 3.61 | A |
| | 2200 | 2200 | 3300 | - | 83% | 7700 | 2090 | 2090 | 3120 | - | 7300 | 2200 | 7300 | 8400 | 620 | 1950 | 2340 | 2.8 | 8.9 | 10.7 | 3.74 | A |
| | 2200 | 2200 | 4000 | - | 90% | 8400 | 2150 | 2150 | 3900 | - | 8200 | 2200 | 8200 | 9590 | 620 | 2150 | 2570 | 2.8 | 9.8 | 11.8 | 3.81 | A |
| | 2200 | 2200 | 6000 | - | 112% | 10400 | 1830 | 1830 | 4960 | - | 8620 | 2200 | 8620 | 10090 | 620 | 2140 | 2610 | 2.8 | 9.8 | 11.9 | 4.03 | A |
| | 2200 | 2200 | 7800 | - | 131% | 12200 | 1580 | 1580 | 5590 | - | 8750 | 2200 | 8750 | 10500 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.07 | A |
| | 2200 | 3300 | 3300 | - | 95% | 8800 | 2000 | 3000 | 3000 | - | 8000 | 2200 | 8000 | 9360 | 620 | 2080 | 2500 | 2.8 | 9.5 | 11.4 | 3.85 | A |
| | 2200 | 3300 | 4000 | - | 102% | 9500 | 1980 | 2960 | 3590 | - | 8530 | 2200 | 8530 | 9980 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.06 | A |
| | 2200 | 3300 | 6000 | - | 124% | 11500 | 1660 | 2490 | 4530 | - | 8680 | 2200 | 8680 | 10150 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.06 | A |
| | 2200 | 3300 | 7800 | - | 143% | 13300 | 1540 | 2310 | 5450 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2250 | 2820 | 2.8 | 10.3 | 12.9 | 4.13 | A |
| | 2200 | 4000 | 4000 | - | 110% | 10200 | 1860 | 3370 | 3370 | - | 8600 | 2200 | 8600 | 10070 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.02 | A |
| | 2200 | 4000 | 6000 | - | 131% | 12200 | 1580 | 2870 | 4300 | - | 8750 | 2200 | 8750 | 10500 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.07 | A |
| | 2200 | 6000 | 6000 | - | 153% | 14200 | 1440 | 3930 | 3930 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2250 | 2820 | 2.8 | 10.3 | 12.9 | 4.13 | A |
| | 3300 | 3300 | 3300 | - | 106% | 9900 | 2840 | 2840 | 2840 | - | 8520 | 2200 | 8520 | 9960 | 620 | 2090 | 2680 | 2.8 | 9.6 | 12.3 | 4.08 | A |
| | 3300 | 3300 | 4000 | - | 114% | 10600 | 2680 | 2680 | 3230 | - | 8590 | 2200 | 8590 | 10050 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.09 | A |
| | 3300 | 3300 | 6000 | - | 135% | 12600 | 2290 | 2290 | 4170 | - | 8750 | 2200 | 8750 | 10500 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.09 | A |
| | 3300 | 3300 | 7800 | - | 155% | 14400 | 2130 | 2130 | 5040 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2250 | 2820 | 2.8 | 10.3 | 12.9 | 4.13 | A |
| | 3300 | 4000 | 4000 | - | 122% | 11300 | 2540 | 3060 | 3060 | - | 8660 | 2200 | 8660 | 10130 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.05 | A |
| | 3300 | 4000 | 6000 | - | 143% | 13300 | 2310 | 2800 | 4190 | - | 9300 | 2200 | 9300 | 10500 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.33 | A |
| | 4000 | 4000 | 4000 | - | 129% | 12000 | 2910 | 2910 | 2910 | - | 8730 | 2200 | 8730 | 10220 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.06 | A |
| | 4000 | 4000 | 6000 | - | 151% | 14000 | 2660 | 2660 | 3980 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.27 | A |
| 4 Unit | 2200 | 2200 | 2200 | 2200 | 95% | 8800 | 2130 | 2130 | 2130 | 2130 | 8520 | 2200 | 8520 | 9970 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.06 | A |
| | 2200 | 2200 | 2200 | 3300 | 106% | 9900 | 1910 | 1910 | 1910 | 2850 | 8580 | 2200 | 8580 | 10040 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.09 | A |
| | 2200 | 2200 | 2200 | 4000 | 114% | 10600 | 1800 | 1800 | 1800 | 3250 | 8650 | 2200 | 8650 | 10120 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.04 | A |
| | 2200 | 2200 | 2200 | 6000 | 135% | 12600 | 1630 | 1630 | 1630 | 4410 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |
| | 2200 | 2200 | 3300 | 3300 | 118% | 11000 | 1730 | 1730 | 2590 | 2590 | 8640 | 2200 | 8640 | 10100 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.04 | A |
| | 2200 | 2200 | 3300 | 4000 | 126% | 11700 | 1640 | 1640 | 2460 | 2970 | 8710 | 2200 | 8710 | 10190 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.07 | A |
| | 2200 | 2200 | 3300 | 6000 | 147% | 13700 | 1490 | 1490 | 2240 | 4080 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |
| | 2200 | 2200 | 4000 | 4000 | 133% | 12400 | 1560 | 1560 | 2830 | 2830 | 8780 | 2200 | 8780 | 10270 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.03 | A |
| | 2200 | 3300 | 3300 | 3300 | 130% | 12100 | 1580 | 2370 | 2370 | 2370 | 8690 | 2200 | 8690 | 10170 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.06 | A |
| | 2200 | 3300 | 3300 | 4000 | 138% | 12800 | 1500 | 2260 | 2260 | 2740 | 8760 | 2200 | 8760 | 10250 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.02 | A |
| | 2200 | 3300 | 3300 | 5000 | 148% | 13800 | 1490 | 2220 | 2220 | 3370 | 9300 | 2200 | 9300 | 10900 | 620 | 2250 | 2820 | 2.8 | 10.3 | 12.9 | 4.13 | A |
| | 2200 | 3300 | 4000 | 4000 | 145% | 13500 | 1530 | 2270 | 2750 | 2750 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |
| | 3300 | 3300 | 3300 | 3300 | 142% | 13200 | 2185 | 2190 | 2185 | 2190 | 8750 | 2200 | 8750 | 10240 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.09 | A |
| | 3300 | 3300 | 3300 | 4000 | 149% | 13900 | 2210 | 2210 | 2210 | 2670 | 9300 | 2200 | 9300 | 10900 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.27 | A |
| | 3300 | 3300 | 4000 | 4000 | 157% | 14600 | 2100 | 2100 | 2550 | 2550 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000, 6000, 7800W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 14.6 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## Jungfrau Y-series

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | Cooling Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2500 | - | - | - | 31% | 2500 | 2500 | - | - | - | 2500 | 1520 | 2500 | 3480 | 390 | 840 | 1100 | 1.8 | 3.8 | 5.0 | 2.98 | C |
| | 3500 | - | - | - | 44% | 3500 | 3500 | - | - | - | 3500 | 1600 | 3500 | 4200 | 400 | 1130 | 1580 | 1.8 | 5.2 | 7.2 | 3.10 | B |
| | 5000 | - | - | - | 63% | 5000 | 4900 | - | - | - | 4900 | 1750 | 4900 | 6240 | 420 | 1520 | 2160 | 1.9 | 7.0 | 9.9 | 3.22 | A |
| 2 Unit | 2500 | 2500 | - | - | 63% | 5000 | 2600 | 2600 | - | - | 5200 | 1750 | 5200 | 6240 | 420 | 1660 | 2000 | 1.9 | 7.6 | 9.2 | 3.13 | B |
| | 2500 | 3500 | - | - | 75% | 6000 | 2540 | 3560 | - | - | 6100 | 1820 | 6100 | 7320 | 440 | 1900 | 2260 | 2 | 8.7 | 10.3 | 3.21 | A |
| | 2500 | 5000 | - | - | 94% | 7500 | 2400 | 4800 | - | - | 7200 | 1900 | 7200 | 8640 | 580 | 2240 | 2690 | 2.7 | 10.3 | 12.3 | 3.21 | A |
| | 3500 | 3500 | - | - | 88% | 7000 | 3500 | 3500 | - | - | 7000 | 1900 | 7000 | 8000 | 580 | 2490 | 2620 | 2.7 | 11.4 | 12.0 | 2.81 | C |
| | 3500 | 5000 | - | - | 106% | 8500 | 3030 | 4320 | - | - | 7350 | 1900 | 7350 | 8820 | 580 | 2290 | 2750 | 2.7 | 10.5 | 12.6 | 3.21 | A |
| | 5000 | 5000 | - | - | 125% | 10000 | 3825 | 3825 | - | - | 7650 | 1900 | 7650 | 9180 | 580 | 2380 | 2860 | 2.7 | 10.9 | 13.1 | 3.21 | A |
| 3 Unit | 2500 | 2500 | 2500 | - | 94% | 7500 | 2510 | 2510 | 2510 | - | 7530 | 1900 | 7530 | 9030 | 580 | 2110 | 2640 | 2.7 | 9.7 | 12.1 | 3.57 | A |
| | 2500 | 2500 | 3500 | - | 106% | 8500 | 2240 | 2240 | 3130 | - | 7610 | 1900 | 7610 | 9130 | 580 | 2140 | 2690 | 2.7 | 9.8 | 12.3 | 3.56 | A |
| | 2500 | 2500 | 5000 | - | 125% | 10000 | 1940 | 1940 | 3880 | - | 7760 | 1900 | 7760 | 9300 | 580 | 2210 | 2780 | 2.7 | 10.1 | 12.7 | 3.51 | A |
| | 2500 | 3500 | 3500 | - | 119% | 9500 | 2030 | 2830 | 2830 | - | 7690 | 1900 | 7690 | 9230 | 580 | 2180 | 2730 | 2.7 | 10.0 | 12.5 | 3.53 | A |
| | 2500 | 3500 | 5000 | - | 138% | 11000 | 1820 | 2550 | 3630 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2870 | 2.7 | 10.3 | 13.1 | 3.54 | A |
| | 3500 | 3500 | 3500 | - | 131% | 10500 | 2670 | 2670 | 2660 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2260 | 2820 | 2.7 | 10.3 | 12.9 | 3.54 | A |
| | 3500 | 3500 | 5000 | - | 150% | 12000 | 2330 | 2330 | 3340 | - | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |
| 4 Unit | 2500 | 2500 | 2500 | 2500 | 125% | 10000 | 1940 | 1940 | 1940 | 1940 | 7760 | 1900 | 7760 | 9300 | 580 | 2220 | 2780 | 2.7 | 10.2 | 12.7 | 3.50 | A |
| | 2500 | 2500 | 2500 | 3500 | 138% | 11000 | 1820 | 1820 | 1820 | 2540 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2870 | 2.7 | 10.5 | 13.1 | 3.48 | A |
| | 2500 | 2500 | 3500 | 3500 | 150% | 12000 | 1670 | 1670 | 2330 | 2330 | 8000 | 1900 | 8000 | 9300 | 580 | 2300 | 2910 | 2.7 | 10.5 | 13.3 | 3.48 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2500, 3500, 5000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 12.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

## Jungfrau Y-series

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | Heating Capacity (W) | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | % | Total | A | B | C | D | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 3200 | - | - | - | 34% | 3200 | 3300 | - | - | - | 3300 | 1820 | 3300 | 3680 | 590 | 1150 | 1500 | 2.7 | 5.3 | 6.9 | 2.87 | D |
| | 4000 | - | - | - | 43% | 4000 | 4000 | - | - | - | 4000 | 1930 | 4000 | 4600 | 600 | 1300 | 1810 | 2.7 | 5.9 | 8.3 | 3.08 | D |
| | 6000 | - | - | - | 65% | 6000 | 6000 | - | - | - | 6000 | 2080 | 6000 | 6440 | 610 | 1750 | 2370 | 2.8 | 8.0 | 10.8 | 3.43 | B |
| 2 Unit | 3200 | 3200 | - | - | 69% | 6400 | 2900 | 2900 | - | - | 5800 | 2100 | 5800 | 6670 | 610 | 1600 | 1930 | 2.8 | 7.3 | 8.8 | 3.63 | A |
| | 3200 | 4000 | - | - | 77% | 7200 | 2980 | 3720 | - | - | 6700 | 2170 | 6700 | 7710 | 610 | 1940 | 2330 | 2.8 | 8.9 | 10.7 | 3.45 | B |
| | 3200 | 6000 | - | - | 99% | 9200 | 2710 | 5090 | - | - | 7800 | 2200 | 7800 | 9360 | 620 | 2160 | 2600 | 2.8 | 9.9 | 11.9 | 3.61 | A |
| | 4000 | 4000 | - | - | 86% | 8000 | 3800 | 3800 | - | - | 7600 | 2200 | 7600 | 8740 | 620 | 2180 | 2510 | 2.8 | 10.0 | 11.5 | 3.49 | B |
| | 4000 | 6000 | - | - | 108% | 10000 | 3250 | 4870 | - | - | 8120 | 2200 | 8120 | 9500 | 620 | 2250 | 2650 | 2.8 | 10.3 | 12.1 | 3.61 | A |
| | 6000 | 6000 | - | - | 129% | 12000 | 4250 | 4250 | - | - | 8500 | 2200 | 8500 | 9950 | 620 | 2340 | 2750 | 2.8 | 10.7 | 12.6 | 3.63 | A |
| 3 Unit | 3200 | 3200 | 3200 | - | 103% | 9600 | 2840 | 2840 | 2840 | - | 8520 | 2200 | 8520 | 9960 | 620 | 2090 | 2680 | 2.8 | 9.6 | 12.3 | 4.08 | A |
| | 3200 | 3200 | 4000 | - | 112% | 10400 | 2650 | 2650 | 3290 | - | 8590 | 2200 | 8590 | 10050 | 620 | 2100 | 2690 | 2.8 | 9.6 | 12.3 | 4.09 | A |
| | 3200 | 3200 | 6000 | - | 133% | 12400 | 2260 | 2260 | 4230 | - | 8750 | 2200 | 8750 | 10900 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.09 | A |
| | 3200 | 4000 | 4000 | - | 120% | 11200 | 2480 | 3090 | 3090 | - | 8660 | 2200 | 8660 | 10130 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.05 | A |
| | 3200 | 4000 | 6000 | - | 142% | 13200 | 2250 | 2820 | 4230 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.33 | A |
| | 4000 | 4000 | 4000 | - | 129% | 12000 | 2910 | 2910 | 2910 | - | 8730 | 2200 | 8730 | 10220 | 620 | 2150 | 2750 | 2.8 | 9.8 | 12.6 | 4.06 | A |
| | 4000 | 4000 | 6000 | - | 151% | 14000 | 2660 | 2660 | 3980 | - | 9300 | 2200 | 9300 | 10900 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.27 | A |
| 4 Unit | 3200 | 3200 | 3200 | 3200 | 138% | 12800 | 2190 | 2190 | 2190 | 2190 | 8760 | 2200 | 8760 | 10240 | 620 | 2140 | 2740 | 2.8 | 9.8 | 12.5 | 4.09 | A |
| | 3200 | 3200 | 3200 | 4000 | 146% | 13600 | 2190 | 2190 | 2190 | 2730 | 9300 | 2200 | 9300 | 10900 | 620 | 2180 | 2790 | 2.8 | 10.0 | 12.8 | 4.27 | A |
| | 3200 | 3200 | 4000 | 4000 | 155% | 14400 | 2070 | 2070 | 2580 | 2580 | 9300 | 2200 | 9300 | 10900 | 620 | 2200 | 2820 | 2.8 | 10.1 | 12.9 | 4.23 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 3200, 4000, 6000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 7.5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 14.4 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## RJ100F5HXEA

Neo Forte & Crystal

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | - | 20% | 2000 | 2000 | - | - | - | - | 2000 | 1600 | 2000 | 3000 | 580 | 700 | 1010 | 2.7 | 3.2 | 4.6 | 2.86 | C |
| | 2600 | - | - | - | - | 26% | 2600 | 2600 | - | - | - | - | 2600 | 1600 | 2600 | 3630 | 580 | 910 | 1210 | 2.7 | 4.2 | 5.5 | 2.86 | C |
| | 3500 | - | - | - | - | 35% | 3500 | 3500 | - | - | - | - | 3500 | 1620 | 3500 | 4740 | 590 | 1070 | 1580 | 2.7 | 4.9 | 7.2 | 3.27 | A |
| | 5200 | - | - | - | - | 52% | 5200 | 5200 | - | - | - | - | 5200 | 1650 | 5200 | 6480 | 600 | 1670 | 2160 | 2.7 | 7.6 | 9.9 | 3.11 | B |
| 2 Unit | 2000 | 2000 | - | - | - | 40% | 4000 | 2000 | 2000 | - | - | - | 4000 | 1680 | 4000 | 4900 | 610 | 1290 | 1650 | 2.8 | 5.9 | 7.6 | 3.10 | B |
| | 2000 | 2600 | - | - | - | 46% | 4600 | 2000 | 2600 | - | - | - | 4600 | 1680 | 4600 | 5530 | 610 | 1430 | 1860 | 2.8 | 6.5 | 8.5 | 3.22 | A |
| | 2000 | 3500 | - | - | - | 55% | 5500 | 2000 | 3500 | - | - | - | 5500 | 1710 | 5500 | 6950 | 620 | 1780 | 2330 | 2.8 | 8.1 | 10.7 | 3.09 | B |
| | 2000 | 5200 | - | - | - | 72% | 7200 | 2000 | 5200 | - | - | - | 7200 | 2210 | 7200 | 8690 | 630 | 2240 | 2910 | 2.9 | 10.3 | 13.3 | 3.21 | A |
| | 2600 | 2600 | - | - | - | 52% | 5200 | 2600 | 2600 | - | - | - | 5200 | 1680 | 5200 | 6320 | 610 | 1630 | 2120 | 2.8 | 7.5 | 9.7 | 3.19 | B |
| | 2600 | 3500 | - | - | - | 61% | 6100 | 2600 | 3500 | - | - | - | 6100 | 1710 | 6100 | 7270 | 620 | 1880 | 2430 | 2.8 | 8.6 | 11.1 | 3.24 | A |
| | 2600 | 5200 | - | - | - | 78% | 7800 | 2600 | 5200 | - | - | - | 7800 | 2210 | 7800 | 9320 | 630 | 2380 | 3120 | 2.9 | 10.9 | 14.3 | 3.28 | A |
| | 3500 | 3500 | - | - | - | 70% | 7000 | 3500 | 3500 | - | - | - | 7000 | 2170 | 7000 | 8530 | 620 | 2180 | 2850 | 2.8 | 10.0 | 13.0 | 3.21 | A |
| | 3500 | 5200 | - | - | - | 87% | 8700 | 3240 | 4810 | - | - | - | 8050 | 2240 | 8050 | 9950 | 640 | 2540 | 3330 | 2.9 | 11.6 | 15.2 | 3.17 | B |
| | 5200 | 5200 | - | - | - | 104% | 10400 | 4310 | 4310 | - | - | - | 8620 | 2440 | 8620 | 10430 | 650 | 2700 | 3500 | 3 | 12.4 | 16.0 | 3.19 | B |
| 3 Unit | 2000 | 2000 | 2000 | - | - | 60% | 6000 | 2000 | 2000 | 2000 | - | - | 6000 | 1760 | 6000 | 7270 | 640 | 1900 | 2460 | 2.9 | 8.7 | 11.3 | 3.16 | B |
| | 2000 | 2000 | 2600 | - | - | 66% | 6600 | 2000 | 2000 | 2600 | - | - | 6600 | 1760 | 6600 | 7900 | 640 | 2050 | 2660 | 2.9 | 9.4 | 12.2 | 3.22 | A |
| | 2000 | 2000 | 3500 | - | - | 75% | 7500 | 2000 | 2000 | 3500 | - | - | 7500 | 2280 | 7500 | 8850 | 650 | 2300 | 2980 | 3 | 10.5 | 13.6 | 3.26 | A |
| | 2000 | 2000 | 5200 | - | - | 92% | 9200 | 1900 | 1900 | 4930 | - | - | 8730 | 2310 | 8730 | 10270 | 660 | 2660 | 3450 | 3 | 12.2 | 15.8 | 3.28 | A |
| | 2000 | 2600 | 2600 | - | - | 72% | 7200 | 2000 | 2600 | 2600 | - | - | 7200 | 2240 | 7200 | 8370 | 640 | 2150 | 2820 | 2.9 | 9.8 | 12.9 | 3.35 | A |
| | 2000 | 2600 | 3500 | - | - | 81% | 8100 | 2000 | 2600 | 3500 | - | - | 8100 | 2280 | 8100 | 9320 | 650 | 2400 | 3130 | 3 | 11.0 | 14.3 | 3.38 | A |
| | 2000 | 2600 | 5200 | - | - | 98% | 9800 | 1800 | 2340 | 4680 | - | - | 8820 | 2310 | 8820 | 10270 | 660 | 2660 | 3450 | 3 | 12.2 | 15.8 | 3.32 | A |
| | 2000 | 3500 | 3500 | - | - | 90% | 9000 | 1930 | 3380 | 3380 | - | - | 8690 | 2280 | 8690 | 10270 | 650 | 2650 | 3440 | 3 | 12.1 | 15.7 | 3.28 | A |
| | 2000 | 3500 | 5200 | - | - | 107% | 10700 | 1670 | 2930 | 4350 | - | - | 8950 | 2510 | 8950 | 10430 | 670 | 2710 | 3510 | 3.1 | 12.4 | 16.1 | 3.30 | A |
| | 2000 | 5200 | 5200 | - | - | 124% | 12400 | 1450 | 3770 | 3770 | - | - | 8990 | 2720 | 8990 | 10740 | 680 | 2780 | 3630 | 3.1 | 12.7 | 16.6 | 3.23 | A |
| | 2600 | 2600 | 2600 | - | - | 78% | 7800 | 2600 | 2600 | 2600 | - | - | 7800 | 2240 | 7800 | 8850 | 640 | 2300 | 2970 | 2.9 | 10.5 | 13.6 | 3.39 | A |
| | 2600 | 2600 | 3500 | - | - | 87% | 8700 | 2600 | 2600 | 3500 | - | - | 8700 | 2280 | 8700 | 9950 | 650 | 2550 | 3340 | 3 | 11.7 | 15.3 | 3.41 | A |
| | 2600 | 2600 | 5200 | - | - | 104% | 10400 | 2230 | 2230 | 4460 | - | - | 8920 | 2480 | 8920 | 10270 | 660 | 2660 | 3450 | 3 | 12.2 | 15.8 | 3.35 | A |
| | 2600 | 3500 | 3500 | - | - | 96% | 9600 | 2380 | 3200 | 3200 | - | - | 8780 | 2280 | 8780 | 10270 | 650 | 2650 | 3440 | 3 | 12.1 | 15.7 | 3.31 | A |
| | 2600 | 3500 | 5200 | - | - | 113% | 11300 | 2020 | 2710 | 4030 | - | - | 8760 | 2510 | 8760 | 10430 | 670 | 2710 | 3510 | 3.1 | 12.4 | 16.1 | 3.23 | A |
| | 2600 | 5200 | 5200 | - | - | 130% | 13000 | 1820 | 3640 | 3640 | - | - | 9100 | 2720 | 9100 | 10900 | 680 | 2830 | 3680 | 3.1 | 13.0 | 16.8 | 3.22 | A |
| | 3500 | 3500 | 3500 | - | - | 105% | 10500 | 2980 | 2980 | 2980 | - | - | 8940 | 2480 | 8940 | 10430 | 660 | 2700 | 3500 | 3 | 12.4 | 16.0 | 3.31 | A |
| | 3500 | 3500 | 5200 | - | - | 122% | 12200 | 2560 | 2560 | 3810 | - | - | 8930 | 2680 | 8930 | 10740 | 670 | 2770 | 3620 | 3.1 | 12.7 | 16.6 | 3.22 | A |
| | 3500 | 5200 | 5200 | - | - | 139% | 13900 | 2340 | 3470 | 3470 | - | - | 9280 | 3110 | 9280 | 11000 | 690 | 2880 | 3740 | 3.2 | 13.2 | 17.1 | 3.22 | A |
| | 5200 | 5200 | 5200 | - | - | 156% | 15600 | 3260 | 3270 | 3270 | - | - | 9800 | 3150 | 9800 | 11000 | 700 | 2850 | 3750 | 3.2 | 13.0 | 17.2 | 3.44 | A |
| 4 Unit | 2000 | 2000 | 2000 | 2000 | - | 80% | 8000 | 2000 | 2000 | 2000 | 2000 | - | 8000 | 2350 | 8000 | 9320 | 670 | 2420 | 3160 | 3.1 | 11.1 | 14.5 | 3.31 | A |
| | 2000 | 2000 | 2000 | 2600 | - | 86% | 8600 | 2000 | 2000 | 2000 | 2600 | - | 8600 | 2350 | 8600 | 9950 | 670 | 2570 | 3360 | 3.1 | 11.8 | 15.4 | 3.35 | A |
| | 2000 | 2000 | 2000 | 3500 | - | 95% | 9500 | 1850 | 1850 | 1850 | 3230 | - | 8780 | 2380 | 8780 | 10270 | 680 | 2670 | 3470 | 3.1 | 12.2 | 15.9 | 3.29 | A |
| | 2000 | 2000 | 2000 | 5200 | - | 112% | 11200 | 1560 | 1560 | 1560 | 4060 | - | 8740 | 2590 | 8740 | 10430 | 690 | 2740 | 3540 | 3.2 | 12.5 | 16.2 | 3.19 | B |
| | 2000 | 2000 | 2600 | 2600 | - | 92% | 9200 | 1900 | 1900 | 2470 | 2470 | - | 8740 | 2350 | 8740 | 10270 | 670 | 2670 | 3460 | 3.1 | 12.2 | 15.8 | 3.27 | A |
| | 2000 | 2000 | 2600 | 3500 | - | 101% | 10100 | 1760 | 1760 | 2280 | 3070 | - | 8870 | 2550 | 8870 | 10270 | 680 | 2670 | 3470 | 3.1 | 12.2 | 15.9 | 3.32 | A |
| | 2000 | 2000 | 2600 | 5200 | - | 118% | 11800 | 1500 | 1500 | 1950 | 3900 | - | 8850 | 2590 | 8850 | 10740 | 690 | 2790 | 3640 | 3.2 | 12.8 | 16.7 | 3.17 | B |
| | 2000 | 2000 | 3500 | 3500 | - | 110% | 11000 | 1580 | 1580 | 2770 | 2770 | - | 8700 | 2550 | 8700 | 10430 | 680 | 2730 | 3530 | 3.1 | 12.5 | 16.2 | 3.19 | B |
| | 2000 | 2000 | 3500 | 5200 | - | 127% | 12700 | 1420 | 1420 | 2490 | 3700 | - | 9030 | 2800 | 9030 | 10900 | 700 | 2840 | 3700 | 3.2 | 13.0 | 16.9 | 3.18 | B |
| | 2000 | 2000 | 5200 | 5200 | - | 144% | 14400 | 1300 | 1300 | 3390 | 3390 | - | 9380 | 3200 | 9380 | 11000 | 710 | 2900 | 3760 | 3.2 | 13.3 | 17.2 | 3.23 | A |
| | 2000 | 2600 | 2600 | 2600 | - | 98% | 9800 | 1800 | 2340 | 2340 | 2340 | - | 8820 | 2350 | 8820 | 10270 | 670 | 2670 | 3460 | 3.1 | 12.2 | 15.8 | 3.30 | A |
| | 2000 | 2600 | 2600 | 3500 | - | 107% | 10700 | 1670 | 2180 | 2180 | 2930 | - | 8960 | 2550 | 8960 | 10430 | 680 | 2720 | 3520 | 3.1 | 12.4 | 16.1 | 3.29 | A |
| | 2000 | 2600 | 2600 | 5200 | - | 124% | 12400 | 1450 | 1880 | 1880 | 3770 | - | 8980 | 2760 | 8980 | 10740 | 690 | 2790 | 3640 | 3.2 | 12.8 | 16.7 | 3.22 | A |
| | 2000 | 2600 | 3500 | 3500 | - | 116% | 11600 | 1520 | 1980 | 2660 | 2660 | - | 8820 | 2550 | 8820 | 10740 | 680 | 2780 | 3630 | 3.1 | 12.7 | 16.6 | 3.17 | B |
| | 2000 | 2600 | 3500 | 5200 | - | 133% | 13300 | 1380 | 1790 | 2410 | 3580 | - | 9160 | 3150 | 9160 | 10900 | 700 | 2840 | 3700 | 3.2 | 13.0 | 16.9 | 3.23 | A |
| | 2000 | 2600 | 5200 | 5200 | - | 150% | 15000 | 1300 | 1700 | 3400 | 3400 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2860 | 3760 | 3.2 | 13.1 | 17.2 | 3.43 | A |
| | 2000 | 3500 | 3500 | 3500 | - | 125% | 12500 | 1440 | 2520 | 2520 | 2520 | - | 9000 | 2760 | 9000 | 10900 | 690 | 2830 | 3690 | 3.2 | 13.0 | 16.9 | 3.18 | B |
| | 2000 | 3500 | 3500 | 5200 | - | 142% | 14200 | 1320 | 2300 | 2300 | 3420 | - | 9340 | 3150 | 9340 | 11000 | 700 | 2890 | 3750 | 3.2 | 13.2 | 17.2 | 3.23 | A |
| | 2000 | 3500 | 5200 | 5200 | - | 159% | 15900 | 1220 | 2160 | 3210 | 3210 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.37 | A |
| | 2600 | 2600 | 2600 | 2600 | - | 104% | 10400 | 2230 | 2230 | 2230 | 2230 | - | 8920 | 2510 | 8920 | 10270 | 670 | 2670 | 3460 | 3.1 | 12.2 | 15.8 | 3.34 | A |
| | 2600 | 2600 | 2600 | 3500 | - | 113% | 11300 | 2020 | 2020 | 2020 | 2720 | - | 8780 | 2550 | 8780 | 10430 | 680 | 2720 | 3520 | 3.1 | 12.4 | 16.1 | 3.23 | A |
| | 2600 | 2600 | 2600 | 5200 | - | 130% | 13000 | 1820 | 1820 | 1820 | 3640 | - | 9100 | 2760 | 9100 | 10900 | 690 | 2840 | 3690 | 3.2 | 13.0 | 16.9 | 3.20 | B |
| | 2600 | 2600 | 3500 | 3500 | - | 122% | 12200 | 1910 | 1910 | 2560 | 2560 | - | 8940 | 2720 | 8940 | 10740 | 680 | 2780 | 3630 | 3.1 | 12.7 | 16.6 | 3.22 | A |
| | 2600 | 2600 | 3500 | 5200 | - | 139% | 13900 | 1740 | 1740 | 2340 | 3480 | - | 9300 | 3150 | 9300 | 11000 | 700 | 2890 | 3750 | 3.2 | 13.2 | 17.2 | 3.22 | A |
| | 2600 | 2600 | 5200 | 5200 | - | 156% | 15600 | 1630 | 1630 | 3270 | 3270 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2860 | 3760 | 3.2 | 13.1 | 17.2 | 3.43 | A |
| | 2600 | 3500 | 3500 | 3500 | - | 131% | 13100 | 1810 | 2440 | 2440 | 2440 | - | 9130 | 3110 | 9130 | 10900 | 690 | 2830 | 3690 | 3.2 | 13.0 | 16.9 | 3.23 | A |
| | 2600 | 3500 | 3500 | 5200 | - | 148% | 14800 | 1660 | 2240 | 2240 | 3320 | - | 9460 | 3150 | 9460 | 11000 | 700 | 2850 | 3750 | 3.2 | 13.0 | 17.2 | 3.32 | A |
| | 2600 | 3500 | 5200 | 5200 | - | 165% | 16500 | 1540 | 2080 | 3090 | 3090 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.37 | A |
| | 3500 | 3500 | 3500 | 3500 | - | 140% | 14000 | 2330 | 2330 | 2330 | 2330 | - | 9320 | 3110 | 9320 | 11000 | 690 | 2880 | 3740 | 3.2 | 13.2 | 17.1 | 3.24 | A |
| | 3500 | 3500 | 3500 | 5200 | - | 157% | 15700 | 2180 | 2180 | 2180 | 3260 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2900 | 3760 | 3.2 | 13.3 | 17.2 | 3.38 | A |
| | 3500 | 3500 | 5200 | 5200 | - | 174% | 17400 | 1970 | 1970 | 2930 | 2930 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2960 | 3770 | 3.3 | 13.5 | 17.3 | 3.31 | A |

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 5 Unit | 2000 | 2000 | 2000 | 2000 | 2000 | 100% | 10000 | 1900 | 1900 | 1900 | 1900 | 1900 | 9500 | 2630 | 9500 | 10270 | 700 | 2700 | 3490 | 3.2 | 12.4 | 16.0 | 3.52 | A |
| | 2000 | 2000 | 2000 | 2000 | 2600 | 106% | 10600 | 1800 | 1800 | 1800 | 1800 | 2340 | 9540 | 2630 | 9540 | 10430 | 700 | 2750 | 3550 | 3.2 | 12.6 | 16.2 | 3.47 | A |
| | 2000 | 2000 | 2000 | 2000 | 3500 | 115% | 11500 | 1680 | 1680 | 1680 | 1680 | 2940 | 9660 | 2660 | 9660 | 10740 | 710 | 2800 | 3650 | 3.2 | 12.8 | 16.7 | 3.45 | A |
| | 2000 | 2000 | 2000 | 2000 | 5200 | 132% | 13200 | 1520 | 1520 | 1520 | 1520 | 3920 | 10000 | 3240 | 10000 | 10900 | 720 | 2870 | 3720 | 3.3 | 13.1 | 17.0 | 3.48 | A |
| | 2000 | 2000 | 2000 | 2600 | 2600 | 112% | 11200 | 1720 | 1720 | 1720 | 2230 | 2230 | 9620 | 2630 | 9620 | 10430 | 700 | 2750 | 3550 | 3.2 | 12.6 | 16.2 | 3.50 | A |
| | 2000 | 2000 | 2000 | 2600 | 3500 | 121% | 12100 | 1600 | 1600 | 1600 | 2080 | 2800 | 9680 | 2840 | 9680 | 10740 | 710 | 2800 | 3650 | 3.2 | 12.8 | 16.7 | 3.46 | A |
| | 2000 | 2000 | 2000 | 2600 | 5200 | 138% | 13800 | 1450 | 1450 | 1450 | 1880 | 3770 | 10000 | 3240 | 10000 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.44 | A |
| | 2000 | 2000 | 2000 | 3500 | 3500 | 130% | 13000 | 1540 | 1540 | 1540 | 2690 | 2690 | 10000 | 3200 | 10000 | 10900 | 710 | 2860 | 3710 | 3.2 | 13.1 | 17.0 | 3.50 | A |
| | 2000 | 2000 | 2000 | 3500 | 5200 | 147% | 14700 | 1360 | 1360 | 1360 | 2380 | 3540 | 10000 | 3290 | 10000 | 11000 | 730 | 2870 | 3780 | 3.3 | 13.1 | 17.3 | 3.48 | A |
| | 2000 | 2000 | 2000 | 5200 | 5200 | 164% | 16400 | 1220 | 1220 | 1220 | 3170 | 3170 | 10000 | 3330 | 10000 | 11000 | 740 | 2930 | 3790 | 3.4 | 13.4 | 17.3 | 3.41 | A |
| | 2000 | 2000 | 2600 | 2600 | 2600 | 118% | 11800 | 1640 | 1640 | 2130 | 2130 | 2130 | 9670 | 2630 | 9670 | 10740 | 700 | 2800 | 3650 | 3.2 | 12.8 | 16.7 | 3.45 | A |
| | 2000 | 2000 | 2600 | 2600 | 3500 | 127% | 12700 | 1570 | 1570 | 2050 | 2050 | 2760 | 10000 | 2840 | 10000 | 10900 | 710 | 2850 | 3710 | 3.2 | 13.0 | 17.0 | 3.51 | A |
| | 2000 | 2000 | 2600 | 2600 | 5200 | 144% | 14400 | 1390 | 1390 | 1810 | 1810 | 3600 | 10000 | 3240 | 10000 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.44 | A |
| | 2000 | 2000 | 2600 | 3500 | 3500 | 136% | 13600 | 1470 | 1470 | 1920 | 2570 | 2570 | 10000 | 3200 | 10000 | 11000 | 710 | 2900 | 3760 | 3.2 | 13.3 | 17.2 | 3.45 | A |
| | 2000 | 2000 | 2600 | 3500 | 5200 | 153% | 15300 | 1310 | 1310 | 1700 | 2290 | 3390 | 10000 | 3290 | 10000 | 11000 | 730 | 2870 | 3780 | 3.3 | 13.1 | 17.3 | 3.48 | A |
| | 2000 | 2000 | 2600 | 5200 | 5200 | 170% | 17000 | 1180 | 1180 | 1520 | 3060 | 3060 | 10000 | 3330 | 10000 | 11000 | 740 | 2980 | 3790 | 3.4 | 13.6 | 17.3 | 3.36 | A |
| | 2000 | 2000 | 3500 | 3500 | 3500 | 145% | 14500 | 1370 | 1370 | 2420 | 2420 | 2420 | 10000 | 3240 | 10000 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2000 | 2000 | 3500 | 3500 | 5200 | 162% | 16200 | 1230 | 1230 | 2160 | 2160 | 3220 | 10000 | 3290 | 10000 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.42 | A |
| | 2000 | 2600 | 2600 | 2600 | 2600 | 124% | 12400 | 1570 | 2040 | 2040 | 2040 | 2040 | 9730 | 2800 | 9730 | 10740 | 700 | 2800 | 3650 | 3.2 | 12.8 | 16.7 | 3.48 | A |
| | 2000 | 2600 | 2600 | 2600 | 3500 | 133% | 13300 | 1520 | 1950 | 1950 | 1950 | 2630 | 10000 | 3200 | 10000 | 10900 | 710 | 2850 | 3710 | 3.2 | 13.0 | 17.0 | 3.51 | A |
| | 2000 | 2600 | 2600 | 2600 | 5200 | 150% | 15000 | 1340 | 1730 | 1730 | 1730 | 3470 | 10000 | 3240 | 10000 | 11000 | 720 | 2870 | 3770 | 3.3 | 13.1 | 17.3 | 3.48 | A |
| | 2000 | 2600 | 2600 | 3500 | 3500 | 142% | 14200 | 1420 | 1830 | 1830 | 2460 | 2460 | 10000 | 3200 | 10000 | 11000 | 710 | 2900 | 3760 | 3.2 | 13.3 | 17.2 | 3.45 | A |
| | 2000 | 2600 | 2600 | 3500 | 5200 | 159% | 15900 | 1260 | 1640 | 1640 | 2200 | 3260 | 10000 | 3290 | 10000 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.42 | A |
| | 2000 | 2600 | 3500 | 3500 | 3500 | 151% | 15100 | 1320 | 1720 | 2320 | 2320 | 2320 | 10000 | 3240 | 10000 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2000 | 2600 | 3500 | 3500 | 5200 | 168% | 16800 | 1190 | 1550 | 2080 | 2080 | 3100 | 10000 | 3290 | 10000 | 11000 | 730 | 2970 | 3780 | 3.3 | 13.6 | 17.3 | 3.37 | A |
| | 2000 | 3500 | 3500 | 3500 | 3500 | 160% | 16000 | 1240 | 2190 | 2190 | 2190 | 2190 | 10000 | 3240 | 10000 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.44 | A |
| | 2600 | 2600 | 2600 | 2600 | 2600 | 130% | 13000 | 2000 | 2000 | 2000 | 2000 | 2000 | 10000 | 3000 | 10000 | 11000 | 700 | 2900 | 3700 | 3.2 | 13.3 | 16.9 | 3.45 | A |
| | 2600 | 2600 | 2600 | 2600 | 3500 | 139% | 13900 | 1870 | 1870 | 1870 | 1870 | 2520 | 10000 | 3200 | 10000 | 11000 | 710 | 2900 | 3760 | 3.2 | 13.3 | 17.2 | 3.45 | A |
| | 2600 | 2600 | 2600 | 2600 | 5200 | 156% | 15600 | 1670 | 1670 | 1670 | 1670 | 3320 | 10000 | 3240 | 10000 | 11000 | 720 | 2870 | 3770 | 3.3 | 13.1 | 17.3 | 3.48 | A |
| | 2600 | 2600 | 2600 | 3500 | 3500 | 148% | 14800 | 1760 | 1760 | 1760 | 2360 | 2360 | 10000 | 3200 | 10000 | 11000 | 710 | 2860 | 3760 | 3.2 | 13.1 | 17.2 | 3.50 | A |
| | 2600 | 2600 | 2600 | 3500 | 5200 | 165% | 16500 | 1580 | 1580 | 1580 | 2120 | 3140 | 10000 | 3290 | 10000 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.42 | A |
| | 2600 | 2600 | 3500 | 3500 | 3500 | 157% | 15700 | 1670 | 1670 | 2220 | 2220 | 2220 | 10000 | 3240 | 10000 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.44 | A |
| | 2600 | 2600 | 3500 | 3500 | 5200 | 174% | 17400 | 1490 | 1490 | 2010 | 2010 | 3000 | 10000 | 3290 | 10000 | 11000 | 730 | 2970 | 3780 | 3.3 | 13.6 | 17.3 | 3.37 | A |
| | 2600 | 3500 | 3500 | 3500 | 3500 | 166% | 16600 | 1560 | 2110 | 2110 | 2110 | 2110 | 10000 | 3240 | 10000 | 11000 | 720 | 2960 | 3770 | 3.3 | 13.5 | 17.3 | 3.38 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2600, 3500, 5200W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 17.4 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

Neo Forte & Crystal

## HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Heating Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | - | 18% | 2200 | 2200 | - | - | - | - | 2200 | 1160 | 2200 | 3160 | 430 | 900 | 1080 | 2 | 4.1 | 4.9 | 2.44 | F |
| | 2900 | - | - | - | - | 24% | 2900 | 2900 | - | - | - | - | 2900 | 1160 | 2900 | 4270 | 430 | 960 | 1150 | 2 | 4.4 | 5.3 | 3.02 | D |
| | 3800 | - | - | - | - | 32% | 3800 | 3800 | - | - | - | - | 3800 | 1190 | 3800 | 5210 | 440 | 1140 | 1410 | 2 | 5.2 | 6.5 | 3.33 | C |
| | 5600 | - | - | - | - | 47% | 5600 | 5600 | - | - | - | - | 5600 | 1220 | 5600 | 7430 | 450 | 1640 | 2010 | 2.1 | 7.5 | 9.2 | 3.41 | B |
| 2 Unit | 2200 | 2200 | - | - | - | 37% | 4400 | 2200 | 2200 | - | - | - | 4400 | 1240 | 4400 | 5530 | 460 | 1250 | 1520 | 2.1 | 5.7 | 7.0 | 3.52 | B |
| | 2200 | 2900 | - | - | - | 43% | 5100 | 2200 | 2900 | - | - | - | 5100 | 1240 | 5100 | 6790 | 460 | 1520 | 1850 | 2.1 | 7.0 | 8.5 | 3.36 | C |
| | 2200 | 3800 | - | - | - | 50% | 6000 | 2200 | 3800 | - | - | - | 6000 | 1270 | 6000 | 7580 | 470 | 1700 | 2060 | 2.2 | 7.8 | 9.4 | 3.53 | B |
| | 2200 | 5600 | - | - | - | 65% | 7800 | 2200 | 5600 | - | - | - | 7800 | 1300 | 7800 | 10110 | 480 | 2240 | 2750 | 2.2 | 10.3 | 12.6 | 3.48 | B |
| | 2900 | 2900 | - | - | - | 48% | 5800 | 2900 | 2900 | - | - | - | 5800 | 1240 | 5800 | 8220 | 460 | 1820 | 2230 | 2.1 | 8.3 | 10.2 | 3.19 | D |
| | 2900 | 3800 | - | - | - | 56% | 6700 | 2900 | 3800 | - | - | - | 6700 | 1270 | 6700 | 9010 | 470 | 2010 | 2440 | 2.2 | 9.2 | 11.2 | 3.33 | C |
| | 2900 | 5600 | - | - | - | 71% | 8500 | 2900 | 5600 | - | - | - | 8500 | 1300 | 8500 | 11690 | 480 | 2590 | 3160 | 2.2 | 11.9 | 14.5 | 3.28 | C |
| | 3800 | 3800 | - | - | - | 63% | 7600 | 3800 | 3800 | - | - | - | 7600 | 1270 | 7600 | 9800 | 470 | 2190 | 2650 | 2.2 | 10.0 | 12.1 | 3.47 | B |
| | 3800 | 5600 | - | - | - | 78% | 9400 | 3800 | 5600 | - | - | - | 9400 | 1470 | 9400 | 12320 | 490 | 2730 | 3330 | 2.2 | 12.5 | 15.2 | 3.44 | B |
| | 5600 | 5600 | - | - | - | 93% | 11200 | 4850 | 4850 | - | - | - | 9700 | 1650 | 9700 | 13110 | 500 | 2920 | 3560 | 2.3 | 13.4 | 16.3 | 3.32 | C |
| 3 Unit | 2200 | 2200 | 2200 | - | - | 55% | 6600 | 2200 | 2200 | 2200 | - | - | 6600 | 1320 | 6600 | 7580 | 490 | 1720 | 2090 | 2.2 | 7.9 | 9.6 | 3.84 | A |
| | 2200 | 2200 | 2900 | - | - | 61% | 7300 | 2200 | 2200 | 2900 | - | - | 7300 | 1320 | 7300 | 9010 | 490 | 2030 | 2460 | 2.2 | 9.3 | 11.3 | 3.60 | B |
| | 2200 | 2200 | 3800 | - | - | 68% | 8200 | 2200 | 2200 | 3800 | - | - | 8200 | 1350 | 8200 | 9800 | 500 | 2210 | 2680 | 2.3 | 10.1 | 12.3 | 3.71 | A |
| | 2200 | 2200 | 5600 | - | - | 83% | 10000 | 2120 | 2120 | 5400 | - | - | 9640 | 1530 | 9640 | 12170 | 510 | 2710 | 3320 | 2.3 | 12.4 | 15.2 | 3.56 | B |
| | 2200 | 2900 | 2900 | - | - | 67% | 8000 | 2200 | 2900 | 2900 | - | - | 8000 | 1320 | 8000 | 10740 | 490 | 2380 | 2920 | 2.2 | 10.9 | 13.4 | 3.36 | C |
| | 2200 | 2900 | 3800 | - | - | 74% | 8900 | 2200 | 2900 | 3800 | - | - | 8900 | 1350 | 8900 | 11380 | 500 | 2520 | 3090 | 2.3 | 11.5 | 14.1 | 3.53 | B |
| | 2200 | 2900 | 5600 | - | - | 89% | 10700 | 2000 | 2630 | 5080 | - | - | 9710 | 1530 | 9710 | 11850 | 510 | 2670 | 3230 | 2.3 | 12.2 | 14.8 | 3.64 | A |
| | 2200 | 3800 | 3800 | - | - | 82% | 9800 | 2200 | 3800 | 3800 | - | - | 9800 | 1500 | 9800 | 12170 | 500 | 2700 | 3310 | 2.3 | 12.4 | 15.1 | 3.63 | A |
| | 2200 | 3800 | 5600 | - | - | 97% | 11600 | 1860 | 3210 | 4730 | - | - | 9800 | 1720 | 9800 | 12170 | 520 | 2720 | 3320 | 2.4 | 12.4 | 15.2 | 3.60 | B |
| | 2200 | 5600 | 5600 | - | - | 112% | 13400 | 1640 | 4170 | 4170 | - | - | 9980 | 1860 | 9980 | 12320 | 530 | 2780 | 3380 | 2.4 | 12.7 | 15.5 | 3.59 | B |
| | 2900 | 2900 | 2900 | - | - | 73% | 8700 | 2900 | 2900 | 2900 | - | - | 8700 | 1470 | 8700 | 11850 | 490 | 2650 | 3210 | 2.2 | 12.1 | 14.7 | 3.28 | C |
| | 2900 | 2900 | 3800 | - | - | 80% | 9600 | 2900 | 2900 | 3800 | - | - | 9600 | 1500 | 9600 | 11530 | 500 | 2560 | 3140 | 2.3 | 11.7 | 14.4 | 3.75 | A |
| | 2900 | 2900 | 5600 | - | - | 95% | 11400 | 2490 | 2490 | 4800 | - | - | 9780 | 1680 | 9780 | 12320 | 510 | 2760 | 3360 | 2.3 | 12.6 | 15.4 | 3.54 | B |
| | 2900 | 3800 | 3800 | - | - | 88% | 10500 | 2680 | 3510 | 3510 | - | - | 9700 | 1500 | 9700 | 11850 | 500 | 2660 | 3220 | 2.3 | 12.2 | 14.7 | 3.65 | A |
| | 2900 | 3800 | 5600 | - | - | 103% | 12300 | 2330 | 3050 | 4490 | - | - | 9870 | 1820 | 9870 | 12170 | 520 | 2720 | 3320 | 2.4 | 12.4 | 15.2 | 3.63 | A |
| | 2900 | 5600 | 5600 | - | - | 118% | 14100 | 2060 | 3990 | 3990 | - | - | 10040 | 1860 | 10040 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.56 | B |
| | 3800 | 3800 | 3800 | - | - | 95% | 11400 | 3260 | 3260 | 3260 | - | - | 9780 | 1680 | 9780 | 12170 | 510 | 2710 | 3310 | 2.3 | 12.4 | 15.1 | 3.61 | A |
| | 3800 | 3800 | 5600 | - | - | 110% | 13200 | 2870 | 2870 | 4230 | - | - | 9970 | 1820 | 9970 | 12320 | 520 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.60 | B |
| | 3800 | 5600 | 5600 | - | - | 125% | 15000 | 2710 | 4000 | 4000 | - | - | 10710 | 2160 | 10710 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.73 | A |
| | 5600 | 5600 | 5600 | - | - | 140% | 16800 | 3670 | 3670 | 3670 | - | - | 11010 | 2200 | 11010 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.76 | A |
| 4 Unit | 2200 | 2200 | 2200 | 2200 | - | 73% | 8800 | 2200 | 2200 | 2200 | 2200 | - | 8800 | 1400 | 8800 | 9800 | 520 | 2240 | 2700 | 2.4 | 10.3 | 12.4 | 3.93 | A |
| | 2200 | 2200 | 2200 | 2900 | - | 79% | 9500 | 2200 | 2200 | 2200 | 2900 | - | 9500 | 1560 | 9500 | 11380 | 520 | 2550 | 3120 | 2.4 | 11.7 | 14.3 | 3.73 | A |
| | 2200 | 2200 | 2200 | 3800 | - | 87% | 10400 | 2050 | 2050 | 2050 | 3540 | - | 9690 | 1590 | 9690 | 12170 | 530 | 2730 | 3330 | 2.4 | 12.5 | 15.2 | 3.55 | B |
| | 2200 | 2200 | 2200 | 5600 | - | 102% | 12200 | 1780 | 1780 | 1780 | 4530 | - | 9870 | 1780 | 9870 | 12170 | 540 | 2740 | 3350 | 2.5 | 12.5 | 15.3 | 3.60 | B |
| | 2200 | 2200 | 2900 | 2900 | - | 85% | 10200 | 2090 | 2090 | 2750 | 2750 | - | 9680 | 1560 | 9680 | 11530 | 520 | 2590 | 3160 | 2.4 | 11.9 | 14.5 | 3.74 | A |
| | 2200 | 2200 | 2900 | 3800 | - | 93% | 11100 | 1930 | 1930 | 2550 | 3340 | - | 9750 | 1590 | 9750 | 11850 | 530 | 2680 | 3250 | 2.4 | 12.3 | 14.9 | 3.64 | A |
| | 2200 | 2200 | 2900 | 5600 | - | 108% | 12900 | 1690 | 1690 | 2230 | 4310 | - | 9920 | 1890 | 9920 | 12170 | 540 | 2740 | 3350 | 2.5 | 12.5 | 15.3 | 3.62 | A |
| | 2200 | 2200 | 3800 | 3800 | - | 100% | 12000 | 1800 | 1800 | 3120 | 3120 | - | 9840 | 1750 | 9840 | 12170 | 530 | 2730 | 3340 | 2.4 | 12.5 | 15.3 | 3.60 | B |
| | 2200 | 2200 | 3800 | 5600 | - | 115% | 13800 | 1600 | 1600 | 2760 | 4070 | - | 10030 | 1930 | 10030 | 12320 | 550 | 2790 | 3390 | 2.5 | 12.8 | 15.5 | 3.59 | B |
| | 2200 | 2200 | 5600 | 5600 | - | 130% | 15600 | 1520 | 1520 | 3870 | 3870 | - | 10780 | 2240 | 10780 | 12800 | 560 | 2890 | 3530 | 2.6 | 13.2 | 16.2 | 3.73 | A |
| | 2200 | 2900 | 2900 | 2900 | - | 91% | 10900 | 1960 | 2590 | 2590 | 2590 | - | 9730 | 1720 | 9730 | 12170 | 520 | 2720 | 3330 | 2.4 | 12.4 | 15.2 | 3.58 | B |
| | 2200 | 2900 | 2900 | 3800 | - | 98% | 11800 | 1830 | 2410 | 2410 | 3160 | - | 9810 | 1750 | 9810 | 12320 | 530 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.54 | B |
| | 2200 | 2900 | 2900 | 5600 | - | 113% | 13600 | 1620 | 2130 | 2130 | 4110 | - | 9990 | 1890 | 9990 | 12480 | 540 | 2830 | 3430 | 2.5 | 13.0 | 15.7 | 3.53 | B |
| | 2200 | 2900 | 3800 | 3800 | - | 106% | 12700 | 1720 | 2270 | 2970 | 2970 | - | 9930 | 1860 | 9930 | 12170 | 530 | 2730 | 3340 | 2.4 | 12.5 | 15.3 | 3.64 | A |
| | 2200 | 2900 | 3800 | 5600 | - | 121% | 14500 | 1620 | 2130 | 2790 | 4120 | - | 10660 | 1930 | 10660 | 12480 | 550 | 2840 | 3440 | 2.5 | 13.0 | 15.7 | 3.75 | A |
| | 2200 | 2900 | 5600 | 5600 | - | 136% | 16300 | 1460 | 1930 | 3720 | 3720 | - | 10830 | 2240 | 10830 | 12960 | 560 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.68 | A |
| | 2200 | 3800 | 3800 | 3800 | - | 113% | 13600 | 1620 | 2790 | 2790 | 2790 | - | 9990 | 1890 | 9990 | 12320 | 540 | 2780 | 3380 | 2.5 | 12.7 | 15.5 | 3.59 | B |
| | 2200 | 3800 | 3800 | 5600 | - | 128% | 15400 | 1540 | 2650 | 2650 | 3910 | - | 10750 | 2200 | 10750 | 12800 | 550 | 2880 | 3520 | 2.5 | 13.2 | 16.1 | 3.73 | A |
| | 2200 | 3800 | 5600 | 5600 | - | 143% | 17200 | 1410 | 2430 | 3580 | 3580 | - | 11000 | 2280 | 11000 | 12960 | 570 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.74 | A |
| | 2900 | 2900 | 2900 | 2900 | - | 97% | 11600 | 2450 | 2450 | 2450 | 2450 | - | 9800 | 1820 | 9800 | 12480 | 520 | 2810 | 3410 | 2.4 | 12.9 | 15.6 | 3.49 | B |
| | 2900 | 2900 | 2900 | 3800 | - | 104% | 12500 | 2290 | 2290 | 2290 | 3000 | - | 9870 | 1860 | 9870 | 12320 | 530 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.56 | B |
| | 2900 | 2900 | 2900 | 5600 | - | 119% | 14300 | 2040 | 2040 | 2040 | 3940 | - | 10060 | 2160 | 10060 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.51 | B |
| | 2900 | 2900 | 3800 | 3800 | - | 112% | 13400 | 2160 | 2160 | 2830 | 2830 | - | 9980 | 1860 | 9980 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.54 | B |
| | 2900 | 2900 | 3800 | 5600 | - | 127% | 15200 | 2050 | 2050 | 2680 | 3950 | - | 10730 | 2200 | 10730 | 12960 | 550 | 2920 | 3560 | 2.5 | 13.4 | 16.3 | 3.67 | A |
| | 2900 | 2900 | 5600 | 5600 | - | 142% | 17000 | 1880 | 1880 | 3620 | 3620 | - | 11000 | 2240 | 11000 | 13110 | 560 | 2980 | 3620 | 2.6 | 13.6 | 16.6 | 3.69 | A |
| | 2900 | 3800 | 3800 | 3800 | - | 119% | 14300 | 2040 | 2670 | 2670 | 2670 | - | 10050 | 1890 | 10050 | 12480 | 540 | 2830 | 3430 | 2.5 | 13.0 | 15.7 | 3.55 | B |
| | 2900 | 3800 | 3800 | 5600 | - | 134% | 16100 | 1950 | 2550 | 2550 | 3760 | - | 10810 | 2200 | 10810 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.69 | A |
| | 2900 | 3800 | 5600 | 5600 | - | 149% | 17900 | 1780 | 2340 | 3440 | 3440 | - | 11000 | 2280 | 11000 | 13110 | 570 | 2990 | 3620 | 2.6 | 13.7 | 16.6 | 3.68 | A |
| | 3800 | 3800 | 3800 | 3800 | - | 127% | 15200 | 2680 | 2680 | 2680 | 2680 | - | 10720 | 2160 | 10720 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.74 | A |
| | 3800 | 3800 | 3800 | 5600 | - | 142% | 17000 | 2460 | 2460 | 2460 | 3620 | - | 11000 | 2240 | 11000 | 12960 | 560 | 2930 | 3570 | 2.6 | 13.4 | 16.3 | 3.75 | A |
| | 3800 | 3800 | 5600 | 5600 | - | 157% | 18800 | 2220 | 2220 | 3280 | 3280 | - | 11000 | 2280 | 11000 | 13430 | 570 | 3040 | 3710 | 2.6 | 13.9 | 17.0 | 3.62 | A |

## HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 5 Unit | 2200 | 2200 | 2200 | 2200 | 2200 | 92% | 11000 | 2200 | 2200 | 2200 | 2200 | 2200 | 11000 | 1650 | 11000 | 13110 | 550 | 2970 | 3610 | 2.5 | 13.6 | 16.5 | 3.70 | A |
| | 2200 | 2200 | 2200 | 2200 | 2900 | 98% | 11700 | 2130 | 2130 | 2130 | 2130 | 2810 | 11330 | 1820 | 11330 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.87 | A |
| | 2200 | 2200 | 2200 | 2200 | 3800 | 105% | 12600 | 2020 | 2020 | 2020 | 2020 | 3490 | 11570 | 1850 | 11570 | 13110 | 560 | 2980 | 3610 | 2.6 | 13.6 | 16.5 | 3.88 | A |
| | 2200 | 2200 | 2200 | 2200 | 5600 | 120% | 14400 | 1740 | 1740 | 1740 | 1740 | 4430 | 11390 | 2000 | 11390 | 13430 | 570 | 3040 | 3710 | 2.6 | 13.9 | 17.0 | 3.75 | A |
| | 2200 | 2200 | 2200 | 2900 | 2900 | 103% | 12400 | 2040 | 2040 | 2040 | 2690 | 2690 | 11500 | 1930 | 11500 | 13430 | 550 | 3020 | 3690 | 2.5 | 13.8 | 16.9 | 3.81 | A |
| | 2200 | 2200 | 2200 | 2900 | 3800 | 111% | 13300 | 1940 | 1940 | 1940 | 2560 | 3350 | 11730 | 1960 | 11730 | 13110 | 560 | 2980 | 3610 | 2.6 | 13.6 | 16.5 | 3.94 | A |
| | 2200 | 2200 | 2200 | 2900 | 5600 | 126% | 15100 | 1690 | 1690 | 1690 | 2220 | 4290 | 11580 | 2280 | 11580 | 13590 | 570 | 3080 | 3750 | 2.6 | 14.1 | 17.2 | 3.76 | A |
| | 2200 | 2200 | 2200 | 3800 | 3800 | 118% | 14200 | 1850 | 1850 | 1850 | 3200 | 3200 | 11950 | 1960 | 11950 | 13430 | 560 | 3030 | 3700 | 2.6 | 13.9 | 16.9 | 3.94 | A |
| | 2200 | 2200 | 2200 | 3800 | 5600 | 133% | 16000 | 1620 | 1620 | 1620 | 2800 | 4130 | 11790 | 2320 | 11790 | 13750 | 580 | 3130 | 3800 | 2.7 | 14.3 | 17.4 | 3.77 | A |
| | 2200 | 2200 | 2200 | 5600 | 5600 | 148% | 17800 | 1480 | 1480 | 1480 | 3780 | 3780 | 12000 | 2360 | 12000 | 14000 | 590 | 3230 | 3940 | 2.7 | 14.8 | 18.0 | 3.72 | A |
| | 2200 | 2200 | 2900 | 2900 | 2900 | 109% | 13100 | 1960 | 1960 | 2590 | 2590 | 2590 | 11690 | 1930 | 11690 | 13430 | 550 | 3020 | 3690 | 2.5 | 13.8 | 16.9 | 3.87 | A |
| | 2200 | 2200 | 2900 | 2900 | 3800 | 117% | 14000 | 1870 | 1870 | 2470 | 2470 | 3230 | 11910 | 1960 | 11910 | 13590 | 560 | 3070 | 3740 | 2.6 | 14.1 | 17.1 | 3.88 | A |
| | 2200 | 2200 | 2900 | 2900 | 5600 | 132% | 15800 | 1640 | 1640 | 2160 | 2160 | 4170 | 11770 | 2280 | 11770 | 13900 | 570 | 3170 | 3840 | 2.6 | 14.5 | 17.6 | 3.71 | A |
| | 2200 | 2200 | 2900 | 3800 | 3800 | 124% | 14900 | 1700 | 1700 | 2240 | 2940 | 2940 | 11520 | 2240 | 11520 | 13590 | 560 | 3070 | 3740 | 2.6 | 14.1 | 17.1 | 3.75 | A |
| | 2200 | 2200 | 2900 | 3800 | 5600 | 139% | 16700 | 1580 | 1580 | 2080 | 2730 | 4020 | 11990 | 2320 | 11990 | 13900 | 580 | 3170 | 3840 | 2.7 | 14.5 | 17.6 | 3.78 | A |
| | 2200 | 2200 | 2900 | 5600 | 5600 | 154% | 18500 | 1430 | 1430 | 1880 | 3630 | 3630 | 12000 | 2360 | 12000 | 14000 | 590 | 3280 | 3940 | 2.7 | 15.0 | 18.0 | 3.66 | A |
| | 2200 | 2200 | 3800 | 3800 | 3800 | 132% | 15800 | 1640 | 1640 | 2830 | 2830 | 2830 | 11770 | 2280 | 11770 | 13750 | 570 | 3120 | 3790 | 2.6 | 14.3 | 17.3 | 3.77 | A |
| | 2200 | 2200 | 3800 | 3800 | 5600 | 147% | 17600 | 1500 | 1500 | 2590 | 2590 | 3820 | 12000 | 2320 | 12000 | 14000 | 580 | 3220 | 3930 | 2.7 | 14.7 | 18.0 | 3.73 | A |
| | 2200 | 2900 | 2900 | 2900 | 2900 | 115% | 13800 | 1890 | 2490 | 2490 | 2490 | 2490 | 11850 | 1930 | 11850 | 13590 | 550 | 3060 | 3730 | 2.5 | 14.0 | 17.1 | 3.87 | A |
| | 2200 | 2900 | 2900 | 2900 | 3800 | 123% | 14700 | 1720 | 2260 | 2260 | 2260 | 2970 | 11470 | 2240 | 11470 | 13750 | 560 | 3110 | 3780 | 2.6 | 14.2 | 17.3 | 3.69 | A |
| | 2200 | 2900 | 2900 | 2900 | 5600 | 138% | 16500 | 1590 | 2100 | 2100 | 2100 | 4050 | 11940 | 2280 | 11940 | 14000 | 570 | 3210 | 3920 | 2.6 | 14.7 | 17.9 | 3.72 | A |
| | 2200 | 2900 | 2900 | 3800 | 3800 | 130% | 15600 | 1650 | 2180 | 2180 | 2850 | 2850 | 11710 | 2240 | 11710 | 13900 | 560 | 3160 | 3830 | 2.6 | 14.5 | 17.5 | 3.71 | A |
| | 2200 | 2900 | 2900 | 3800 | 5600 | 145% | 17400 | 1520 | 2000 | 2000 | 2620 | 3860 | 12000 | 2320 | 12000 | 14000 | 580 | 3260 | 3920 | 2.7 | 14.9 | 17.9 | 3.68 | A |
| | 2200 | 2900 | 3800 | 3800 | 3800 | 138% | 16500 | 1590 | 2100 | 2750 | 2750 | 2750 | 11940 | 2280 | 11940 | 13900 | 570 | 3160 | 3830 | 2.6 | 14.5 | 17.5 | 3.78 | A |
| | 2200 | 2900 | 3800 | 3800 | 5600 | 153% | 18300 | 1450 | 1900 | 2490 | 2490 | 3670 | 12000 | 2320 | 12000 | 14000 | 580 | 3270 | 3930 | 2.7 | 15.0 | 18.0 | 3.67 | A |
| | 2200 | 3800 | 3800 | 3800 | 3800 | 145% | 17400 | 1520 | 2620 | 2620 | 2620 | 2620 | 12000 | 2280 | 12000 | 14000 | 570 | 3210 | 3920 | 2.6 | 14.7 | 17.9 | 3.74 | A |
| | 2900 | 2900 | 2900 | 2900 | 2900 | 121% | 14500 | 2400 | 2400 | 2400 | 2400 | 2400 | 12000 | 3400 | 12000 | 14000 | 550 | 2930 | 3900 | 2.5 | 13.4 | 17.8 | 4.10 | A |
| | 2900 | 2900 | 2900 | 2900 | 3800 | 128% | 15400 | 2190 | 2190 | 2190 | 2190 | 2870 | 11630 | 2240 | 11630 | 13900 | 560 | 3150 | 3820 | 2.6 | 14.4 | 17.5 | 3.69 | A |
| | 2900 | 2900 | 2900 | 2900 | 5600 | 143% | 17200 | 2020 | 2020 | 2020 | 2020 | 3920 | 12000 | 2280 | 12000 | 14000 | 570 | 3260 | 3920 | 2.6 | 14.9 | 17.9 | 3.68 | A |
| | 2900 | 2900 | 2900 | 3800 | 3800 | 136% | 16300 | 2110 | 2110 | 2110 | 2770 | 2770 | 11870 | 2240 | 11870 | 14000 | 560 | 3200 | 3910 | 2.6 | 14.6 | 17.9 | 3.71 | A |
| | 2900 | 2900 | 2900 | 3800 | 5600 | 151% | 18100 | 1920 | 1920 | 1920 | 2530 | 3710 | 12000 | 2320 | 12000 | 14000 | 580 | 3310 | 3920 | 2.7 | 15.1 | 17.9 | 3.63 | A |
| | 2900 | 2900 | 3800 | 3800 | 3800 | 143% | 17200 | 2020 | 2020 | 2650 | 2650 | 2660 | 12000 | 2280 | 12000 | 14000 | 570 | 3250 | 3910 | 2.6 | 14.9 | 17.9 | 3.69 | A |
| | 2900 | 2900 | 3800 | 3800 | 5600 | 158% | 19000 | 1830 | 1830 | 2400 | 2400 | 3540 | 12000 | 3400 | 12000 | 14000 | 580 | 3360 | 3930 | 2.7 | 15.4 | 18.0 | 3.57 | B |
| | 2900 | 3800 | 3800 | 3800 | 3800 | 151% | 18100 | 1920 | 2520 | 2520 | 2520 | 2520 | 12000 | 2280 | 12000 | 14000 | 570 | 3260 | 3920 | 2.6 | 14.9 | 17.9 | 3.68 | A |

1. Heating capacity is based on 20˚CDB (indoor temperature), 7˚CDB/6˚CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 2900, 3800, 5600W class: Wall Mounted Neo forte & Crystal Series [only for MH***FNEA, MH***FAEA Type]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 19.0 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

# FJM Capacity Combination

## Maldives P Series & Deluxe

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2000 | - | - | - | - | 20% | 2000 | 2000 | - | - | - | - | 2000 | 1600 | 2000 | 3000 | 580 | 700 | 1010 | 2.7 | 3.2 | 4.6 | 2.86 | C |
| | 2500 | - | - | - | - | 25% | 2500 | 2500 | - | - | - | - | 2500 | 1600 | 2500 | 3630 | 580 | 800 | 1210 | 2.7 | 3.7 | 5.5 | 3.13 | B |
| | 3500 | - | - | - | - | 35% | 3500 | 3500 | - | - | - | - | 3500 | 1620 | 3500 | 4740 | 590 | 1070 | 1580 | 2.7 | 4.9 | 7.2 | 3.27 | A |
| | 5000 | - | - | - | - | 50% | 5000 | 5000 | - | - | - | - | 5000 | 1650 | 5000 | 6480 | 600 | 1500 | 2160 | 2.7 | 6.9 | 9.9 | 3.33 | A |
| | 6800 | - | - | - | - | 68% | 6800 | 6800 | - | - | - | - | 6800 | 1710 | 6800 | 8690 | 620 | 2180 | 2900 | 2.8 | 10.0 | 13.3 | 3.12 | B |
| 2 Unit | 2000 | 2000 | - | - | - | 40% | 4000 | 2000 | 2000 | - | - | - | 4000 | 1680 | 4000 | 4900 | 610 | 1260 | 1650 | 2.8 | 5.8 | 7.6 | 3.17 | B |
| | 2000 | 2500 | - | - | - | 45% | 4500 | 2000 | 2500 | - | - | - | 4500 | 1680 | 4500 | 5530 | 610 | 1400 | 1860 | 2.8 | 6.4 | 8.5 | 3.21 | A |
| | 2000 | 3500 | - | - | - | 55% | 5500 | 2000 | 3500 | - | - | - | 5500 | 1710 | 5500 | 6950 | 620 | 1750 | 2330 | 2.8 | 8.0 | 10.7 | 3.14 | B |
| | 2000 | 5000 | - | - | - | 70% | 7000 | 2000 | 5000 | - | - | - | 7000 | 2210 | 7000 | 8690 | 630 | 2190 | 2910 | 2.9 | 10.0 | 13.3 | 3.20 | B |
| | 2000 | 6800 | - | - | - | 88% | 8800 | 1830 | 6240 | - | - | - | 8070 | 2280 | 8070 | 10110 | 650 | 2550 | 3390 | 3 | 11.7 | 15.5 | 3.16 | B |
| | 2500 | 2500 | - | - | - | 50% | 5000 | 2500 | 2500 | - | - | - | 5000 | 1680 | 5000 | 6320 | 610 | 1600 | 2120 | 2.8 | 7.3 | 9.7 | 3.13 | B |
| | 2500 | 3500 | - | - | - | 60% | 6000 | 2500 | 3500 | - | - | - | 6000 | 1710 | 6000 | 7270 | 620 | 1840 | 2430 | 2.8 | 8.4 | 11.1 | 3.26 | A |
| | 2500 | 5000 | - | - | - | 75% | 7500 | 2500 | 5000 | - | - | - | 7500 | 2210 | 7500 | 9320 | 630 | 2340 | 3120 | 2.9 | 10.7 | 14.3 | 3.21 | A |
| | 2500 | 6800 | - | - | - | 93% | 9300 | 2190 | 5960 | - | - | - | 8150 | 2280 | 8150 | 10110 | 650 | 2550 | 3390 | 3 | 11.7 | 15.5 | 3.20 | B |
| | 3500 | 3500 | - | - | - | 70% | 7000 | 3500 | 3500 | - | - | - | 7000 | 2170 | 7000 | 8530 | 620 | 2130 | 2850 | 2.8 | 9.7 | 13.0 | 3.29 | A |
| | 3500 | 5000 | - | - | - | 85% | 8500 | 3300 | 4720 | - | - | - | 8020 | 2240 | 8020 | 9950 | 640 | 2490 | 3330 | 2.9 | 11.4 | 15.2 | 3.22 | A |
| | 3500 | 6800 | - | - | - | 103% | 10300 | 2920 | 5670 | - | - | - | 8590 | 2480 | 8590 | 10740 | 660 | 2700 | 3600 | 3 | 12.4 | 16.5 | 3.18 | B |
| | 5000 | 5000 | - | - | - | 100% | 10000 | 4280 | 4280 | - | - | - | 8560 | 2440 | 8560 | 10430 | 650 | 2650 | 3500 | 3 | 12.1 | 16.0 | 3.23 | A |
| | 5000 | 6800 | - | - | - | 118% | 11800 | 3740 | 5080 | - | - | - | 8820 | 2510 | 8820 | 10900 | 670 | 2760 | 3670 | 3.1 | 12.6 | 16.8 | 3.20 | B |
| | 6800 | 6800 | - | - | - | 136% | 13600 | 4550 | 4550 | - | - | - | 9100 | 3110 | 9100 | 11000 | 690 | 2830 | 3740 | 3.2 | 13.0 | 17.1 | 3.22 | A |
| 3 Unit | 2000 | 2000 | 2000 | - | - | 60% | 6000 | 2000 | 2000 | 2000 | - | - | 6000 | 1760 | 6000 | 7270 | 640 | 1870 | 2460 | 2.9 | 8.6 | 11.3 | 3.21 | A |
| | 2000 | 2000 | 2500 | - | - | 65% | 6500 | 2000 | 2000 | 2500 | - | - | 6500 | 1760 | 6500 | 7900 | 640 | 2010 | 2660 | 2.9 | 9.2 | 12.2 | 3.23 | A |
| | 2000 | 2000 | 3500 | - | - | 75% | 7500 | 2000 | 2000 | 3500 | - | - | 7500 | 2280 | 7500 | 8850 | 650 | 2260 | 2980 | 3 | 10.3 | 13.6 | 3.32 | A |
| | 2000 | 2000 | 5000 | - | - | 90% | 9000 | 1930 | 1930 | 4830 | - | - | 8690 | 2310 | 8690 | 10270 | 660 | 2610 | 3450 | 3 | 11.9 | 15.8 | 3.33 | A |
| | 2000 | 2000 | 6800 | - | - | 108% | 10800 | 1660 | 1660 | 5650 | - | - | 8970 | 2550 | 8970 | 10430 | 680 | 2680 | 3530 | 3.1 | 12.3 | 16.2 | 3.35 | A |
| | 2000 | 2500 | 2500 | - | - | 70% | 7000 | 2000 | 2500 | 2500 | - | - | 7000 | 2240 | 7000 | 8370 | 640 | 2110 | 2820 | 2.9 | 9.7 | 12.9 | 3.32 | A |
| | 2000 | 2500 | 3500 | - | - | 80% | 8000 | 2000 | 2500 | 3500 | - | - | 8000 | 2280 | 8000 | 9320 | 650 | 2350 | 3130 | 3 | 10.8 | 14.3 | 3.40 | A |
| | 2000 | 2500 | 5000 | - | - | 95% | 9500 | 1850 | 2310 | 4620 | - | - | 8780 | 2310 | 8780 | 10270 | 660 | 2610 | 3450 | 3 | 11.9 | 15.8 | 3.36 | A |
| | 2000 | 2500 | 6800 | - | - | 113% | 11300 | 1550 | 1940 | 5270 | - | - | 8760 | 2550 | 8760 | 10430 | 680 | 2680 | 3530 | 3.1 | 12.3 | 16.2 | 3.27 | A |
| | 2000 | 3500 | 3500 | - | - | 90% | 9000 | 1930 | 3380 | 3380 | - | - | 8690 | 2280 | 8690 | 10270 | 650 | 2600 | 3440 | 3 | 11.9 | 15.7 | 3.34 | A |
| | 2000 | 3500 | 5000 | - | - | 105% | 10500 | 1700 | 2980 | 4250 | - | - | 8930 | 2510 | 8930 | 10430 | 670 | 2660 | 3510 | 3.1 | 12.2 | 16.1 | 3.36 | A |
| | 2000 | 3500 | 6800 | - | - | 123% | 12300 | 1460 | 2550 | 4950 | - | - | 8960 | 2760 | 8960 | 10740 | 690 | 2730 | 3630 | 3.2 | 12.5 | 16.6 | 3.28 | A |
| | 2000 | 5000 | 5000 | - | - | 120% | 12000 | 1480 | 3710 | 3710 | - | - | 8900 | 2720 | 8900 | 10740 | 680 | 2720 | 3630 | 3.1 | 12.4 | 16.6 | 3.27 | A |
| | 2000 | 5000 | 6800 | - | - | 138% | 13800 | 1340 | 3360 | 4560 | - | - | 9260 | 3150 | 9260 | 11000 | 700 | 2840 | 3750 | 3.2 | 13.0 | 17.2 | 3.26 | A |
| | 2000 | 6800 | 6800 | - | - | 156% | 15600 | 1260 | 4270 | 4270 | - | - | 9800 | 3240 | 9800 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.43 | A |
| | 2500 | 2500 | 2500 | - | - | 75% | 7500 | 2500 | 2500 | 2500 | - | - | 7500 | 2240 | 7500 | 8850 | 640 | 2250 | 2970 | 2.9 | 10.3 | 13.6 | 3.33 | A |
| | 2500 | 2500 | 3500 | - | - | 85% | 8500 | 2500 | 2500 | 3500 | - | - | 8500 | 2280 | 8500 | 9950 | 650 | 2500 | 3340 | 3 | 11.4 | 15.3 | 3.40 | A |
| | 2500 | 2500 | 5000 | - | - | 100% | 10000 | 2210 | 2210 | 4430 | - | - | 8850 | 2480 | 8850 | 10270 | 660 | 2610 | 3450 | 3 | 11.9 | 15.8 | 3.39 | A |
| | 2500 | 2500 | 6800 | - | - | 118% | 11800 | 1880 | 1880 | 5110 | - | - | 8870 | 2550 | 8870 | 10740 | 680 | 2720 | 3630 | 3.1 | 12.4 | 16.6 | 3.26 | A |
| | 2500 | 3500 | 3500 | - | - | 95% | 9500 | 2310 | 3230 | 3230 | - | - | 8770 | 2280 | 8770 | 10270 | 650 | 2600 | 3440 | 3 | 11.9 | 15.7 | 3.37 | A |
| | 2500 | 3500 | 5000 | - | - | 110% | 11000 | 1980 | 2770 | 3950 | - | - | 8700 | 2510 | 8700 | 10430 | 670 | 2660 | 3510 | 3.1 | 12.2 | 16.1 | 3.27 | A |
| | 2500 | 3500 | 6800 | - | - | 128% | 12800 | 1770 | 2480 | 4810 | - | - | 9060 | 2760 | 9060 | 10900 | 690 | 2780 | 3690 | 3.2 | 12.7 | 16.9 | 3.26 | A |
| | 2500 | 5000 | 5000 | - | - | 125% | 12500 | 1800 | 3600 | 3600 | - | - | 9000 | 2720 | 9000 | 10900 | 680 | 2770 | 3680 | 3.1 | 12.7 | 16.8 | 3.25 | A |
| | 2500 | 5000 | 6800 | - | - | 143% | 14300 | 1640 | 3270 | 4450 | - | - | 9360 | 3150 | 9360 | 11000 | 700 | 2740 | 3750 | 3.2 | 12.5 | 17.2 | 3.42 | A |
| | 2500 | 6800 | 6800 | - | - | 161% | 16100 | 1520 | 4140 | 4140 | - | - | 9800 | 3240 | 9800 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.43 | A |
| | 3500 | 3500 | 3500 | - | - | 105% | 10500 | 2980 | 2980 | 2980 | - | - | 8940 | 2480 | 8940 | 10430 | 660 | 2650 | 3500 | 3 | 12.1 | 16.0 | 3.37 | A |
| | 3500 | 3500 | 5000 | - | - | 120% | 12000 | 2600 | 2600 | 3710 | - | - | 8910 | 2680 | 8910 | 10740 | 670 | 2710 | 3620 | 3.1 | 12.4 | 16.6 | 3.29 | A |
| | 3500 | 3500 | 6800 | - | - | 138% | 13800 | 2350 | 2350 | 4560 | - | - | 9260 | 3110 | 9260 | 11000 | 690 | 2830 | 3740 | 3.2 | 13.0 | 17.1 | 3.27 | A |
| | 3500 | 5000 | 5000 | - | - | 135% | 13500 | 2390 | 3410 | 3410 | - | - | 9210 | 3110 | 9210 | 11000 | 690 | 2820 | 3740 | 3.2 | 12.9 | 17.1 | 3.27 | A |
| | 3500 | 5000 | 6800 | - | - | 153% | 15300 | 2240 | 3200 | 4360 | - | - | 9800 | 3200 | 9800 | 11000 | 710 | 2800 | 3760 | 3.2 | 12.8 | 17.2 | 3.50 | A |
| | 3500 | 6800 | 6800 | - | - | 171% | 17100 | 2000 | 3900 | 3900 | - | - | 9800 | 3290 | 9800 | 11000 | 730 | 2910 | 3780 | 3.3 | 13.3 | 17.3 | 3.37 | A |
| | 5000 | 5000 | 5000 | - | - | 150% | 15000 | 3260 | 3270 | 3270 | - | - | 9800 | 3150 | 9800 | 11000 | 700 | 2790 | 3750 | 3.2 | 12.8 | 17.2 | 3.51 | A |
| | 5000 | 5000 | 6800 | - | - | 168% | 16800 | 2920 | 2920 | 3960 | - | - | 9800 | 3240 | 9800 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.37 | A |

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 4 Unit | 2000 | 2000 | 2000 | 2000 | - | 80% | 8000 | 2000 | 2000 | 2000 | 2000 | - | 8000 | 2350 | 8000 | 9320 | 670 | 2380 | 3160 | 3.1 | 10.9 | 14.5 | 3.36 | A |
| | 2000 | 2000 | 2000 | 2500 | - | 85% | 8500 | 2000 | 2000 | 2000 | 2500 | - | 8500 | 2350 | 8500 | 9950 | 670 | 2520 | 3360 | 3.1 | 11.5 | 15.4 | 3.37 | A |
| | 2000 | 2000 | 2000 | 3500 | - | 95% | 9500 | 1850 | 1850 | 1850 | 3230 | - | 8780 | 2380 | 8780 | 10270 | 680 | 2620 | 3470 | 3.1 | 12.0 | 15.9 | 3.35 | A |
| | 2000 | 2000 | 2000 | 5000 | - | 110% | 11000 | 1580 | 1580 | 1580 | 3950 | - | 8690 | 2590 | 8690 | 10430 | 690 | 2690 | 3540 | 3.2 | 12.3 | 16.2 | 3.23 | A |
| | 2000 | 2000 | 2000 | 6800 | - | 128% | 12800 | 1420 | 1420 | 1420 | 4820 | - | 9080 | 2840 | 9080 | 10900 | 710 | 2800 | 3710 | 3.2 | 12.8 | 17.0 | 3.24 | A |
| | 2000 | 2000 | 2500 | 2500 | - | 90% | 9000 | 1930 | 1930 | 2420 | 2420 | - | 8700 | 2350 | 8700 | 10270 | 670 | 2620 | 3460 | 3.1 | 12.0 | 15.8 | 3.32 | A |
| | 2000 | 2000 | 2500 | 3500 | - | 100% | 10000 | 1770 | 1770 | 2210 | 3100 | - | 8850 | 2550 | 8850 | 10270 | 680 | 2620 | 3470 | 3.1 | 12.0 | 15.9 | 3.38 | A |
| | 2000 | 2000 | 2500 | 5000 | - | 115% | 11500 | 1530 | 1530 | 1910 | 3830 | - | 8800 | 2590 | 8800 | 10740 | 690 | 2730 | 3640 | 3.2 | 12.5 | 16.7 | 3.22 | A |
| | 2000 | 2000 | 2500 | 6800 | - | 133% | 13300 | 1380 | 1380 | 1720 | 4680 | - | 9160 | 3200 | 9160 | 10900 | 710 | 2800 | 3710 | 3.2 | 12.8 | 17.0 | 3.27 | A |
| | 2000 | 2000 | 3500 | 3500 | - | 110% | 11000 | 1580 | 1580 | 2770 | 2770 | - | 8700 | 2550 | 8700 | 10430 | 680 | 2680 | 3530 | 3.1 | 12.3 | 16.2 | 3.25 | A |
| | 2000 | 2000 | 3500 | 5000 | - | 125% | 12500 | 1440 | 1440 | 2520 | 3600 | - | 9000 | 2800 | 9000 | 10900 | 700 | 2790 | 3700 | 3.2 | 12.8 | 16.9 | 3.23 | A |
| | 2000 | 2000 | 3500 | 6800 | - | 143% | 14300 | 1310 | 1310 | 2290 | 4450 | - | 9360 | 3240 | 9360 | 11000 | 720 | 2760 | 3770 | 3.3 | 12.6 | 17.3 | 3.39 | A |
| | 2000 | 2000 | 5000 | 5000 | - | 140% | 14000 | 1330 | 1330 | 3320 | 3320 | - | 9300 | 3200 | 9300 | 11000 | 710 | 2850 | 3760 | 3.2 | 13.0 | 17.2 | 3.26 | A |
| | 2000 | 2000 | 5000 | 6800 | - | 158% | 15800 | 1240 | 1240 | 3100 | 4220 | - | 9800 | 3290 | 9800 | 11000 | 730 | 2870 | 3780 | 3.3 | 13.1 | 17.3 | 3.41 | A |
| | 2000 | 2500 | 2500 | 2500 | - | 95% | 9500 | 1850 | 2310 | 2310 | 2310 | - | 8780 | 2350 | 8780 | 10270 | 670 | 2620 | 3460 | 3.1 | 12.0 | 15.8 | 3.35 | A |
| | 2000 | 2500 | 2500 | 3500 | - | 105% | 10500 | 1700 | 2130 | 2130 | 2980 | - | 8940 | 2550 | 8940 | 10430 | 680 | 2670 | 3520 | 3.1 | 12.2 | 16.1 | 3.35 | A |
| | 2000 | 2500 | 2500 | 5000 | - | 120% | 12000 | 1480 | 1850 | 1850 | 3700 | - | 8880 | 2760 | 8880 | 10740 | 690 | 2730 | 3640 | 3.2 | 12.5 | 16.7 | 3.25 | A |
| | 2000 | 2500 | 2500 | 6800 | - | 138% | 13800 | 1340 | 1680 | 1680 | 4560 | - | 9260 | 3200 | 9260 | 11000 | 710 | 2850 | 3760 | 3.2 | 13.0 | 17.2 | 3.25 | A |
| | 2000 | 2500 | 3500 | 3500 | - | 115% | 11500 | 1530 | 1910 | 2680 | 2680 | - | 8800 | 2550 | 8800 | 10740 | 680 | 2720 | 3630 | 3.1 | 12.4 | 16.6 | 3.24 | A |
| | 2000 | 2500 | 3500 | 5000 | - | 130% | 13000 | 1400 | 1750 | 2450 | 3500 | - | 9100 | 3150 | 9100 | 10900 | 700 | 2790 | 3700 | 3.2 | 12.8 | 16.9 | 3.26 | A |
| | 2000 | 2500 | 3500 | 6800 | - | 148% | 14800 | 1280 | 1600 | 2240 | 4350 | - | 9470 | 3240 | 9470 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.37 | A |
| | 2000 | 2500 | 5000 | 5000 | - | 145% | 14500 | 1300 | 1620 | 3240 | 3240 | - | 9400 | 3200 | 9400 | 11000 | 710 | 2800 | 3760 | 3.2 | 12.8 | 17.2 | 3.36 | A |
| | 2000 | 2500 | 5000 | 6800 | - | 163% | 16300 | 1200 | 1500 | 3010 | 4090 | - | 9800 | 3290 | 9800 | 11000 | 730 | 2870 | 3780 | 3.3 | 13.1 | 17.3 | 3.41 | A |
| | 2000 | 3500 | 3500 | 3500 | - | 125% | 12500 | 1440 | 2520 | 2520 | 2520 | - | 9000 | 2760 | 9000 | 10900 | 690 | 2780 | 3690 | 3.2 | 12.7 | 16.9 | 3.24 | A |
| | 2000 | 3500 | 3500 | 5000 | - | 140% | 14000 | 1330 | 2330 | 2330 | 3330 | - | 9320 | 3150 | 9320 | 11000 | 700 | 2840 | 3750 | 3.2 | 13.0 | 17.2 | 3.28 | A |
| | 2000 | 3500 | 3500 | 6800 | - | 158% | 15800 | 1240 | 2170 | 2170 | 4220 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.43 | A |
| | 2000 | 3500 | 5000 | 5000 | - | 155% | 15500 | 1270 | 2210 | 3160 | 3160 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2850 | 3770 | 3.3 | 13.0 | 17.3 | 3.44 | A |
| | 2000 | 3500 | 5000 | 6800 | - | 173% | 17300 | 1140 | 1980 | 2830 | 3850 | - | 9800 | 3330 | 9800 | 11000 | 740 | 2920 | 3790 | 3.4 | 13.4 | 17.3 | 3.36 | A |
| | 2000 | 5000 | 5000 | 5000 | - | 170% | 17000 | 1160 | 2880 | 2880 | 2880 | - | 9800 | 3290 | 9800 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.36 | A |
| | 2500 | 2500 | 2500 | 2500 | - | 100% | 10000 | 2210 | 2210 | 2210 | 2210 | - | 8840 | 2510 | 8840 | 10270 | 670 | 2620 | 3460 | 3.1 | 12.0 | 15.8 | 3.37 | A |
| | 2500 | 2500 | 2500 | 3500 | - | 110% | 11000 | 1980 | 1980 | 1980 | 2770 | - | 8710 | 2550 | 8710 | 10430 | 680 | 2670 | 3520 | 3.1 | 12.2 | 16.1 | 3.26 | A |
| | 2500 | 2500 | 2500 | 5000 | - | 125% | 12500 | 1800 | 1800 | 1800 | 3600 | - | 9000 | 2760 | 9000 | 10900 | 690 | 2780 | 3690 | 3.2 | 12.7 | 16.9 | 3.24 | A |
| | 2500 | 2500 | 2500 | 6800 | - | 143% | 14300 | 1640 | 1640 | 1640 | 4460 | - | 9380 | 3200 | 9380 | 11000 | 710 | 2750 | 3760 | 3.2 | 12.6 | 17.2 | 3.41 | A |
| | 2500 | 2500 | 3500 | 3500 | - | 120% | 12000 | 1850 | 1850 | 2600 | 2600 | - | 8900 | 2720 | 8900 | 10740 | 680 | 2720 | 3630 | 3.1 | 12.4 | 16.6 | 3.27 | A |
| | 2500 | 2500 | 3500 | 5000 | - | 135% | 13500 | 1700 | 1700 | 2390 | 3410 | - | 9200 | 3150 | 9200 | 11000 | 700 | 2830 | 3750 | 3.2 | 13.0 | 17.2 | 3.25 | A |
| | 2500 | 2500 | 3500 | 6800 | - | 153% | 15300 | 1600 | 1600 | 2240 | 4360 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.49 | A |
| | 2500 | 2500 | 5000 | 5000 | - | 150% | 15000 | 1630 | 1630 | 3270 | 3270 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2800 | 3760 | 3.2 | 12.8 | 17.2 | 3.50 | A |
| | 2500 | 2500 | 5000 | 6800 | - | 168% | 16800 | 1460 | 1460 | 2920 | 3960 | - | 9800 | 3290 | 9800 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.36 | A |
| | 2500 | 3500 | 3500 | 3500 | - | 130% | 13000 | 1750 | 2450 | 2450 | 2450 | - | 9100 | 3110 | 9100 | 10900 | 690 | 2780 | 3690 | 3.2 | 12.7 | 16.9 | 3.27 | A |
| | 2500 | 3500 | 3500 | 5000 | - | 145% | 14500 | 1620 | 2270 | 2270 | 3240 | - | 9400 | 3150 | 9400 | 11000 | 700 | 2790 | 3750 | 3.2 | 12.8 | 17.2 | 3.37 | A |
| | 2500 | 3500 | 3500 | 6800 | - | 163% | 16300 | 1510 | 2100 | 2100 | 4090 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.43 | A |
| | 2500 | 3500 | 5000 | 5000 | - | 160% | 16000 | 1540 | 2140 | 3060 | 3060 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2850 | 3770 | 3.3 | 13.0 | 17.3 | 3.44 | A |
| | 3500 | 3500 | 3500 | 3500 | - | 140% | 14000 | 2330 | 2330 | 2330 | 2330 | - | 9320 | 3110 | 9320 | 11000 | 690 | 2830 | 3740 | 3.2 | 13.0 | 17.1 | 3.29 | A |
| | 3500 | 3500 | 3500 | 5000 | - | 155% | 15500 | 2210 | 2210 | 2210 | 3170 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2840 | 3760 | 3.2 | 13.0 | 17.2 | 3.45 | A |
| | 3500 | 3500 | 3500 | 6800 | - | 173% | 17300 | 1980 | 1980 | 1980 | 3860 | - | 9800 | 3290 | 9800 | 11000 | 730 | 2910 | 3780 | 3.3 | 13.3 | 17.3 | 3.37 | A |
| | 3500 | 3500 | 5000 | 5000 | - | 170% | 17000 | 2020 | 2020 | 2880 | 2880 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.37 | A |

# FJM Capacity Combination

## RJ100F5HXEA

Maldives P Series & Deluxe

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 5 Unit | 2000 | 2000 | 2000 | 2000 | 2000 | 100% | 10000 | 1900 | 1900 | 1900 | 1900 | 1900 | 9500 | 2630 | 9500 | 10270 | 700 | 2650 | 3490 | 3.2 | 12.1 | 16.0 | 3.58 | A |
| | 2000 | 2000 | 2000 | 2000 | 2500 | 105% | 10500 | 1820 | 1820 | 1820 | 1820 | 2270 | 9550 | 2630 | 9550 | 10430 | 700 | 2700 | 3550 | 3.2 | 12.4 | 16.2 | 3.54 | A |
| | 2000 | 2000 | 2000 | 2000 | 3500 | 115% | 11500 | 1680 | 1680 | 1680 | 1680 | 2940 | 9660 | 2660 | 9660 | 10740 | 710 | 2750 | 3650 | 3.2 | 12.6 | 16.7 | 3.51 | A |
| | 2000 | 2000 | 2000 | 2000 | 5000 | 130% | 13000 | 1540 | 1540 | 1540 | 1540 | 3840 | 10000 | 3240 | 10000 | 10900 | 720 | 2810 | 3720 | 3.3 | 12.9 | 17.0 | 3.56 | A |
| | 2000 | 2000 | 2000 | 2000 | 6800 | 148% | 14800 | 1350 | 1350 | 1350 | 1350 | 4600 | 10000 | 3330 | 10000 | 11000 | 740 | 2830 | 3790 | 3.4 | 13.0 | 17.3 | 3.53 | A |
| | 2000 | 2000 | 2000 | 2500 | 2500 | 110% | 11000 | 1750 | 1750 | 1750 | 2180 | 2180 | 9610 | 2630 | 9610 | 10430 | 700 | 2700 | 3550 | 3.2 | 12.4 | 16.2 | 3.56 | A |
| | 2000 | 2000 | 2000 | 2500 | 3500 | 120% | 12000 | 1620 | 1620 | 1620 | 2020 | 2830 | 9710 | 2840 | 9710 | 10740 | 710 | 2750 | 3650 | 3.2 | 12.6 | 16.7 | 3.53 | A |
| | 2000 | 2000 | 2000 | 2500 | 5000 | 135% | 13500 | 1480 | 1480 | 1480 | 1860 | 3700 | 10000 | 3240 | 10000 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2000 | 2000 | 2000 | 2500 | 6800 | 153% | 15300 | 1310 | 1310 | 1310 | 1630 | 4440 | 10000 | 3330 | 10000 | 11000 | 740 | 2830 | 3790 | 3.4 | 13.0 | 17.3 | 3.53 | A |
| | 2000 | 2000 | 2000 | 3500 | 3500 | 130% | 13000 | 1540 | 1540 | 1540 | 2690 | 2690 | 10000 | 3200 | 10000 | 10900 | 710 | 2800 | 3710 | 3.2 | 12.8 | 17.0 | 3.57 | A |
| | 2000 | 2000 | 2000 | 3500 | 5000 | 145% | 14500 | 1380 | 1380 | 1380 | 2410 | 3450 | 10000 | 3290 | 10000 | 11000 | 730 | 2820 | 3780 | 3.3 | 12.9 | 17.3 | 3.55 | A |
| | 2000 | 2000 | 2000 | 3500 | 6800 | 163% | 16300 | 1230 | 1230 | 1230 | 2150 | 4160 | 10000 | 3380 | 10000 | 11000 | 750 | 2880 | 3800 | 3.4 | 13.2 | 17.4 | 3.47 | A |
| | 2000 | 2000 | 2000 | 5000 | 5000 | 160% | 16000 | 1240 | 1240 | 1240 | 3140 | 3140 | 10000 | 3330 | 10000 | 11000 | 740 | 2880 | 3790 | 3.4 | 13.2 | 17.3 | 3.47 | A |
| | 2000 | 2000 | 2500 | 2500 | 2500 | 115% | 11500 | 1680 | 1680 | 2100 | 2100 | 2100 | 9660 | 2630 | 9660 | 10740 | 700 | 2740 | 3650 | 3.2 | 12.5 | 16.7 | 3.53 | A |
| | 2000 | 2000 | 2500 | 2500 | 3500 | 125% | 12500 | 1600 | 1600 | 2000 | 2000 | 2800 | 10000 | 2840 | 10000 | 10900 | 710 | 2800 | 3710 | 3.2 | 12.8 | 17.0 | 3.57 | A |
| | 2000 | 2000 | 2500 | 2500 | 5000 | 140% | 14000 | 1430 | 1430 | 1790 | 1790 | 3560 | 10000 | 3240 | 10000 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2000 | 2000 | 2500 | 2500 | 6800 | 158% | 15800 | 1270 | 1270 | 1580 | 1580 | 4300 | 10000 | 3330 | 10000 | 11000 | 740 | 2880 | 3790 | 3.4 | 13.2 | 17.3 | 3.47 | A |
| | 2000 | 2000 | 2500 | 3500 | 3500 | 135% | 13500 | 1480 | 1480 | 1860 | 2590 | 2590 | 10000 | 3200 | 10000 | 11000 | 710 | 2850 | 3760 | 3.2 | 13.0 | 17.2 | 3.51 | A |
| | 2000 | 2000 | 2500 | 3500 | 5000 | 150% | 15000 | 1330 | 1330 | 1680 | 2330 | 3330 | 10000 | 3290 | 10000 | 11000 | 730 | 2820 | 3780 | 3.3 | 12.9 | 17.3 | 3.55 | A |
| | 2000 | 2000 | 2500 | 3500 | 6800 | 168% | 16800 | 1190 | 1190 | 1490 | 2080 | 4050 | 10000 | 3380 | 10000 | 11000 | 750 | 2930 | 3800 | 3.4 | 13.4 | 17.4 | 3.41 | A |
| | 2000 | 2000 | 2500 | 5000 | 5000 | 165% | 16500 | 1210 | 1210 | 1520 | 3030 | 3030 | 10000 | 3330 | 10000 | 11000 | 740 | 2930 | 3790 | 3.4 | 13.4 | 17.3 | 3.41 | A |
| | 2000 | 2000 | 3500 | 3500 | 3500 | 145% | 14500 | 1370 | 1370 | 2420 | 2420 | 2420 | 10000 | 3240 | 10000 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.56 | A |
| | 2000 | 2000 | 3500 | 3500 | 5000 | 160% | 16000 | 1250 | 1250 | 2190 | 2190 | 3120 | 10000 | 3290 | 10000 | 11000 | 730 | 2870 | 3780 | 3.3 | 13.1 | 17.3 | 3.48 | A |
| | 2000 | 2500 | 2500 | 2500 | 2500 | 120% | 12000 | 1620 | 2020 | 2020 | 2020 | 2020 | 9700 | 2800 | 9700 | 10740 | 700 | 2740 | 3650 | 3.2 | 12.5 | 16.7 | 3.54 | A |
| | 2000 | 2500 | 2500 | 2500 | 3500 | 130% | 13000 | 1550 | 1920 | 1920 | 1920 | 2690 | 10000 | 3200 | 10000 | 10900 | 710 | 2800 | 3710 | 3.2 | 12.8 | 17.0 | 3.57 | A |
| | 2000 | 2500 | 2500 | 2500 | 5000 | 145% | 14500 | 1390 | 1720 | 1720 | 1720 | 3450 | 10000 | 3240 | 10000 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.56 | A |
| | 2000 | 2500 | 2500 | 2500 | 6800 | 163% | 16300 | 1240 | 1530 | 1530 | 1530 | 4170 | 10000 | 3330 | 10000 | 11000 | 740 | 2880 | 3790 | 3.4 | 13.2 | 17.3 | 3.47 | A |
| | 2000 | 2500 | 2500 | 3500 | 3500 | 140% | 14000 | 1440 | 1790 | 1790 | 2490 | 2490 | 10000 | 3200 | 10000 | 11000 | 710 | 2850 | 3760 | 3.2 | 13.0 | 17.2 | 3.51 | A |
| | 2000 | 2500 | 2500 | 3500 | 5000 | 155% | 15500 | 1290 | 1610 | 1610 | 2260 | 3230 | 10000 | 3290 | 10000 | 11000 | 730 | 2860 | 3780 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2000 | 2500 | 2500 | 3500 | 6800 | 173% | 17300 | 1160 | 1450 | 1450 | 2020 | 3920 | 10000 | 3380 | 10000 | 11000 | 750 | 2930 | 3800 | 3.4 | 13.4 | 17.4 | 3.41 | A |
| | 2000 | 2500 | 2500 | 5000 | 5000 | 170% | 17000 | 1180 | 1470 | 1470 | 2940 | 2940 | 10000 | 3330 | 10000 | 11000 | 740 | 2930 | 3790 | 3.4 | 13.4 | 17.3 | 3.41 | A |
| | 2000 | 2500 | 3500 | 3500 | 3500 | 150% | 15000 | 1340 | 1670 | 2330 | 2330 | 2330 | 10000 | 3240 | 10000 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.56 | A |
| | 2000 | 2500 | 3500 | 3500 | 5000 | 165% | 16500 | 1210 | 1520 | 2120 | 2120 | 3030 | 10000 | 3290 | 10000 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.42 | A |
| | 2000 | 3500 | 3500 | 3500 | 3500 | 160% | 16000 | 1240 | 2190 | 2190 | 2190 | 2190 | 10000 | 3240 | 10000 | 11000 | 720 | 2860 | 3770 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2500 | 2500 | 2500 | 2500 | 2500 | 125% | 12500 | 2000 | 2000 | 2000 | 2000 | 2000 | 10000 | 3000 | 10000 | 11000 | 700 | 2900 | 3700 | 3.2 | 13.3 | 16.9 | 3.45 | A |
| | 2500 | 2500 | 2500 | 2500 | 3500 | 135% | 13500 | 1850 | 1850 | 1850 | 1850 | 2600 | 10000 | 3200 | 10000 | 11000 | 710 | 2840 | 3760 | 3.2 | 13.0 | 17.2 | 3.52 | A |
| | 2500 | 2500 | 2500 | 2500 | 5000 | 150% | 15000 | 1670 | 1670 | 1670 | 1670 | 3320 | 10000 | 3240 | 10000 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.56 | A |
| | 2500 | 2500 | 2500 | 2500 | 6800 | 168% | 16800 | 1490 | 1490 | 1490 | 1490 | 4040 | 10000 | 3330 | 10000 | 11000 | 740 | 2930 | 3790 | 3.4 | 13.4 | 17.3 | 3.41 | A |
| | 2500 | 2500 | 2500 | 3500 | 3500 | 145% | 14500 | 1720 | 1720 | 1720 | 2420 | 2420 | 10000 | 3200 | 10000 | 11000 | 710 | 2800 | 3760 | 3.2 | 12.8 | 17.2 | 3.57 | A |
| | 2500 | 2500 | 2500 | 3500 | 5000 | 160% | 16000 | 1560 | 1560 | 1560 | 2190 | 3130 | 10000 | 3290 | 10000 | 11000 | 730 | 2860 | 3780 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2500 | 2500 | 3500 | 3500 | 3500 | 155% | 15500 | 1610 | 1610 | 2260 | 2260 | 2260 | 10000 | 3240 | 10000 | 11000 | 720 | 2850 | 3770 | 3.3 | 13.0 | 17.3 | 3.51 | A |
| | 2500 | 2500 | 3500 | 3500 | 5000 | 170% | 17000 | 1470 | 1470 | 2060 | 2060 | 2940 | 10000 | 3290 | 10000 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.42 | A |
| | 2500 | 3500 | 3500 | 3500 | 3500 | 165% | 16500 | 1520 | 2120 | 2120 | 2120 | 2120 | 10000 | 3240 | 10000 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.44 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2000, 2500, 3500, 5000, 6800W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 17.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2200 | - | - | - | - | 18% | 2200 | 2200 | - | - | - | - | 2200 | 1160 | 2200 | 3160 | 430 | 900 | 1080 | 2 | 4.1 | 4.9 | 2.44 | F |
| | 3300 | - | - | - | - | 28% | 3300 | 3200 | - | - | - | - | 3200 | 1160 | 3200 | 4270 | 430 | 1070 | 1284 | 2 | 4.9 | 5.9 | 2.99 | D |
| | 4000 | - | - | - | - | 33% | 4000 | 4000 | - | - | - | - | 4000 | 1190 | 4000 | 5210 | 440 | 1280 | 1536 | 2 | 5.9 | 7.0 | 3.13 | D |
| | 6000 | - | - | - | - | 50% | 6000 | 6000 | - | - | - | - | 6000 | 1220 | 6000 | 7430 | 450 | 1800 | 2160 | 2.1 | 8.2 | 9.9 | 3.33 | C |
| | 7800 | - | - | - | - | 65% | 7800 | 7800 | - | - | - | - | 7800 | 1270 | 7800 | 9640 | 470 | 2350 | 2820 | 2.2 | 10.8 | 12.9 | 3.32 | C |
| 2 Unit | 2200 | 2200 | - | - | - | 37% | 4400 | 2200 | 2200 | - | - | - | 4400 | 1240 | 4400 | 5530 | 460 | 1250 | 1520 | 2.1 | 5.7 | 7.0 | 3.52 | B |
| | 2200 | 3300 | - | - | - | 46% | 5500 | 2200 | 3300 | - | - | - | 5500 | 1240 | 5500 | 6790 | 460 | 1520 | 1850 | 2.1 | 7.0 | 8.5 | 3.62 | A |
| | 2200 | 4000 | - | - | - | 52% | 6200 | 2200 | 4000 | - | - | - | 6200 | 1270 | 6200 | 7580 | 470 | 1700 | 2060 | 2.2 | 7.8 | 9.4 | 3.65 | A |
| | 2200 | 6000 | - | - | - | 68% | 8200 | 2200 | 6000 | - | - | - | 8200 | 1300 | 8200 | 10110 | 480 | 2240 | 2750 | 2.2 | 10.3 | 12.6 | 3.66 | A |
| | 2200 | 7800 | - | - | - | 83% | 10000 | 2200 | 7800 | - | - | - | 10000 | 1500 | 10000 | 12480 | 500 | 2790 | 3390 | 2.3 | 12.8 | 15.5 | 3.58 | B |
| | 3300 | 3300 | - | - | - | 55% | 6600 | 3300 | 3300 | - | - | - | 6600 | 1240 | 6600 | 8220 | 460 | 1820 | 2230 | 2.1 | 8.3 | 10.2 | 3.63 | A |
| | 3300 | 4000 | - | - | - | 61% | 7300 | 3300 | 4000 | - | - | - | 7300 | 1270 | 7300 | 9010 | 470 | 2010 | 2440 | 2.2 | 9.2 | 11.2 | 3.63 | A |
| | 3300 | 6000 | - | - | - | 78% | 9300 | 3300 | 6000 | - | - | - | 9300 | 1300 | 9300 | 11690 | 480 | 2590 | 3160 | 2.2 | 11.9 | 14.5 | 3.59 | B |
| | 3300 | 7800 | - | - | - | 93% | 11100 | 3150 | 7450 | - | - | - | 10600 | 1500 | 10600 | 13110 | 500 | 2920 | 3560 | 2.3 | 13.4 | 16.3 | 3.63 | A |
| | 4000 | 4000 | - | - | - | 67% | 8000 | 4000 | 4000 | - | - | - | 8000 | 1270 | 8000 | 9800 | 470 | 2190 | 2650 | 2.2 | 10.0 | 12.1 | 3.65 | A |
| | 4000 | 6000 | - | - | - | 83% | 10000 | 4000 | 6000 | - | - | - | 10000 | 1470 | 10000 | 12320 | 490 | 2730 | 3330 | 2.2 | 12.5 | 15.2 | 3.66 | A |
| | 4000 | 7800 | - | - | - | 98% | 11800 | 3590 | 7010 | - | - | - | 10600 | 1530 | 10600 | 13110 | 510 | 2930 | 3560 | 2.3 | 13.4 | 16.3 | 3.62 | A |
| | 6000 | 6000 | - | - | - | 100% | 12000 | 5300 | 5300 | - | - | - | 10600 | 1650 | 10600 | 13110 | 500 | 2920 | 3560 | 2.3 | 13.4 | 16.3 | 3.63 | A |
| | 6000 | 7800 | - | - | - | 115% | 13800 | 4610 | 5990 | - | - | - | 10600 | 1820 | 10600 | 13110 | 520 | 2940 | 3580 | 2.4 | 13.5 | 16.4 | 3.61 | A |
| | 7800 | 7800 | - | - | - | 130% | 15600 | 5300 | 5300 | - | - | - | 10600 | 2160 | 10600 | 12960 | 540 | 2920 | 3560 | 2.5 | 13.4 | 16.3 | 3.63 | A |
| 3 Unit | 2200 | 2200 | 2200 | - | - | 55% | 6600 | 2200 | 2200 | 2200 | - | - | 6600 | 1320 | 6600 | 7580 | 490 | 1720 | 2090 | 2.2 | 7.9 | 9.6 | 3.84 | A |
| | 2200 | 2200 | 3300 | - | - | 64% | 7700 | 2200 | 2200 | 3300 | - | - | 7700 | 1320 | 7700 | 9010 | 490 | 2030 | 2460 | 2.2 | 9.3 | 11.3 | 3.79 | A |
| | 2200 | 2200 | 4000 | - | - | 70% | 8400 | 2200 | 2200 | 4000 | - | - | 8400 | 1350 | 8400 | 9800 | 500 | 2210 | 2680 | 2.3 | 10.1 | 12.3 | 3.80 | A |
| | 2200 | 2200 | 6000 | - | - | 87% | 10400 | 2050 | 2050 | 5590 | - | - | 9690 | 1530 | 9690 | 12170 | 510 | 2710 | 3320 | 2.3 | 12.4 | 15.2 | 3.58 | B |
| | 2200 | 2200 | 7800 | - | - | 102% | 12200 | 1780 | 1780 | 6300 | - | - | 9860 | 1750 | 9860 | 12170 | 530 | 2730 | 3340 | 2.4 | 12.5 | 15.3 | 3.61 | A |
| | 2200 | 3300 | 3300 | - | - | 73% | 8800 | 2200 | 3300 | 3300 | - | - | 8800 | 1320 | 8800 | 10740 | 490 | 2380 | 2920 | 2.2 | 10.9 | 13.4 | 3.70 | A |
| | 2200 | 3300 | 4000 | - | - | 79% | 9500 | 2200 | 3300 | 4000 | - | - | 9500 | 1350 | 9500 | 11380 | 500 | 2520 | 3090 | 2.3 | 11.5 | 14.1 | 3.77 | A |
| | 2200 | 3300 | 6000 | - | - | 96% | 11500 | 1870 | 2810 | 5110 | - | - | 9790 | 1530 | 9790 | 11850 | 510 | 2670 | 3230 | 2.3 | 12.2 | 14.8 | 3.67 | A |
| | 2200 | 3300 | 7800 | - | - | 111% | 13300 | 1650 | 2470 | 5850 | - | - | 9970 | 1860 | 9970 | 12170 | 530 | 2730 | 3340 | 2.4 | 12.5 | 15.3 | 3.65 | A |
| | 2200 | 4000 | 4000 | - | - | 85% | 10200 | 2090 | 3790 | 3790 | - | - | 9670 | 1500 | 9670 | 12170 | 500 | 2700 | 3310 | 2.3 | 12.4 | 15.1 | 3.58 | B |
| | 2200 | 4000 | 6000 | - | - | 102% | 12200 | 1780 | 3230 | 4850 | - | - | 9860 | 1720 | 9860 | 12170 | 520 | 2720 | 3320 | 2.4 | 12.4 | 15.2 | 3.63 | A |
| | 2200 | 4000 | 7800 | - | - | 117% | 14000 | 1580 | 2870 | 5590 | - | - | 10040 | 1890 | 10040 | 12320 | 540 | 2780 | 3380 | 2.5 | 12.7 | 15.5 | 3.61 | A |
| | 2200 | 6000 | 6000 | - | - | 118% | 14200 | 1560 | 4250 | 4250 | - | - | 10060 | 1860 | 10060 | 12320 | 530 | 2780 | 3380 | 2.4 | 12.7 | 15.5 | 3.62 | A |
| | 2200 | 6000 | 7800 | - | - | 133% | 16000 | 1490 | 4050 | 5270 | - | - | 10810 | 2200 | 10810 | 12800 | 550 | 2880 | 3520 | 2.5 | 13.2 | 16.1 | 3.75 | A |
| | 2200 | 7800 | 7800 | - | - | 148% | 17800 | 1360 | 4820 | 4820 | - | - | 11000 | 2280 | 11000 | 12960 | 570 | 2950 | 3590 | 2.6 | 13.5 | 16.4 | 3.73 | A |
| | 3300 | 3300 | 3300 | - | - | 83% | 9900 | 3210 | 3210 | 3210 | - | - | 9630 | 1470 | 9630 | 11850 | 490 | 2650 | 3210 | 2.2 | 12.1 | 14.7 | 3.63 | A |
| | 3300 | 3300 | 4000 | - | - | 88% | 10600 | 3020 | 3020 | 3660 | - | - | 9700 | 1500 | 9700 | 11530 | 500 | 2560 | 3140 | 2.3 | 11.7 | 14.4 | 3.79 | A |
| | 3300 | 3300 | 6000 | - | - | 105% | 12600 | 2590 | 2590 | 4710 | - | - | 9890 | 1680 | 9890 | 12320 | 510 | 2760 | 3360 | 2.3 | 12.6 | 15.4 | 3.58 | B |
| | 3300 | 3300 | 7800 | - | - | 120% | 14400 | 2440 | 2440 | 5770 | - | - | 10650 | 1860 | 10650 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.78 | A |
| | 3300 | 4000 | 4000 | - | - | 94% | 11300 | 2850 | 3460 | 3460 | - | - | 9770 | 1500 | 9770 | 11850 | 500 | 2660 | 3220 | 2.3 | 12.2 | 14.7 | 3.67 | A |
| | 3300 | 4000 | 6000 | - | - | 111% | 13300 | 2470 | 3000 | 4500 | - | - | 9970 | 1820 | 9970 | 12170 | 520 | 2720 | 3320 | 2.4 | 12.4 | 15.2 | 3.67 | A |
| | 3300 | 4000 | 7800 | - | - | 126% | 15100 | 2340 | 2840 | 5540 | - | - | 10720 | 1890 | 10720 | 12480 | 540 | 2830 | 3430 | 2.5 | 13.0 | 15.7 | 3.79 | A |
| | 3300 | 6000 | 6000 | - | - | 128% | 15300 | 2320 | 4210 | 4210 | - | - | 10740 | 1860 | 10740 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.81 | A |
| | 3300 | 6000 | 7800 | - | - | 143% | 17100 | 2120 | 3860 | 5020 | - | - | 11000 | 2200 | 11000 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.75 | A |
| | 3300 | 7800 | 7800 | - | - | 158% | 18900 | 1920 | 4540 | 4540 | - | - | 11000 | 2280 | 11000 | 13110 | 570 | 2990 | 3630 | 2.6 | 13.7 | 16.6 | 3.68 | A |
| | 4000 | 4000 | 4000 | - | - | 100% | 12000 | 3280 | 3280 | 3280 | - | - | 9840 | 1680 | 9840 | 12170 | 510 | 2710 | 3310 | 2.3 | 12.4 | 15.1 | 3.63 | A |
| | 4000 | 4000 | 6000 | - | - | 117% | 14000 | 2870 | 2870 | 4300 | - | - | 10040 | 1820 | 10040 | 12320 | 520 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.62 | A |
| | 4000 | 4000 | 7800 | - | - | 132% | 15800 | 2730 | 2730 | 5330 | - | - | 10790 | 2160 | 10790 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 4000 | 6000 | 6000 | - | - | 133% | 16000 | 2700 | 4050 | 4050 | - | - | 10800 | 2160 | 10800 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 4000 | 6000 | 7800 | - | - | 148% | 17800 | 2470 | 3710 | 4820 | - | - | 11000 | 2240 | 11000 | 12960 | 560 | 2930 | 3570 | 2.6 | 13.4 | 16.3 | 3.75 | A |
| | 4000 | 7800 | 7800 | - | - | 163% | 19600 | 2240 | 4380 | 4380 | - | - | 11000 | 2320 | 11000 | 13430 | 580 | 3040 | 3720 | 2.7 | 13.9 | 17.0 | 3.62 | A |
| | 6000 | 6000 | 6000 | - | - | 150% | 18000 | 3660 | 3670 | 3670 | - | - | 11000 | 2200 | 11000 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.75 | A |
| | 6000 | 6000 | 7800 | - | - | 165% | 19800 | 3330 | 3330 | 4340 | - | - | 11000 | 2280 | 11000 | 13430 | 570 | 3040 | 3710 | 2.6 | 13.9 | 17.0 | 3.62 | A |

# FJM Capacity Combination

## RJ100F5HXEA

Maldives P Series & Deluxe

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 4 Unit | 2200 | 2200 | 2200 | 2200 | - | 73% | 8800 | 2200 | 2200 | 2200 | 2200 | - | 8800 | 1400 | 8800 | 9800 | 520 | 2240 | 2700 | 2.4 | 10.3 | 12.4 | 3.93 | A |
| | 2200 | 2200 | 2200 | 3300 | - | 83% | 9900 | 2140 | 2140 | 2140 | 3210 | - | 9630 | 1560 | 9630 | 11380 | 520 | 2550 | 3120 | 2.4 | 11.7 | 14.3 | 3.78 | A |
| | 2200 | 2200 | 2200 | 4000 | - | 88% | 10600 | 2010 | 2010 | 2010 | 3660 | - | 9690 | 1590 | 9690 | 12170 | 530 | 2730 | 3330 | 2.4 | 12.5 | 15.2 | 3.55 | B |
| | 2200 | 2200 | 2200 | 6000 | - | 105% | 12600 | 1730 | 1730 | 1730 | 4710 | - | 9900 | 1780 | 9900 | 12170 | 540 | 2740 | 3350 | 2.5 | 12.5 | 15.3 | 3.61 | A |
| | 2200 | 2200 | 2200 | 7800 | - | 120% | 14400 | 1630 | 1630 | 1630 | 5770 | - | 10660 | 1960 | 10660 | 12320 | 560 | 2810 | 3410 | 2.6 | 12.9 | 15.6 | 3.79 | A |
| | 2200 | 2200 | 3300 | 3300 | - | 92% | 11000 | 1950 | 1950 | 2920 | 2920 | - | 9740 | 1560 | 9740 | 11530 | 520 | 2590 | 3160 | 2.4 | 11.9 | 14.5 | 3.76 | A |
| | 2200 | 2200 | 3300 | 4000 | - | 98% | 11700 | 1840 | 1840 | 2760 | 3350 | - | 9790 | 1590 | 9790 | 11850 | 530 | 2680 | 3250 | 2.4 | 12.3 | 14.9 | 3.65 | A |
| | 2200 | 2200 | 3300 | 6000 | - | 114% | 13700 | 1610 | 1610 | 2410 | 4380 | - | 10010 | 1890 | 10010 | 12170 | 540 | 2740 | 3350 | 2.5 | 12.5 | 15.3 | 3.65 | A |
| | 2200 | 2200 | 3300 | 7800 | - | 129% | 15500 | 1530 | 1530 | 2290 | 5410 | - | 10760 | 1960 | 10760 | 12480 | 560 | 2850 | 3450 | 2.6 | 13.0 | 15.8 | 3.78 | A |
| | 2200 | 2200 | 4000 | 4000 | - | 103% | 12400 | 1750 | 1750 | 3190 | 3190 | - | 9880 | 1750 | 9880 | 12170 | 530 | 2730 | 3340 | 2.4 | 12.5 | 15.3 | 3.62 | A |
| | 2200 | 2200 | 4000 | 6000 | - | 120% | 14400 | 1630 | 1630 | 2960 | 4440 | - | 10660 | 1930 | 10660 | 12320 | 550 | 2790 | 3390 | 2.5 | 12.8 | 15.5 | 3.82 | A |
| | 2200 | 2200 | 4000 | 7800 | - | 135% | 16200 | 1470 | 1470 | 2670 | 5210 | - | 10820 | 2280 | 10820 | 12800 | 570 | 2900 | 3540 | 2.6 | 13.3 | 16.2 | 3.73 | A |
| | 2200 | 2200 | 6000 | 6000 | - | 137% | 16400 | 1460 | 1460 | 3970 | 3970 | - | 10860 | 2240 | 10860 | 12800 | 560 | 2890 | 3530 | 2.6 | 13.2 | 16.2 | 3.76 | A |
| | 2200 | 2200 | 6000 | 7800 | - | 152% | 18200 | 1330 | 1330 | 3630 | 4710 | - | 11000 | 2320 | 11000 | 12960 | 580 | 2960 | 3600 | 2.7 | 13.5 | 16.5 | 3.72 | A |
| | 2200 | 3300 | 3300 | 3300 | - | 101% | 12100 | 1790 | 2690 | 2690 | 2690 | - | 9860 | 1720 | 9860 | 12170 | 520 | 2720 | 3330 | 2.4 | 12.4 | 15.2 | 3.63 | A |
| | 2200 | 3300 | 3300 | 4000 | - | 107% | 12800 | 1710 | 2560 | 2560 | 3100 | - | 9930 | 1750 | 9930 | 12320 | 530 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.58 | B |
| | 2200 | 3300 | 3300 | 6000 | - | 123% | 14800 | 1590 | 2380 | 2380 | 4330 | - | 10680 | 1890 | 10680 | 12480 | 540 | 2830 | 3430 | 2.5 | 13.0 | 15.7 | 3.77 | A |
| | 2200 | 3300 | 3300 | 7800 | - | 138% | 16600 | 1440 | 2160 | 2160 | 5100 | - | 10860 | 2240 | 10860 | 12960 | 560 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.69 | A |
| | 2200 | 3300 | 4000 | 4000 | - | 113% | 13500 | 1630 | 2440 | 2960 | 2960 | - | 9990 | 1860 | 9990 | 12170 | 530 | 2730 | 3340 | 2.4 | 12.5 | 15.3 | 3.66 | A |
| | 2200 | 3300 | 4000 | 6000 | - | 129% | 15500 | 1530 | 2290 | 2780 | 4170 | - | 10770 | 1930 | 10770 | 12480 | 550 | 2840 | 3440 | 2.5 | 13.0 | 15.7 | 3.79 | A |
| | 2200 | 3300 | 4000 | 7800 | - | 144% | 17300 | 1400 | 2100 | 2540 | 4960 | - | 11000 | 2280 | 11000 | 12960 | 570 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.74 | A |
| | 2200 | 3300 | 6000 | 6000 | - | 146% | 17500 | 1390 | 2070 | 3770 | 3770 | - | 11000 | 2240 | 11000 | 12960 | 560 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.74 | A |
| | 2200 | 3300 | 6000 | 7800 | - | 161% | 19300 | 1250 | 1880 | 3420 | 4450 | - | 11000 | 2320 | 11000 | 13110 | 580 | 3000 | 3640 | 2.7 | 13.7 | 16.7 | 3.67 | A |
| | 2200 | 4000 | 4000 | 4000 | - | 118% | 14200 | 1560 | 2830 | 2830 | 2830 | - | 10050 | 1890 | 10050 | 12320 | 540 | 2780 | 3380 | 2.5 | 12.7 | 15.5 | 3.62 | A |
| | 2200 | 4000 | 4000 | 6000 | - | 135% | 16200 | 1470 | 2670 | 2670 | 4010 | - | 10820 | 2200 | 10820 | 12800 | 550 | 2880 | 3520 | 2.5 | 13.2 | 16.1 | 3.76 | A |
| | 2200 | 4000 | 4000 | 7800 | - | 150% | 18000 | 1350 | 2440 | 2440 | 4770 | - | 11000 | 2280 | 11000 | 12960 | 570 | 2950 | 3590 | 2.6 | 13.5 | 16.4 | 3.73 | A |
| | 2200 | 4000 | 6000 | 6000 | - | 152% | 18200 | 1330 | 2410 | 3630 | 3630 | - | 11000 | 2280 | 11000 | 12960 | 570 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.74 | A |
| | 2200 | 4000 | 6000 | 7800 | - | 167% | 20000 | 1210 | 2200 | 3300 | 4290 | - | 11000 | 2360 | 11000 | 13430 | 590 | 3050 | 3730 | 2.7 | 14.0 | 17.1 | 3.61 | A |
| | 2200 | 6000 | 6000 | 6000 | - | 168% | 20200 | 1190 | 3270 | 3270 | 3270 | - | 11000 | 2320 | 11000 | 13430 | 580 | 3050 | 3720 | 2.7 | 14.0 | 17.0 | 3.61 | A |
| | 3300 | 3300 | 3300 | 3300 | - | 110% | 13200 | 2490 | 2490 | 2490 | 2490 | - | 9960 | 1820 | 9960 | 12480 | 520 | 2810 | 3410 | 2.4 | 12.9 | 15.6 | 3.54 | B |
| | 3300 | 3300 | 3300 | 4000 | - | 116% | 13900 | 2380 | 2380 | 2380 | 2880 | - | 10020 | 1860 | 10020 | 12320 | 530 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.62 | A |
| | 3300 | 3300 | 3300 | 6000 | - | 133% | 15900 | 2240 | 2240 | 2240 | 4080 | - | 10800 | 2160 | 10800 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 3300 | 3300 | 3300 | 7800 | - | 148% | 17700 | 2050 | 2050 | 2050 | 4850 | - | 11000 | 2240 | 11000 | 12960 | 560 | 2940 | 3580 | 2.6 | 13.5 | 16.4 | 3.74 | A |
| | 3300 | 3300 | 4000 | 4000 | - | 122% | 14600 | 2410 | 2410 | 2920 | 2920 | - | 10660 | 1860 | 10660 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.78 | A |
| | 3300 | 3300 | 4000 | 6000 | - | 138% | 16600 | 2160 | 2160 | 2620 | 3930 | - | 10870 | 2200 | 10870 | 12960 | 550 | 2920 | 3560 | 2.5 | 13.4 | 16.3 | 3.72 | A |
| | 3300 | 3300 | 4000 | 7800 | - | 153% | 18400 | 1970 | 1970 | 2400 | 4660 | - | 11000 | 2280 | 11000 | 13110 | 570 | 2990 | 3620 | 2.6 | 13.7 | 16.6 | 3.68 | A |
| | 3300 | 3300 | 6000 | 6000 | - | 155% | 18600 | 1950 | 1950 | 3550 | 3550 | - | 11000 | 2240 | 11000 | 13110 | 560 | 2980 | 3620 | 2.6 | 13.6 | 16.6 | 3.69 | A |
| | 3300 | 3300 | 6000 | 7800 | - | 170% | 20400 | 1780 | 1780 | 3240 | 4200 | - | 11000 | 2320 | 11000 | 13590 | 580 | 3090 | 3760 | 2.7 | 14.1 | 17.2 | 3.56 | B |
| | 3300 | 4000 | 4000 | 4000 | - | 128% | 15300 | 2320 | 2810 | 2810 | 2810 | - | 10750 | 1890 | 10750 | 12480 | 540 | 2830 | 3430 | 2.5 | 13.0 | 15.7 | 3.80 | A |
| | 3300 | 4000 | 4000 | 6000 | - | 144% | 17300 | 2100 | 2540 | 2540 | 3820 | - | 11000 | 2200 | 11000 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.75 | A |
| | 3300 | 4000 | 4000 | 7800 | - | 159% | 19100 | 1910 | 2300 | 2300 | 4490 | - | 11000 | 2280 | 11000 | 13110 | 570 | 2990 | 3630 | 2.6 | 13.7 | 16.6 | 3.68 | A |
| | 3300 | 4000 | 6000 | 6000 | - | 161% | 19300 | 1880 | 2280 | 3420 | 3420 | - | 11000 | 2280 | 11000 | 13110 | 570 | 2990 | 3620 | 2.6 | 13.7 | 16.6 | 3.68 | A |
| | 4000 | 4000 | 4000 | 4000 | - | 133% | 16000 | 2700 | 2700 | 2700 | 2700 | - | 10800 | 2160 | 10800 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 4000 | 4000 | 4000 | 6000 | - | 150% | 18000 | 2440 | 2440 | 2440 | 3680 | - | 11000 | 2240 | 11000 | 12960 | 560 | 2930 | 3570 | 2.6 | 13.4 | 16.3 | 3.75 | A |
| | 4000 | 4000 | 4000 | 7800 | - | 165% | 19800 | 2220 | 2220 | 2220 | 4340 | - | 11000 | 2320 | 11000 | 13430 | 580 | 3040 | 3720 | 2.7 | 13.9 | 17.0 | 3.62 | A |
| | 4000 | 4000 | 6000 | 6000 | - | 167% | 20000 | 2200 | 2200 | 3300 | 3300 | - | 11000 | 2280 | 11000 | 13430 | 570 | 3040 | 3710 | 2.6 | 13.9 | 17.0 | 3.62 | A |

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 5 Unit | 2200 | 2200 | 2200 | 2200 | 2200 | 92% | 11000 | 2200 | 2200 | 2200 | 2200 | 2200 | 11000 | 1650 | 11000 | 13110 | 550 | 2970 | 3610 | 2.5 | 13.6 | 16.5 | 3.70 | A |
| | 2200 | 2200 | 2200 | 2200 | 3300 | 101% | 12100 | 2080 | 2080 | 2080 | 2080 | 3120 | 11440 | 1820 | 11440 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.90 | A |
| | 2200 | 2200 | 2200 | 2200 | 4000 | 107% | 12800 | 1990 | 1990 | 1990 | 1990 | 3620 | 11580 | 1850 | 11580 | 13110 | 560 | 2980 | 3610 | 2.6 | 13.6 | 16.5 | 3.89 | A |
| | 2200 | 2200 | 2200 | 2200 | 6000 | 123% | 14800 | 1710 | 1710 | 1710 | 1710 | 4660 | 11500 | 2000 | 11500 | 13430 | 570 | 3040 | 3710 | 2.6 | 13.9 | 17.0 | 3.78 | A |
| | 2200 | 2200 | 2200 | 2200 | 7800 | 138% | 16600 | 1580 | 1580 | 1580 | 1580 | 5610 | 11930 | 2360 | 11930 | 13750 | 590 | 3140 | 3810 | 2.7 | 14.4 | 17.4 | 3.80 | A |
| | 2200 | 2200 | 2200 | 3300 | 3300 | 110% | 13200 | 1950 | 1950 | 1950 | 2930 | 2930 | 11710 | 1930 | 11710 | 13430 | 550 | 3020 | 3690 | 2.5 | 13.8 | 16.9 | 3.88 | A |
| | 2200 | 2200 | 2200 | 3300 | 4000 | 116% | 13900 | 1880 | 1880 | 1880 | 2820 | 3420 | 11880 | 1960 | 11880 | 13110 | 560 | 2980 | 3610 | 2.6 | 13.6 | 16.5 | 3.99 | A |
| | 2200 | 2200 | 2200 | 3300 | 6000 | 133% | 15900 | 1630 | 1630 | 1630 | 2440 | 4450 | 11780 | 2280 | 11780 | 13590 | 570 | 3080 | 3750 | 2.6 | 14.1 | 17.2 | 3.82 | A |
| | 2200 | 2200 | 2200 | 3300 | 7800 | 148% | 17700 | 1490 | 1490 | 1490 | 2240 | 5290 | 12000 | 2360 | 12000 | 13900 | 590 | 3190 | 3860 | 2.7 | 14.6 | 17.7 | 3.76 | A |
| | 2200 | 2200 | 2200 | 4000 | 4000 | 122% | 14600 | 1730 | 1730 | 1730 | 3140 | 3140 | 11470 | 1960 | 11470 | 13430 | 560 | 3030 | 3700 | 2.6 | 13.9 | 16.9 | 3.79 | A |
| | 2200 | 2200 | 2200 | 4000 | 6000 | 138% | 16600 | 1580 | 1580 | 1580 | 2880 | 4320 | 11940 | 2320 | 11940 | 13750 | 580 | 3130 | 3800 | 2.7 | 14.3 | 17.4 | 3.81 | A |
| | 2200 | 2200 | 2200 | 4000 | 7800 | 153% | 18400 | 1430 | 1430 | 1430 | 2620 | 5090 | 12000 | 2400 | 12000 | 14000 | 600 | 3240 | 3940 | 2.7 | 14.8 | 18.0 | 3.70 | A |
| | 2200 | 2200 | 2200 | 6000 | 6000 | 155% | 18600 | 1420 | 1420 | 1420 | 3870 | 3870 | 12000 | 2360 | 12000 | 14000 | 590 | 3230 | 3940 | 2.7 | 14.8 | 18.0 | 3.72 | A |
| | 2200 | 2200 | 3300 | 3300 | 3300 | 119% | 14300 | 1840 | 1840 | 2760 | 2760 | 2760 | 11960 | 1930 | 11960 | 13430 | 550 | 3020 | 3690 | 2.5 | 13.8 | 16.9 | 3.96 | A |
| | 2200 | 2200 | 3300 | 3300 | 4000 | 125% | 15000 | 1690 | 1690 | 2540 | 2540 | 3080 | 11540 | 1960 | 11540 | 13590 | 560 | 3070 | 3740 | 2.6 | 14.1 | 17.1 | 3.76 | A |
| | 2200 | 2200 | 3300 | 3300 | 6000 | 142% | 17000 | 1550 | 1550 | 2330 | 2330 | 4240 | 12000 | 2280 | 12000 | 13900 | 570 | 3170 | 3840 | 2.6 | 14.5 | 17.6 | 3.79 | A |
| | 2200 | 2200 | 3300 | 3300 | 7800 | 157% | 18800 | 1400 | 1400 | 2110 | 2110 | 4980 | 12000 | 2360 | 12000 | 14000 | 590 | 3280 | 3940 | 2.7 | 15.0 | 18.0 | 3.66 | A |
| | 2200 | 2200 | 3300 | 4000 | 4000 | 131% | 15700 | 1640 | 1640 | 2470 | 2990 | 2990 | 11730 | 2240 | 11730 | 13590 | 560 | 3070 | 3740 | 2.6 | 14.1 | 17.1 | 3.82 | A |
| | 2200 | 2200 | 3300 | 4000 | 6000 | 148% | 17700 | 1490 | 1490 | 2240 | 2710 | 4070 | 12000 | 2320 | 12000 | 13900 | 580 | 3170 | 3840 | 2.7 | 14.5 | 17.6 | 3.79 | A |
| | 2200 | 2200 | 3300 | 4000 | 7800 | 163% | 19500 | 1350 | 1350 | 2040 | 2460 | 4800 | 12000 | 2400 | 12000 | 14000 | 600 | 3280 | 3940 | 2.7 | 15.0 | 18.0 | 3.66 | A |
| | 2200 | 2200 | 3300 | 6000 | 6000 | 164% | 19700 | 1340 | 1340 | 2020 | 3650 | 3650 | 12000 | 2360 | 12000 | 14000 | 590 | 3280 | 3940 | 2.7 | 15.0 | 18.0 | 3.66 | A |
| | 2200 | 2200 | 4000 | 4000 | 4000 | 137% | 16400 | 1600 | 1600 | 2900 | 2900 | 2900 | 11900 | 2280 | 11900 | 13750 | 570 | 3120 | 3790 | 2.6 | 14.3 | 17.3 | 3.81 | A |
| | 2200 | 2200 | 4000 | 4000 | 6000 | 153% | 18400 | 1430 | 1430 | 2610 | 2610 | 3920 | 12000 | 2320 | 12000 | 14000 | 580 | 3220 | 3930 | 2.7 | 14.7 | 18.0 | 3.73 | A |
| | 2200 | 3300 | 3300 | 3300 | 3300 | 128% | 15400 | 1670 | 2500 | 2500 | 2500 | 2500 | 11670 | 1930 | 11670 | 13590 | 550 | 3060 | 3730 | 2.5 | 14.0 | 17.1 | 3.81 | A |
| | 2200 | 3300 | 3300 | 3300 | 4000 | 134% | 16100 | 1620 | 2420 | 2420 | 2420 | 2940 | 11820 | 2240 | 11820 | 13750 | 560 | 3110 | 3780 | 2.6 | 14.2 | 17.3 | 3.80 | A |
| | 2200 | 3300 | 3300 | 3300 | 6000 | 151% | 18100 | 1460 | 2190 | 2190 | 2190 | 3970 | 12000 | 2280 | 12000 | 14000 | 570 | 3210 | 3920 | 2.6 | 14.7 | 17.9 | 3.74 | A |
| | 2200 | 3300 | 3300 | 3300 | 7800 | 166% | 19900 | 1330 | 1990 | 1990 | 1990 | 4700 | 12000 | 2360 | 12000 | 14000 | 590 | 3320 | 3940 | 2.7 | 15.2 | 18.0 | 3.61 | A |
| | 2200 | 3300 | 3300 | 4000 | 4000 | 140% | 16800 | 1570 | 2350 | 2360 | 2860 | 2860 | 12000 | 2240 | 12000 | 13900 | 560 | 3160 | 3830 | 2.6 | 14.5 | 17.5 | 3.80 | A |
| | 2200 | 3300 | 3300 | 4000 | 6000 | 157% | 18800 | 1400 | 2110 | 2110 | 2550 | 3830 | 12000 | 2320 | 12000 | 14000 | 580 | 3260 | 3920 | 2.7 | 14.9 | 17.9 | 3.68 | A |
| | 2200 | 3300 | 3300 | 4000 | 7800 | 172% | 20600 | 1290 | 1920 | 1920 | 2330 | 4540 | 12000 | 2400 | 12000 | 14000 | 600 | 3370 | 3940 | 2.7 | 15.4 | 18.0 | 3.56 | B |
| | 2200 | 3300 | 3300 | 6000 | 6000 | 173% | 20800 | 1280 | 1900 | 1900 | 3460 | 3460 | 12000 | 2360 | 12000 | 14000 | 590 | 3370 | 3940 | 2.7 | 15.4 | 18.0 | 3.56 | B |
| | 2200 | 3300 | 4000 | 4000 | 4000 | 146% | 17500 | 1520 | 2260 | 2740 | 2740 | 2740 | 12000 | 2280 | 12000 | 13900 | 570 | 3160 | 3830 | 2.6 | 14.5 | 17.5 | 3.80 | A |
| | 2200 | 3300 | 4000 | 4000 | 6000 | 163% | 19500 | 1360 | 2030 | 2460 | 2460 | 3690 | 12000 | 2320 | 12000 | 14000 | 580 | 3270 | 3930 | 2.7 | 15.0 | 18.0 | 3.67 | A |
| | 2200 | 4000 | 4000 | 4000 | 4000 | 152% | 18200 | 1440 | 2640 | 2640 | 2640 | 2640 | 12000 | 2280 | 12000 | 14000 | 570 | 3210 | 3920 | 2.6 | 14.7 | 17.9 | 3.74 | A |
| | 3300 | 3300 | 3300 | 3300 | 3300 | 138% | 16500 | 2400 | 2400 | 2400 | 2400 | 2400 | 12000 | 3400 | 12000 | 14000 | 550 | 2930 | 3900 | 2.5 | 13.4 | 17.8 | 4.10 | A |
| | 3300 | 3300 | 3300 | 3300 | 4000 | 143% | 17200 | 2300 | 2300 | 2300 | 2300 | 2800 | 12000 | 2240 | 12000 | 13900 | 560 | 3150 | 3820 | 2.6 | 14.4 | 17.5 | 3.81 | A |
| | 3300 | 3300 | 3300 | 3300 | 6000 | 160% | 19200 | 2060 | 2060 | 2060 | 2060 | 3760 | 12000 | 2280 | 12000 | 14000 | 570 | 3260 | 3920 | 2.6 | 14.9 | 17.9 | 3.68 | A |
| | 3300 | 3300 | 3300 | 3300 | 7800 | 175% | 21000 | 1890 | 1890 | 1890 | 1890 | 4440 | 12000 | 2360 | 12000 | 14000 | 590 | 3370 | 3940 | 2.7 | 15.4 | 18.0 | 3.56 | B |
| | 3300 | 3300 | 3300 | 4000 | 4000 | 149% | 17900 | 2210 | 2210 | 2210 | 2680 | 2690 | 12000 | 2240 | 12000 | 14000 | 560 | 3200 | 3910 | 2.6 | 14.6 | 17.9 | 3.75 | A |
| | 3300 | 3300 | 3300 | 4000 | 6000 | 166% | 19900 | 1990 | 1990 | 1990 | 2410 | 3620 | 12000 | 2320 | 12000 | 14000 | 580 | 3310 | 3920 | 2.7 | 15.1 | 17.9 | 3.63 | A |
| | 3300 | 3300 | 4000 | 4000 | 4000 | 155% | 18600 | 2130 | 2130 | 2580 | 2580 | 2580 | 12000 | 2280 | 12000 | 14000 | 570 | 3250 | 3910 | 2.6 | 14.9 | 17.9 | 3.69 | A |
| | 3300 | 3300 | 4000 | 4000 | 6000 | 172% | 20600 | 1920 | 1920 | 2330 | 2330 | 3500 | 12000 | 3400 | 12000 | 14000 | 580 | 3360 | 3930 | 2.7 | 15.4 | 18.0 | 3.57 | B |
| | 3300 | 4000 | 4000 | 4000 | 4000 | 161% | 19300 | 2040 | 2490 | 2490 | 2490 | 2490 | 12000 | 2280 | 12000 | 14000 | 570 | 3260 | 3920 | 2.6 | 14.9 | 17.9 | 3.68 | A |

1. Heating capacity is based on 20˚CDB (indoor temperature), 7˚CDB/6˚CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2200, 3300, 4000, 6000, 7800W class: Wall Mounted Madives P Series, Maldives DELUXE [only for AQV**PSBN, AQV***PMEN, AQV***PMBN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 20.6 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.

# FJM Capacity Combination

## RJ100F5HXEA

Jungfrau Y-series

### COOLING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Cooling Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 2500 | - | - | - | - | 25% | 2500 | 2500 | - | - | - | - | 2500 | 1600 | 2500 | 3630 | 580 | 800 | 1210 | 2.7 | 3.7 | 5.5 | 3.13 | B |
| | 3500 | - | - | - | - | 35% | 3500 | 3500 | - | - | - | - | 3500 | 1620 | 3500 | 4740 | 590 | 1070 | 1580 | 2.7 | 4.9 | 7.2 | 3.27 | A |
| | 5000 | - | - | - | - | 50% | 5000 | 5000 | - | - | - | - | 5000 | 1650 | 5000 | 6480 | 600 | 1500 | 2160 | 2.7 | 6.9 | 9.9 | 3.33 | A |
| 2 Unit | 2500 | 2500 | - | - | - | 50% | 5000 | 2500 | 2500 | - | - | - | 5000 | 1680 | 5000 | 6320 | 610 | 1600 | 2120 | 2.8 | 7.3 | 9.7 | 3.13 | B |
| | 2500 | 3500 | - | - | - | 60% | 6000 | 2500 | 3500 | - | - | - | 6000 | 1710 | 6000 | 7270 | 620 | 1840 | 2430 | 2.8 | 8.4 | 11.1 | 3.26 | A |
| | 2500 | 5000 | - | - | - | 75% | 7500 | 2500 | 5000 | - | - | - | 7500 | 2210 | 7500 | 9320 | 630 | 2340 | 3120 | 2.9 | 10.7 | 14.3 | 3.21 | A |
| | 3500 | 3500 | - | - | - | 70% | 7000 | 3500 | 3500 | - | - | - | 7000 | 2170 | 7000 | 8530 | 620 | 2130 | 2850 | 2.8 | 9.7 | 13.0 | 3.29 | A |
| | 3500 | 5000 | - | - | - | 85% | 8500 | 3300 | 4720 | - | - | - | 8020 | 2240 | 8020 | 9950 | 640 | 2490 | 3330 | 2.9 | 11.4 | 15.2 | 3.22 | A |
| | 5000 | 5000 | - | - | - | 100% | 10000 | 4280 | 4280 | - | - | - | 8560 | 2440 | 8560 | 10430 | 650 | 2650 | 3500 | 3 | 12.1 | 16.0 | 3.23 | A |
| 3 Unit | 2500 | 2500 | 2500 | - | - | 75% | 7500 | 2500 | 2500 | 2500 | - | - | 7500 | 2240 | 7500 | 8850 | 640 | 2250 | 2970 | 2.9 | 10.3 | 13.6 | 3.33 | A |
| | 2500 | 2500 | 3500 | - | - | 85% | 8500 | 2500 | 2500 | 3500 | - | - | 8500 | 2280 | 8500 | 9950 | 650 | 2500 | 3340 | 3 | 11.4 | 15.3 | 3.40 | A |
| | 2500 | 2500 | 5000 | - | - | 100% | 10000 | 2210 | 2210 | 4430 | - | - | 8850 | 2480 | 8850 | 10270 | 660 | 2610 | 3450 | 3 | 11.9 | 15.8 | 3.39 | A |
| | 2500 | 3500 | 3500 | - | - | 95% | 9500 | 2310 | 3230 | 3230 | - | - | 8770 | 2280 | 8770 | 10270 | 650 | 2600 | 3440 | 3 | 11.9 | 15.7 | 3.37 | A |
| | 2500 | 3500 | 5000 | - | - | 110% | 11000 | 1980 | 2770 | 3950 | - | - | 8700 | 2510 | 8700 | 10430 | 670 | 2660 | 3510 | 3.1 | 12.2 | 16.1 | 3.27 | A |
| | 2500 | 5000 | 5000 | - | - | 125% | 12500 | 1800 | 3600 | 3600 | - | - | 9000 | 2720 | 9000 | 10900 | 680 | 2770 | 3680 | 3.1 | 12.7 | 16.8 | 3.25 | A |
| | 3500 | 3500 | 3500 | - | - | 105% | 10500 | 2980 | 2980 | 2980 | - | - | 8940 | 2480 | 8940 | 10430 | 660 | 2650 | 3500 | 3 | 12.1 | 16.0 | 3.37 | A |
| | 3500 | 3500 | 5000 | - | - | 120% | 12000 | 2600 | 2600 | 3710 | - | - | 8910 | 2680 | 8910 | 10740 | 670 | 2710 | 3620 | 3.1 | 12.4 | 16.6 | 3.29 | A |
| | 3500 | 5000 | 5000 | - | - | 135% | 13500 | 2390 | 3410 | 3410 | - | - | 9210 | 3110 | 9210 | 11000 | 690 | 2820 | 3740 | 3.2 | 12.9 | 17.1 | 3.27 | A |
| | 5000 | 5000 | 5000 | - | - | 150% | 15000 | 3260 | 3270 | 3270 | - | - | 9800 | 3150 | 9800 | 11000 | 700 | 2790 | 3750 | 3.2 | 12.8 | 17.2 | 3.51 | A |
| 4 Unit | 2500 | 2500 | 2500 | 2500 | - | 100% | 10000 | 2210 | 2210 | 2210 | 2210 | - | 8840 | 2510 | 8840 | 10270 | 670 | 2620 | 3460 | 3.1 | 12.0 | 15.8 | 3.37 | A |
| | 2500 | 2500 | 2500 | 3500 | - | 110% | 11000 | 1980 | 1980 | 1980 | 2770 | - | 8710 | 2550 | 8710 | 10430 | 680 | 2670 | 3520 | 3.1 | 12.2 | 16.1 | 3.26 | A |
| | 2500 | 2500 | 2500 | 5000 | - | 125% | 12500 | 1800 | 1800 | 1800 | 3600 | - | 9000 | 2760 | 9000 | 10900 | 690 | 2780 | 3690 | 3.2 | 12.7 | 16.9 | 3.24 | A |
| | 2500 | 2500 | 3500 | 3500 | - | 120% | 12000 | 1850 | 1850 | 2600 | 2600 | - | 8900 | 2720 | 8900 | 10740 | 680 | 2720 | 3630 | 3.1 | 12.4 | 16.6 | 3.27 | A |
| | 2500 | 2500 | 3500 | 5000 | - | 135% | 13500 | 1700 | 1700 | 2390 | 3410 | - | 9200 | 3150 | 9200 | 11000 | 700 | 2830 | 3750 | 3.2 | 13.0 | 17.2 | 3.25 | A |
| | 2500 | 2500 | 5000 | 5000 | - | 150% | 15000 | 1630 | 1630 | 3270 | 3270 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2800 | 3760 | 3.2 | 12.8 | 17.2 | 3.50 | A |
| | 2500 | 3500 | 3500 | 3500 | - | 130% | 13000 | 1750 | 2450 | 2450 | 2450 | - | 9100 | 3110 | 9100 | 10900 | 690 | 2780 | 3690 | 3.2 | 12.7 | 16.9 | 3.27 | A |
| | 2500 | 3500 | 3500 | 5000 | - | 145% | 14500 | 1620 | 2270 | 2270 | 3240 | - | 9400 | 3150 | 9400 | 11000 | 700 | 2790 | 3750 | 3.2 | 12.8 | 17.2 | 3.37 | A |
| | 2500 | 3500 | 5000 | 5000 | - | 160% | 16000 | 1540 | 2140 | 3060 | 3060 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2850 | 3770 | 3.3 | 13.0 | 17.3 | 3.44 | A |
| | 3500 | 3500 | 3500 | 3500 | - | 140% | 14000 | 2330 | 2330 | 2330 | 2330 | - | 9320 | 3110 | 9320 | 11000 | 690 | 2830 | 3740 | 3.2 | 13.0 | 17.1 | 3.29 | A |
| | 3500 | 3500 | 3500 | 5000 | - | 155% | 15500 | 2210 | 2210 | 2210 | 3170 | - | 9800 | 3200 | 9800 | 11000 | 710 | 2840 | 3760 | 3.2 | 13.0 | 17.2 | 3.45 | A |
| | 3500 | 3500 | 5000 | 5000 | - | 170% | 17000 | 2020 | 2020 | 2880 | 2880 | - | 9800 | 3240 | 9800 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.37 | A |
| 5 Unit | 2500 | 2500 | 2500 | 2500 | 2500 | 125% | 12500 | 2000 | 2000 | 2000 | 2000 | 2000 | 10000 | 3000 | 10000 | 11000 | 700 | 2900 | 3700 | 3.2 | 13.3 | 16.9 | 3.45 | A |
| | 2500 | 2500 | 2500 | 2500 | 3500 | 135% | 13500 | 1850 | 1850 | 1850 | 1850 | 2600 | 10000 | 3200 | 10000 | 11000 | 710 | 2840 | 3760 | 3.2 | 13.0 | 17.2 | 3.52 | A |
| | 2500 | 2500 | 2500 | 2500 | 5000 | 150% | 15000 | 1670 | 1670 | 1670 | 1670 | 3320 | 10000 | 3240 | 10000 | 11000 | 720 | 2810 | 3770 | 3.3 | 12.9 | 17.3 | 3.56 | A |
| | 2500 | 2500 | 2500 | 3500 | 3500 | 145% | 14500 | 1720 | 1720 | 1720 | 2420 | 2420 | 10000 | 3200 | 10000 | 11000 | 710 | 2800 | 3760 | 3.2 | 12.8 | 17.2 | 3.57 | A |
| | 2500 | 2500 | 2500 | 3500 | 5000 | 160% | 16000 | 1560 | 1560 | 1560 | 2190 | 3130 | 10000 | 3290 | 10000 | 11000 | 730 | 2860 | 3780 | 3.3 | 13.1 | 17.3 | 3.50 | A |
| | 2500 | 2500 | 3500 | 3500 | 3500 | 155% | 15500 | 1610 | 1610 | 2260 | 2260 | 2260 | 10000 | 3240 | 10000 | 11000 | 720 | 2850 | 3770 | 3.3 | 13.0 | 17.3 | 3.51 | A |
| | 2500 | 2500 | 3500 | 3500 | 5000 | 170% | 17000 | 1470 | 1470 | 2060 | 2060 | 2940 | 10000 | 3290 | 10000 | 11000 | 730 | 2920 | 3780 | 3.3 | 13.4 | 17.3 | 3.42 | A |
| | 2500 | 3500 | 3500 | 3500 | 3500 | 165% | 16500 | 1520 | 2120 | 2120 | 2120 | 2120 | 10000 | 3240 | 10000 | 11000 | 720 | 2910 | 3770 | 3.3 | 13.3 | 17.3 | 3.44 | A |

1. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 2500, 3500, 5000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 17.0 kW (@ Cooling)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.

### HEATING

| Outdoor Unit | Indoor Unit Combination | | | | | | | Heating Capacity (W) | | | | | | Capacity W | | | Power Consumption W | | | Current A | | | EER | EG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | A | B | C | D | E | % | Total | A | B | C | D | E | Total | MIN | NOM | MAX | MIN | NOM | MAX | MIN | NOM | MAX | | |
| 1 Unit | 3300 | - | - | - | - | 28% | 3300 | 3200 | - | - | - | - | 3200 | 1160 | 3200 | 4270 | 430 | 1070 | 1284 | 2 | 4.9 | 5.9 | 2.99 | D |
| | 4000 | - | - | - | - | 33% | 4000 | 4000 | - | - | - | - | 4000 | 1190 | 4000 | 5210 | 440 | 1280 | 1536 | 2 | 5.9 | 7.0 | 3.13 | D |
| | 6000 | - | - | - | - | 50% | 6000 | 6000 | - | - | - | - | 6000 | 1220 | 6000 | 7430 | 450 | 1980 | 2376 | 2.1 | 9.1 | 10.9 | 3.03 | D |
| 2 Unit | 3300 | 3300 | - | - | - | 55% | 6600 | 3300 | 3300 | - | - | - | 6600 | 1240 | 6600 | 8220 | 460 | 1820 | 2230 | 2.1 | 8.3 | 10.2 | 3.63 | A |
| | 3300 | 4000 | - | - | - | 61% | 7300 | 3300 | 4000 | - | - | - | 7300 | 1270 | 7300 | 9010 | 470 | 2010 | 2440 | 2.2 | 9.2 | 11.2 | 3.63 | A |
| | 3300 | 6000 | - | - | - | 78% | 9300 | 3300 | 6000 | - | - | - | 9300 | 1300 | 9300 | 11690 | 480 | 2590 | 3160 | 2.2 | 11.9 | 14.5 | 3.59 | B |
| | 4000 | 4000 | - | - | - | 67% | 8000 | 4000 | 4000 | - | - | - | 8000 | 1270 | 8000 | 9800 | 470 | 2190 | 2650 | 2.2 | 10.0 | 12.1 | 3.65 | A |
| | 4000 | 6000 | - | - | - | 83% | 10000 | 4000 | 6000 | - | - | - | 10000 | 1470 | 10000 | 12320 | 490 | 2730 | 3330 | 2.2 | 12.5 | 15.2 | 3.66 | A |
| | 6000 | 6000 | - | - | - | 100% | 12000 | 5300 | 5300 | - | - | - | 10600 | 1650 | 10600 | 13110 | 500 | 2920 | 3560 | 2.3 | 13.4 | 16.3 | 3.63 | A |
| 3 Unit | 3300 | 3300 | 3300 | - | - | 83% | 9900 | 3210 | 3210 | 3210 | - | - | 9630 | 1470 | 9630 | 11850 | 490 | 2650 | 3210 | 2.2 | 12.1 | 14.7 | 3.63 | A |
| | 3300 | 3300 | 4000 | - | - | 88% | 10600 | 3020 | 3020 | 3660 | - | - | 9700 | 1500 | 9700 | 11530 | 500 | 2560 | 3140 | 2.3 | 11.7 | 14.4 | 3.79 | A |
| | 3300 | 3300 | 6000 | - | - | 105% | 12600 | 2590 | 2590 | 4710 | - | - | 9890 | 1680 | 9890 | 12320 | 510 | 2760 | 3360 | 2.3 | 12.6 | 15.4 | 3.58 | B |
| | 3300 | 4000 | 4000 | - | - | 94% | 11300 | 2850 | 3460 | 3460 | - | - | 9770 | 1500 | 9770 | 11850 | 500 | 2660 | 3220 | 2.3 | 12.2 | 14.7 | 3.67 | A |
| | 3300 | 4000 | 6000 | - | - | 111% | 13300 | 2470 | 3000 | 4500 | - | - | 9970 | 1820 | 9970 | 12170 | 520 | 2720 | 3320 | 2.4 | 12.4 | 15.2 | 3.67 | A |
| | 3300 | 6000 | 6000 | - | - | 128% | 15300 | 2320 | 4210 | 4210 | - | - | 10740 | 1860 | 10740 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.81 | A |
| | 4000 | 4000 | 4000 | - | - | 100% | 12000 | 3280 | 3280 | 3280 | - | - | 9840 | 1680 | 9840 | 12170 | 510 | 2710 | 3310 | 2.3 | 12.4 | 15.1 | 3.63 | A |
| | 4000 | 4000 | 6000 | - | - | 117% | 14000 | 2870 | 2870 | 4300 | - | - | 10040 | 1820 | 10040 | 12320 | 520 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.62 | A |
| | 4000 | 6000 | 6000 | - | - | 133% | 16000 | 2700 | 4050 | 4050 | - | - | 10800 | 2160 | 10800 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 6000 | 6000 | 6000 | - | - | 150% | 18000 | 3660 | 3670 | 3670 | - | - | 11000 | 2200 | 11000 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.75 | A |
| 4 Unit | 3300 | 3300 | 3300 | 3300 | - | 110% | 13200 | 2490 | 2490 | 2490 | 2490 | - | 9960 | 1820 | 9960 | 12480 | 520 | 2810 | 3410 | 2.4 | 12.9 | 15.6 | 3.54 | B |
| | 3300 | 3300 | 3300 | 4000 | - | 116% | 13900 | 2380 | 2380 | 2380 | 2880 | - | 10020 | 1860 | 10020 | 12320 | 530 | 2770 | 3370 | 2.4 | 12.7 | 15.4 | 3.62 | A |
| | 3300 | 3300 | 3300 | 6000 | - | 133% | 15900 | 2240 | 2240 | 2240 | 4080 | - | 10800 | 2160 | 10800 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 3300 | 3300 | 4000 | 4000 | - | 122% | 14600 | 2410 | 2410 | 2920 | 2920 | - | 10660 | 1860 | 10660 | 12480 | 530 | 2820 | 3420 | 2.4 | 12.9 | 15.7 | 3.78 | A |
| | 3300 | 3300 | 4000 | 6000 | - | 138% | 16600 | 2160 | 2160 | 2620 | 3930 | - | 10870 | 2200 | 10870 | 12960 | 550 | 2920 | 3560 | 2.5 | 13.4 | 16.3 | 3.72 | A |
| | 3300 | 3300 | 6000 | 6000 | - | 155% | 18600 | 1950 | 1950 | 3550 | 3550 | - | 11000 | 2240 | 11000 | 13110 | 560 | 2980 | 3620 | 2.6 | 13.6 | 16.6 | 3.69 | A |
| | 3300 | 4000 | 4000 | 4000 | - | 128% | 15300 | 2320 | 2810 | 2810 | 2810 | - | 10750 | 1890 | 10750 | 12480 | 540 | 2830 | 3430 | 2.5 | 13.0 | 15.7 | 3.80 | A |
| | 3300 | 4000 | 4000 | 6000 | - | 144% | 17300 | 2100 | 2540 | 2540 | 3820 | - | 11000 | 2200 | 11000 | 12960 | 550 | 2930 | 3570 | 2.5 | 13.4 | 16.3 | 3.75 | A |
| | 3300 | 4000 | 6000 | 6000 | - | 161% | 19300 | 1880 | 2280 | 3420 | 3420 | - | 11000 | 2280 | 11000 | 13110 | 570 | 2990 | 3620 | 2.6 | 13.7 | 16.6 | 3.68 | A |
| | 4000 | 4000 | 4000 | 4000 | - | 133% | 16000 | 2700 | 2700 | 2700 | 2700 | - | 10800 | 2160 | 10800 | 12800 | 540 | 2870 | 3510 | 2.5 | 13.1 | 16.1 | 3.76 | A |
| | 4000 | 4000 | 4000 | 6000 | - | 150% | 18000 | 2440 | 2440 | 2440 | 3680 | - | 11000 | 2240 | 11000 | 12960 | 560 | 2930 | 3570 | 2.6 | 13.4 | 16.3 | 3.75 | A |
| | 4000 | 4000 | 6000 | 6000 | - | 167% | 20000 | 2200 | 2200 | 3300 | 3300 | - | 11000 | 2280 | 11000 | 13430 | 570 | 3040 | 3710 | 2.6 | 13.9 | 17.0 | 3.62 | A |
| 5 Unit | 3300 | 3300 | 3300 | 3300 | 3300 | 138% | 16500 | 2400 | 2400 | 2400 | 2400 | 2400 | 12000 | 3400 | 12000 | 14000 | 550 | 2930 | 3900 | 2.5 | 13.4 | 17.8 | 4.10 | A |
| | 3300 | 3300 | 3300 | 3300 | 4000 | 143% | 17200 | 2300 | 2300 | 2300 | 2300 | 2800 | 12000 | 2240 | 12000 | 13900 | 560 | 3150 | 3820 | 2.6 | 14.4 | 17.5 | 3.81 | A |
| | 3300 | 3300 | 3300 | 3300 | 6000 | 160% | 19200 | 2060 | 2060 | 2060 | 2060 | 3760 | 12000 | 2280 | 12000 | 14000 | 570 | 3260 | 3920 | 2.6 | 14.9 | 17.9 | 3.68 | A |
| | 3300 | 3300 | 3300 | 4000 | 4000 | 149% | 17900 | 2220 | 2220 | 2220 | 2670 | 2670 | 12000 | 2240 | 12000 | 14000 | 560 | 3200 | 3910 | 2.6 | 14.6 | 17.9 | 3.75 | A |
| | 3300 | 3300 | 3300 | 4000 | 6000 | 166% | 19900 | 1990 | 1990 | 1990 | 2410 | 3620 | 12000 | 2320 | 12000 | 14000 | 580 | 3310 | 3920 | 2.7 | 15.1 | 17.9 | 3.63 | A |
| | 3300 | 3300 | 4000 | 4000 | 4000 | 155% | 18600 | 2130 | 2130 | 2580 | 2580 | 2580 | 12000 | 2280 | 12000 | 14000 | 570 | 3250 | 3910 | 2.6 | 14.9 | 17.9 | 3.69 | A |
| | 3300 | 3300 | 4000 | 4000 | 6000 | 172% | 20600 | 1920 | 1920 | 2330 | 2330 | 3500 | 12000 | 3400 | 12000 | 14000 | 580 | 3360 | 3930 | 2.7 | 15.4 | 18.0 | 3.57 | B |
| | 3300 | 4000 | 4000 | 4000 | 4000 | 161% | 19300 | 2040 | 2490 | 2490 | 2490 | 2490 | 12000 | 2280 | 12000 | 14000 | 570 | 3260 | 3920 | 2.6 | 14.9 | 17.9 | 3.68 | A |

1. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
2. The above is the value for connecting with the following indoor units.
   - 3200, 4000, 6000W class: Wall Mounted Jungfrau Y Series [only for AQV**YWAN]
3. Capacities are based on the following conditions:
   - Corresponding refrigerant piping length : 5m / - Level difference : 0m
4. The total ability of connected a indoor unit is up to 20.6 kW (@ Heating)
5. It is impossible to connect the indoor unit for one room only.
6. Power consumption include indoor unit power.