

## Dehumidifier LEF 30

Art.-No.: 23.690.35

Bar code: 4006825561982

Sales unit: 1 pc

With the dehumidifier LEF 30 you could avoid humidity, for example at living-, store- and cellar rooms, and so you would not have wet walls, smelly odours, mould formation and condensation water.

In the machine is a ventilator installed which channels the humid air through an evaporator which cools down the air. Spare humidity gets collected as condensate in a condensate tank and the dehumidified air would be blowed out with muted raised temperature.

## **Features:**

- Handle (1)
- To the rear tiltable air discharge opening (2)
- Display ,,condenser full" (3)
- Operating mode display (4)
- Display "defrost" (defrosting the carburetor) (5)
- 2 grades speed switch for ventilator (6)
- Rollers (7)
- Condensate box with gauge-glass and float for overflow safety (8)
- Air inlet with washable dust filter (9)
- On/ off switch with humidity-adjustment (40 % 80 % RH, continuous duty) (10)

By a continuous operation it's possible to use a hose connection for constant conduction of the

## Technical data:

Operation clamping:  $220 - 240 \text{ V} \sim 50 \text{ Hz}$ Power input max.: 560 WTemperature area:  $+8^{\circ} \text{ C} - +32^{\circ} \text{ C}$ 

Dehumidification capacity: 48 C - +32 C at 30°C and 80 %

humidity 30 1 / day at 27°C and 60 % humidity 15 1 / day

Volume of condensate box approx.: 7.01

Refrigerant: R134a / 230 g

- Tool dimensions approx.: 645 x 342 x 320 mm - Net weight: 17.3 kg

Net weight: 17.3 kg
Gross weight: 18.7 kg

Packing dimensions: 400 x 375 x 690 mm

