

SINGLE

Technical Data Book

360 Cassette for EU (R410A/50Hz/HP)



Model (IDU) AC***KN4DKH/EU
(ODU) AC***KX4D*H/EU

History

Version	Modification	Date	Remark
Ver 1.0	Release 360 Cassette TDB	15.12.18	

Index

1 Nomenclature

2 Specifications

3 Capacity table

4 Dimensional drawing

5 Electrical wiring diagram

6 Sound pressure level

7 Sound power level

***8 Temperature and air flow
distribution***

9 Cycle diagram

10 Capacity correction

Nomenclature

Model Names

AC

(1)

071

(2)

K

(3)

N

(4)

4

(5)

D

(6)

K

(7)

H

(8)

/**EU**

Buyer

(1) Classification

AC	SINGLE
AM	VRF

(2) Capacity

x 1/10 kW (3 digits)

(3) Version

H	2014
J	2015
K	2016

(4) Product Type

N	Indoor Unit
X	Outdoor Unit

(5) Product Notation

1	1Way Cassette
2	2Way Cassette
N	4Way Cassette S (600 x 600)
4	4Way Cassette S / 360 CST
L	LSP Duct (Slim Duct)
M	MSP Duct
H	HSP Duct
C	Ceiling
T	Neo Forte
E	OAP Duct

(6) Feature

D	DELUXE
F	FLAGSHIP
P	Premium
G(EHS)	Cascade (EEV)

(7) Rating Voltage

C	1Ø, 208~230V, 60Hz
E	1Ø, 220~240V, 50Hz
G	3Ø, 380~415V, 50Hz
K	1Ø, 220~240V, 50/60Hz
N	3Ø, 380~415V, 50/60Hz

(8) Mode

C	Cooling Only(R410A)
H	Heat Pump(R410A)
D	Cooling Only(R22)
E	Heat Pump(R22)

2 Specifications

360 Cassette

Type				360 Cassette		360 Cassette			
Model Name		Indoor Unit		AC071KN4DKH/EU		AC090KN4DKH/EU			
		Outdoor Unit		AC071KX4DKH/EU		AC090KX4DKH/EU			
System	Mode		-		Heat Pump		Heat Pump		
	Capacity	Cooling(Min/Std/Max)		kW	2.20 / 7.10 / 8.00		3.00 / 9.00 / 11.30		
				Btu/h	7,500 / 24,200 / 27,300		10,200 / 30,700 / 38,600		
		Heating(Min/Std/Max)		kW	1.90 / 8.00 / 9.00		2.20 / 10.00 / 13.90		
				Btu/h	6,500 / 27,300 / 30,700		7,500 / 34,100 / 47,400		
	Power	Power Input (Nominal)	Cooling(Min/Std/Max)	kW	0.35 / 2.49 / 3.95		0.60 / 2.82 / 4.46		
			Heating(Min/Std/Max)		0.35 / 2.40 / 3.95		0.46 / 2.65 / 5.20		
		Current Input (Nominal)	Cooling(Min/Std/Max)	A	2.00 / 11.10 / 17.00		3.00 / 12.70 / 19.40		
			Heating(Min/Std/Max)		2.00 / 10.70 / 17.00		2.50 / 12.50 / 22.70		
		MCA		A	21.50 (MCA)		24.50 (MCA)		
		MFA		A	23.65		26.95		
	Energy Efficiency	EER (Nominal Cooling)		-	2.85		3.19		
		COP (Nominal Heating)		-	3.33		3.77		
		Energy Grade		-	SEER 6.2 (A++)		SEER 6.8 (A++)		
				-	SCOP 4.1 (A+)		SCOP 4.3 (A+)		
	Piping Connections	Liquid Pipe		Ø, mm	6.35		9.52		
				Ø, inch	1/4"		3/8"		
				Ø, mm	15.88		15.88		
				Ø, inch	5/8"		5/8"		
		Gas Pipe	Installation Limitation		Max. Length	m		50 (55)	
			Max. Height		m	30 (30)		30 (30)	
	Field Wiring	Power Source Wire		Ø, mm	2.50		2.50		
		Transmission Cable		Ø, mm	0.75 ~ 1.50		0.75 ~ 1.50		
	Refrigerant	Type		-	R410A		R410A		
		Control Method		-	EEV		EEV		
		Factory Charging		kg	1.50		3.00		
Indoor Unit	Power Supply			Ø, #, V, Hz	1,2,220-240,50		1,2,220-240,50		
	Fan	Type		-	Turbo Fan		Turbo Fan		
		Motor	Output	W	65		97		
				CMM	17.50 / 15.90 / 14.30		30.10 / 24.40 / 19.80		
		Air Flow Rate		High/Mid/Low	l/s	291.67 / 265.00 / 238.33		501.67 / 406.67 / 330.00	
					mmAq	-		-	
	External Static Pressure		Min/Std/Max	Pa	-		-		
				Pa	-		-		
	Drain	Drain Pipe		Ø,mm	VP25 (OD 32,ID 25)		VP25 (OD 32,ID 25)		
	Sound	Pressure	High/Mid/Low		dB(A)	36 / 33 / 29		43 / 38 / 33	
		Power	Cooling			53		60	
	External Dimension	Net Weight		kg	21.00		24.00		
		Shipping Weight		kg	25.00		29.00		
		Net Dimensions (WxHxD)		mm	947 x 281 x 947		947 x 365 x 947		
		Shipping Dimensions (WxHxD)		mm	990 x 330 x 990		990 x 414 x 990		
	Panel Size	Panel model		-	PC4NUDMAN		PC4NUDMAN		
		Panel Net Weight		kg	3.60		3.60		
		Shipping Weight		kg	6.00		6.00		
		Net Dimensions (WxHxD)		mm	1,000 x 66 x 1,000		1,000 x 66 x 1,000		
		Shipping Dimensions (WxHxD)		mm	1,093 x 85 x 1,083		1,093 x 85 x 1,083		
	Additional Accessories	Drain pump	Drain pump	-	-		-		
			Max. Lifting	mm/liter/h	-		-		
		Air Filter		-	-		-		
	Outdoor Unit	Power Supply			Ø, #, V, Hz	1,2,220-240,50		1,2,220-240,50	
		Compressor	Type		-	BLDC Rotary		BLDC Rotary	
			Model		-	UG4T200FUA4		UG8T300FUBJU	
Output			kW	1.79		2.82			
Oil			Type	-	POE		PVE		
		Fan		-					
Air Flow Rate		Cooling	CMM	58.50		78.00			
			l/s	975.00		1,300.00			
Sound		Pressure	Cooling/Heating	dB(A)	49 / 51		52 / 53		
					Power	Cooling	65		68
External Dimension		Net Weight		kg	50.50		72.00		
		Shipping Weight		kg	55.00		77.00		
		Net Dimensions (WxHxD)		mm	880 x 798 x 310		940 x 998 x 330		
		Shipping Dimensions (WxHxD)		mm	1,023 x 891 x 413		995 x 1,096 x 426		
Operating Temp. Range		Cooling		°C	-15.0 ~ 50.0		-15.0 ~ 50.0		
		Heating		°C	-20.0 ~ 24.0		-20.0 ~ 24.0		

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) Panel type is option. (Ceiling Type/Open Type)

About each detail spec, please refer to Dimensional Drawing pages.

2 Specifications

360 Cassette

Type				360 Cassette		360 Cassette		
Model Name		Indoor Unit		AC100KN4DKH/EU		AC100KN4DKH/EU		
		Outdoor Unit		AC100KX4DNH/EU		AC100KX4DKH/EU		
System	Mode			Heat Pump		Heat Pump		
	Capacity	Cooling(Min/Std/Max)		kW	3.00 / 10.00 / 12.00	3.00 / 10.00 / 12.00		
				Btu/h	10,200 / 34,100 / 40,900	10,200 / 34,100 / 40,900		
		Heating(Min/Std/Max)		kW	2.20 / 11.20 / 15.50	2.20 / 11.20 / 15.50		
				Btu/h	7,500 / 38,200 / 52,900	7,500 / 38,200 / 52,900		
	Power	Power Input (Nominal)	Cooling(Min/Std/Max)	kW	0.60 / 3.40 / 4.70	0.60 / 3.40 / 4.70		
			Heating(Min/Std/Max)		0.46 / 3.15 / 5.40	0.46 / 3.15 / 5.40		
		Current Input (Nominal)	Cooling(Min/Std/Max)	A	1.50 / 5.30 / 7.10	3.00 / 15.10 / 20.40		
			Heating(Min/Std/Max)		1.20 / 4.90 / 8.40	2.50 / 14.60 / 23.00		
		MCA		A	17.60 (MCA)	24.50 (MCA)		
		MFA		A	17.60	26.95		
	Energy Efficiency	EER (Nominal Cooling)		-	2.94	2.94		
		COP (Nominal Heating)		-	3.56	3.56		
		Energy Grade		-	SEER 6.8 (A++)	SEER 6.8 (A++)		
				-	SCOP 4.3 (A+)	SCOP 4.3 (A+)		
	Piping Connections	Liquid Pipe		Ø, mm	9.52	9.52		
				Ø, inch	3/8"	3/8"		
		Gas Pipe		Ø, mm	15.88	15.88		
				Ø, inch	5/8"	5/8"		
		Installation Limitation	Max. Length	m	50 (55)	50 (55)		
			Max. Height	m	30 (30)	30 (30)		
	Field Wiring	Power Source Wire		Ø, mm	2.50	2.50		
		Transmission Cable		Ø, mm	0.75 ~ 1.50	0.75 ~ 1.50		
	Refrigerant	Type		-	R410A	R410A		
		Control Method		-	EEV	EEV		
		Factory Charging		kg	3.00	3.00		
Indoor Unit	Power Supply			Ø, #, V, Hz	1,2,220-240,50	1,2,220-240,50		
	Fan	Type		-	Turbo Fan	Turbo Fan		
		Motor	Output	W	97	97		
				CMM	31.20 / 25.50 / 19.80	31.20 / 25.50 / 19.80		
		Air Flow Rate	High/Mid/Low	l/s	520.00 / 425.00 / 330.00	520.00 / 425.00 / 330.00		
				External Static Pressure	Min/Std/Max	mmAq	-	-
	Pa	-	-					
	Drain	Drain Pipe		Ø,mm	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)		
	Sound	Pressure	High/Mid/Low	dB(A)	44 / 39 / 33	44 / 39 / 33		
		Power	Cooling		61	61		
	External Dimension	Net Weight		kg	24.00	24.00		
		Shipping Weight		kg	29.00	29.00		
		Net Dimensions (WxHxD)		mm	947 x 365 x 947	947 x 365 x 947		
		Shipping Dimensions (WxHxD)		mm	990 x 414 x 990	990 x 414 x 990		
	Panel Size	Panel model		-	PC4NUDMAN	PC4NUDMAN		
		Panel Net Weight		kg	3.60	3.60		
		Shipping Weight		kg	6.00	6.00		
		Net Dimensions (WxHxD)		mm	1,000 x 66 x 1,000	1,000 x 66 x 1,000		
		Shipping Dimensions (WxHxD)		mm	1,093 x 85 x 1,083	1,093 x 85 x 1,083		
	Additional Accessories	Drain pump	Drain pump	-	-	-		
			Max. Lifting	mm/liter/h	-	-		
	Air Filter			-	-	-		
	Outdoor Unit	Power Supply			Ø, #, V, Hz	3,4,380-415,50	1,2,220-240,50	
		Compressor	Type		-	Twin BLDC Rotary	BLDC Rotary	
			Model		-	UG8T300FUCJU	UG8T300FUBJU	
			Output		kW	2.82	2.82	
Oil			Type	-	PVE	PVE		
		-		PVE	PVE			
Fan		Air Flow Rate	Cooling	CMM	78.00	78.00		
				l/s	1,300.00	1,300.00		
Sound		Pressure	Cooling/Heating	dB(A)	52 / 54	52 / 54		
					69	69		
External Dimension		Net Weight		kg	72.00	72.00		
		Shipping Weight		kg	77.00	77.00		
		Net Dimensions (WxHxD)		mm	940 x 998 x 330	940 x 998 x 330		
		Shipping Dimensions (WxHxD)		mm	995 x 1,096 x 426	995 x 1,096 x 426		
Operating Temp. Range		Cooling		°C	-15.0 ~ 50.0	-15.0 ~ 50.0		
		Heating		°C	-20.0 ~ 24.0	-20.0 ~ 24.0		

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) Panel type is option. (Ceiling Type/Open Type)

About each detail spec, please refer to Dimensional Drawing pages.

2 Specifications

360 Cassette

Type				360 Cassette		360 Cassette			
Model Name		Indoor Unit		AC120KN4DKH/EU		AC120KN4DKH/EU			
		Outdoor Unit		AC120KX4DNH/EU		AC120KX4DKH/EU			
System	Mode			-	Heat Pump		Heat Pump		
	Capacity	Cooling(Min/Std/Max)		kW	3.50 / 12.00 / 13.50		3.50 / 12.00 / 13.50		
				Btu/h	11,900 / 40,900 / 46,100		11,900 / 40,900 / 46,100		
		Heating(Min/Std/Max)		kW	3.50 / 13.00 / 15.50		3.50 / 13.00 / 15.50		
				Btu/h	11,900 / 44,400 / 52,900		11,900 / 44,400 / 52,900		
	Power	Power Input (Nominal)	Cooling(Min/Std/Max)	kW	0.90 / 4.70 / 7.90		0.90 / 4.70 / 5.30		
			Heating(Min/Std/Max)		0.75 / 4.00 / 7.90		0.75 / 4.00 / 5.50		
		Current Input (Nominal)	Cooling(Min/Std/Max)	A	2.10 / 7.10 / 12.00		4.30 / 20.50 / 23.00		
			Heating(Min/Std/Max)		2.10 / 6.10 / 12.00		3.70 / 17.70 / 24.00		
		MCA		A	17.60 (MCA)		26.50 (MCA)		
		MFA		A	17.60		29.15		
	Energy Efficiency	EER (Nominal Cooling)		-	2.55		2.55		
		COP (Nominal Heating)		-	3.25		3.25		
		Energy Grade		-	SEER 5.7 (A+)		SEER 5.7 (A+)		
				-	SCOP 4.1 (A+)		SCOP 4.1 (A+)		
	Piping Connections	Liquid Pipe		Ø, mm	9.52		9.52		
				Ø, inch	3/8"		3/8"		
		Gas Pipe		Ø, mm	15.88		15.88		
				Ø, inch	5/8"		5/8"		
		Installation Limitation	Max. Length	m	50 (55)		50 (55)		
			Max. Height	m	30 (30)		30 (30)		
	Field Wiring	Power Source Wire		Ø, mm	2.50		2.50		
		Transmission Cable		Ø, mm	0.75 ~ 1.50		0.75 ~ 1.50		
	Refrigerant	Type		-	R410A		R410A		
		Control Method		-	EEV		EEV		
		Factory Charging		kg	3.00		3.00		
Indoor Unit	Power Supply			Ø, #, V, Hz	1,2,220-240,50		1,2,220-240,50		
	Fan	Type		-	Turbo Fan		Turbo Fan		
		Motor	Output	W	97		97		
				CMM	32.50 / 25.50 / 19.80		32.50 / 25.50 / 19.80		
		Air Flow Rate		High/Mid/Low	l/s	541.67 / 425.00 / 330.00		541.67 / 425.00 / 330.00	
					mmAq	-		-	
	External Static Pressure		Min/Std/Max	Pa	-		-		
				Pa	-		-		
	Drain	Drain Pipe		Ø,mm	VP25 (OD 32,ID 25)		VP25 (OD 32,ID 25)		
	Sound	Pressure	High/Mid/Low	dB(A)	45 / 40 / 35		45 / 40 / 35		
		Power	Cooling		61		61		
	External Dimension	Net Weight		kg	24.00		24.00		
		Shipping Weight		kg	29.00		29.00		
		Net Dimensions (WxHxD)		mm	947 x 365 x 947		947 x 365 x 947		
		Shipping Dimensions (WxHxD)		mm	990 x 414 x 990		990 x 414 x 990		
	Panel Size	Panel model		-	PC4NUDMAN		PC4NUDMAN		
		Panel Net Weight		kg	3.60		3.60		
		Shipping Weight		kg	6.00		6.00		
		Net Dimensions (WxHxD)		mm	1,000 x 66 x 1,000		1,000 x 66 x 1,000		
		Shipping Dimensions (WxHxD)		mm	1,093 x 85 x 1,083		1,093 x 85 x 1,083		
	Additional Accessories	Drain pump	Drain pump	-	-		-		
			Max. Lifting	mm/liter/h	-		-		
		Air Filter		-	-		-		
	Outdoor Unit	Power Supply			Ø, #, V, Hz	3,4,380-415,50		1,2,220-240,50	
		Compressor	Type		-	Twin BLDC Rotary		Twin BLDC Rotary	
			Model		-	UG5T450FUFJX		UG5T450FUEJX	
Output			kW	4.12		4.12			
Oil			Type	-	PVE		PVE		
Fan		Air Flow Rate	Cooling	CMM	78.00		78.00		
				l/s	1,300.00		1,300.00		
Sound		Pressure	Cooling/Heating	dB(A)	54 / 56		54 / 56		
		Power	Cooling		70		70		
External Dimension		Net Weight		kg	80.00		80.00		
		Shipping Weight		kg	85.00		85.00		
		Net Dimensions (WxHxD)		mm	940 x 998 x 330		940 x 998 x 330		
		Shipping Dimensions (WxHxD)		mm	995 x 1,096 x 426		995 x 1,096 x 426		
Operating Temp. Range		Cooling		°C	-15.0 ~ 50.0		-15.0 ~ 50.0		
		Heating		°C	-20.0 ~ 24.0		-20.0 ~ 24.0		

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) Panel type is option. (Ceiling Type/Open Type)

About each detail spec, please refer to Dimensional Drawing pages.

2 Specifications

360 Cassette

Type				360 Cassette		360 Cassette		
Model Name		Indoor Unit		AC140KN4DKH/EU		AC140KN4DKH/EU		
		Outdoor Unit		AC140KX4DNH/EU		AC140KX4DKH/EU		
System	Mode			Heat Pump		Heat Pump		
	Capacity	Cooling(Min/Std/Max)		kW	3.50 / 13.40 / 15.50	3.49 / 13.40 / 15.50		
				Btu/h	11,900 / 45,700 / 52,900	11,900 / 45,700 / 52,900		
		Heating(Min/Std/Max)		kW	3.50 / 15.50 / 18.00	3.50 / 15.50 / 18.00		
				Btu/h	11,900 / 52,900 / 61,400	11,900 / 52,900 / 61,400		
	Power	Power Input (Nominal)	Cooling(Min/Std/Max)	kW	0.80 / 4.18 / 7.90	0.80 / 4.18 / 6.44		
			Heating(Min/Std/Max)		0.70 / 4.30 / 7.90	0.70 / 4.30 / 7.36		
		Current Input (Nominal)	Cooling(Min/Std/Max)	A	2.10 / 6.60 / 12.00	3.70 / 18.20 / 28.00		
			Heating(Min/Std/Max)		1.90 / 6.80 / 12.00	3.50 / 18.70 / 32.00		
		MCA		A	17.60 (MCA)	33.50 (MCA)		
		MFA		A	17.60	36.85		
	Energy Efficiency	EER (Nominal Cooling)		-	3.21	3.21		
		COP (Nominal Heating)		-	3.60	3.60		
		Energy Grade		-	-	-		
				-	-	-		
	Piping Connections	Liquid Pipe		Ø, mm	9.52	9.52		
				Ø, inch	3/8"	3/8"		
		Gas Pipe		Ø, mm	15.88	15.88		
				Ø, inch	5/8"	5/8"		
		Installation Limitation	Max. Length	m	75 (75)	75 (75)		
			Max. Height	m	30 (30)	30 (30)		
	Field Wiring	Power Source Wire		Ø, mm	2.50	2.50		
		Transmission Cable		Ø, mm	0.75 ~ 1.50	0.75 ~ 1.50		
	Refrigerant	Type		-	R410A	R410A		
		Control Method		-	EEV	EEV		
Factory Charging		kg	3.50	3.50				
Indoor Unit	Power Supply			Ø, #, V, Hz	1,2,220-240,50	1,2,220-240,50		
	Fan	Type		-	Turbo Fan	Turbo Fan		
		Motor	Output	W	1	1		
				CMM	32.40 / 27.10 / 22.80	32.40 / 27.10 / 22.80		
		Air Flow Rate	High/Mid/Low	l/s	540.00 / 451.67 / 380.00	540.00 / 451.67 / 380.00		
		External Static Pressure		Min/Std/Max	mmAq	-	-	
	Pa				-	-		
	Drain	Drain Pipe		Ø,mm	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)		
	Sound	Pressure	High/Mid/Low	dB(A)	45 / 41 / 37	45 / 41 / 37		
		Power	Cooling		61	61		
	External Dimension	Net Weight		kg	25.50	25.50		
		Shipping Weight		kg	30.00	30.00		
		Net Dimensions (WxHxD)		mm	947 x 365 x 947	947 x 365 x 947		
		Shipping Dimensions (WxHxD)		mm	990 x 414 x 990	990 x 414 x 990		
	Panel Size	Panel model		-	PC4NUDMAN	PC4NUDMAN		
		Panel Net Weight		kg	3.60	3.60		
		Shipping Weight		kg	6.00	6.00		
		Net Dimensions (WxHxD)		mm	1,000 x 66 x 1,000	1,000 x 66 x 1,000		
		Shipping Dimensions (WxHxD)		mm	1,093 x 85 x 1,083	1,093 x 85 x 1,083		
	Additional Accessories	Drain pump	Drain pump	-	-	-		
		Max. Lifting		mm/liter/h	-	-		
	Air Filter			-	-	-		
	Outdoor Unit	Power Supply			Ø, #, V, Hz	3,4,380-415,50	1,2,220-240,50	
		Compressor	Type		-	Twin BLDC Rotary	Twin BLDC Rotary	
Model			-	UG5T450FUFJX	UG5T450FUEJX			
Output			kW	4.12	4.12			
Oil			Type	-	PVE	PVE		
Fan		Air Flow Rate	Cooling	CMM	111.00	111.00		
				l/s	1,850.00	1,850.00		
Sound		Pressure	Cooling/Heating	dB(A)	53 / 54	53 / 54		
		Power	Cooling		69	69		
External Dimension		Net Weight		kg	92.50	92.50		
		Shipping Weight		kg	102.50	102.50		
		Net Dimensions (WxHxD)		mm	940 x 1,210 x 330	940 x 1,210 x 330		
		Shipping Dimensions (WxHxD)		mm	995 x 1,338 x 426	995 x 1,338 x 426		
Operating Temp. Range		Cooling		°C	-15.0 ~ 50.0	-15.0 ~ 50.0		
		Heating		°C	-20.0 ~ 24.0	-20.0 ~ 24.0		

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) Panel type is option. (Ceiling Type/Open Type)

About each detail spec, please refer to Dimensional Drawing pages.

3 Capacity table

360 Cassette

AC071KN4DKH/EU + AC071KX4DKH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	8.10	5.70	1.50	8.30	5.80	1.54	8.50	6.00	1.58	8.70	6.10	1.62	8.80	6.20	1.63	8.90	6.30	1.66	9.10	6.40	1.70
21.0	7.80	5.60	1.82	8.00	5.70	1.87	8.20	5.90	1.92	8.40	6.00	1.96	8.40	6.00	1.98	8.60	6.10	2.01	8.80	6.30	2.06
35.0	6.60	4.90	2.31	6.80	5.00	2.37	6.90	5.10	2.43	7.10	5.20	2.49	7.20	5.30	2.51	7.30	5.30	2.55	7.40	5.50	2.61
46.0	5.10	4.20	2.69	5.20	4.30	2.75	5.30	4.40	2.82	5.40	4.50	2.89	5.50	4.50	2.91	5.60	4.60	2.96	5.70	4.70	3.03
50.0	4.50	3.90	2.82	4.60	4.00	2.89	4.70	4.10	2.96	4.80	4.20	3.04	4.90	4.20	3.06	4.90	4.30	3.11	5.10	4.40	3.19

Heating

TC : Total Capacity, PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	5.70	2.73	5.70	2.71	5.60	2.68	5.50	2.65	5.50	2.63	5.40	2.60
-10.0	7.90	3.61	7.80	3.58	7.80	3.54	7.70	3.50	7.60	3.47	7.50	3.43
-5.0	8.00	3.27	7.90	3.24	7.80	3.20	7.70	3.17	7.70	3.14	7.60	3.11
0.0	8.10	2.93	8.00	2.90	7.90	2.90	7.80	2.84	7.70	2.81	7.70	2.78
7.0	8.20	2.45	8.10	2.42	8.00	2.40	7.90	2.38	7.80	2.35	7.80	2.33
24.0	11.20	3.40	11.10	3.37	11.00	3.33	10.90	3.30	10.80	3.27	10.70	3.23

AC090KN4DKH/EU + AC090KX4DKH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	9.40	7.20	2.67	9.60	7.30	2.73	9.80	7.50	2.80	10.10	7.70	2.87	10.20	7.80	2.89	10.30	7.90	2.94	10.60	8.10	3.01
21.0	10.30	7.60	2.56	10.50	7.80	2.63	10.80	8.00	2.69	11.10	8.20	2.76	11.20	8.30	2.78	11.30	8.40	2.82	11.60	8.60	2.89
35.0	8.40	6.80	2.62	8.60	7.00	2.69	8.80	7.20	2.75	9.00	7.40	2.82	9.10	7.40	2.84	9.20	7.50	2.89	9.40	7.70	2.96
46.0	7.10	6.20	3.12	7.30	6.30	3.20	7.50	6.50	3.28	7.70	6.60	3.36	7.70	6.70	3.38	7.80	6.80	3.44	8.00	6.90	3.52
50.0	6.00	5.60	2.91	6.20	5.70	2.98	6.30	5.90	3.06	6.50	6.00	3.13	6.50	6.10	3.16	6.60	6.20	3.21	6.80	6.30	3.28

Heating

TC : Total Capacity PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	7.00	3.09	7.00	3.06	6.90	3.03	6.80	3.00	6.80	2.97	6.70	2.94
-10.0	10.40	4.33	10.30	4.28	10.20	4.24	10.10	4.20	10.00	4.16	9.90	4.11
-5.0	10.30	3.85	10.20	3.81	10.10	3.77	10.00	3.73	9.90	3.70	9.80	3.66
0.0	10.30	3.37	10.20	3.34	10.10	3.30	10.00	3.27	9.90	3.24	9.80	3.21
7.0	10.20	2.70	10.10	2.68	10.00	2.65	9.90	2.62	9.80	2.60	9.70	2.57
24.0	14.20	3.51	14.00	3.48	13.90	3.45	13.80	3.41	13.60	3.38	13.50	3.34

3 Capacity table

360 Cassette

AC100KN4DKH/EU + AC100KX4DNH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	10.40	8.00	3.22	10.70	8.20	3.30	10.90	8.40	3.38	11.20	8.60	3.46	11.30	8.60	3.49	11.50	8.80	3.54	11.70	9.00	3.63
21.0	11.40	8.50	3.09	11.70	8.70	3.17	12.00	8.90	3.25	12.30	9.10	3.33	12.40	9.20	3.35	12.60	9.40	3.41	12.90	9.60	3.49
35.0	9.30	7.40	3.16	9.50	7.60	3.24	9.80	7.80	3.32	10.00	8.00	3.40	10.10	8.10	3.43	10.20	8.20	3.48	10.50	8.40	3.57
46.0	7.90	6.80	3.76	8.10	7.00	3.85	8.30	7.20	3.95	8.50	7.40	4.05	8.60	7.40	4.08	8.70	7.50	4.14	8.90	7.70	4.24
50.0	6.70	6.20	3.51	6.90	6.40	3.60	7.00	6.50	3.68	7.20	6.70	3.77	7.30	6.70	3.80	7.40	6.80	3.86	7.50	7.00	3.96

Heating

TC : Total Capacity, PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	7.80	3.67	7.80	3.64	7.70	3.60	7.60	3.56	7.50	3.53	7.50	3.49
-10.0	11.60	5.23	11.50	5.18	11.40	5.13	11.30	5.08	11.20	5.03	11.10	4.98
-5.0	11.60	4.64	11.50	4.59	11.30	4.55	11.20	4.50	11.10	4.46	11.00	4.41
0.0	11.50	4.04	11.40	4.00	11.30	4.00	11.20	3.92	11.10	3.89	11.00	3.85
7.0	11.40	3.21	11.30	3.18	11.20	3.15	11.10	3.12	11.00	3.09	10.90	3.06
24.0	15.90	4.23	15.80	4.19	15.60	4.15	15.50	4.11	15.30	4.07	15.20	4.03

AC100KN4DKH/EU + AC100KX4DKH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	10.40	8.00	3.22	10.70	8.20	3.30	10.90	8.40	3.38	11.20	8.60	3.46	11.30	8.60	3.49	11.50	8.80	3.54	11.70	9.00	3.63
21.0	11.40	8.50	3.09	11.70	8.70	3.17	12.00	8.90	3.25	12.30	9.10	3.33	12.40	9.20	3.35	12.60	9.40	3.41	12.90	9.60	3.49
35.0	9.30	7.50	3.16	9.50	7.60	3.24	9.80	7.80	3.32	10.00	8.00	3.40	10.10	8.10	3.43	10.20	8.20	3.48	10.50	8.40	3.57
46.0	7.90	6.80	3.76	8.10	7.00	3.85	8.30	7.20	3.95	8.50	7.40	4.05	8.60	7.40	4.08	8.70	7.50	4.14	8.90	7.70	4.24
50.0	6.70	6.20	3.51	6.90	6.40	3.60	7.00	6.50	3.68	7.20	6.70	3.77	7.30	6.70	3.80	7.40	6.80	3.86	7.50	7.00	3.96

Heating

TC : Total Capacity PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	7.90	3.67	7.80	3.64	7.70	3.60	7.60	3.56	7.50	3.53	7.50	3.49
-10.0	11.60	5.23	11.50	5.18	11.40	5.13	11.30	5.08	11.20	5.03	11.10	4.98
-5.0	11.60	4.64	11.50	4.59	11.30	4.55	11.20	4.50	11.10	4.46	11.00	4.41
0.0	11.50	4.04	11.40	4.00	11.30	4.00	11.20	3.93	11.10	3.89	10.90	3.85
7.0	11.40	3.21	11.30	3.18	11.20	3.15	11.10	3.12	11.00	3.09	10.90	3.06
24.0	15.90	4.23	15.80	4.19	15.60	4.15	15.40	4.11	15.30	4.07	15.10	4.03

3 Capacity table

360 Cassette

AC120KN4DKH/EU + AC120KX4DNH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	15.60	10.20	3.53	16.00	10.40	3.62	16.40	10.70	3.71	16.80	10.90	3.80	16.90	11.00	3.83	17.20	11.20	3.89	17.60	11.50	3.98
21.0	12.50	9.10	3.60	12.80	9.30	3.69	13.10	9.50	3.78	13.40	9.70	3.87	13.50	9.80	3.90	13.70	10.00	3.97	14.10	10.20	4.06
35.0	11.20	8.50	4.37	11.40	8.70	4.48	11.70	8.90	4.59	12.00	9.10	4.70	12.10	9.20	4.74	12.30	9.30	4.81	12.60	9.60	4.93
46.0	9.50	8.30	4.50	9.70	8.50	4.61	10.00	8.80	4.72	10.20	9.00	4.84	10.30	9.00	4.88	10.40	9.20	4.96	10.70	9.40	5.08
50.0	6.90	6.60	3.71	7.10	6.70	3.81	7.30	6.90	3.90	7.40	7.10	4.00	7.50	7.10	4.03	7.60	7.20	4.09	7.80	7.40	4.19

Heating

TC : Total Capacity, PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	9.60	4.74	9.50	4.70	9.40	4.65	9.30	4.60	9.20	4.56	9.10	4.51
-10.0	13.00	6.01	12.80	5.95	12.70	5.89	12.60	5.83	12.40	5.78	12.30	5.72
-5.0	13.00	5.44	12.90	5.39	12.80	5.34	12.70	5.28	12.50	5.23	12.40	5.18
0.0	13.10	4.88	13.00	4.83	12.90	4.80	12.70	4.73	12.60	4.68	12.50	4.64
7.0	13.30	4.08	13.10	4.04	13.00	4.00	12.90	3.96	12.70	3.92	12.60	3.88
24.0	16.80	4.49	16.70	4.44	16.50	4.40	16.30	4.36	16.20	4.31	16.00	4.27

AC120KN4DKH/EU + AC120KX4DKH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	15.60	10.20	3.53	16.00	10.40	3.62	16.40	10.70	3.71	16.80	10.90	3.80	16.90	11.00	3.83	17.20	11.20	3.89	17.60	11.50	3.98
21.0	12.50	9.10	3.60	12.80	9.30	3.69	13.10	9.50	3.78	13.40	9.70	3.87	13.50	9.80	3.90	13.70	10.00	3.97	14.10	10.20	4.06
35.0	11.20	8.50	4.37	11.40	8.70	4.48	11.70	8.90	4.59	12.00	9.10	4.70	12.10	9.20	4.74	12.30	9.30	4.81	12.60	9.60	4.93
46.0	9.50	8.30	4.50	9.70	8.50	4.61	10.00	8.80	4.72	10.20	9.00	4.84	10.30	9.00	4.88	10.40	9.20	4.96	10.70	9.40	5.08
50.0	6.90	6.60	3.71	7.10	6.70	3.81	7.30	6.90	3.90	7.40	7.10	4.00	7.50	7.10	4.03	7.60	7.20	4.09	7.80	7.40	4.19

Heating

TC : Total Capacity PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	9.60	4.74	9.50	4.70	9.40	4.65	9.30	4.60	9.20	4.56	9.10	4.51
-10.0	13.00	6.01	12.80	5.95	12.70	5.89	12.60	5.84	12.40	5.78	12.30	5.72
-5.0	13.00	5.44	12.90	5.39	12.80	5.34	12.70	5.28	12.50	5.23	12.40	5.18
0.0	13.10	4.88	13.00	4.83	12.90	4.80	12.70	4.73	12.60	4.69	12.50	4.64
7.0	13.30	4.08	13.10	4.04	13.00	4.00	12.90	3.96	12.70	3.92	12.60	3.88
24.0	16.80	4.49	16.70	4.44	16.50	4.40	16.40	4.36	16.20	4.31	16.00	4.27

3 Capacity table

360 Cassette

AC140KN4DKH/EU + AC140KX4DNH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	16.20	10.90	4.35	16.60	11.20	4.46	17.00	11.50	4.57	17.40	11.80	4.68	17.60	11.90	4.72	17.80	12.00	4.79	18.30	12.30	4.91
21.0	14.10	9.70	4.08	14.40	10.00	4.18	14.80	10.20	4.28	15.10	10.50	4.39	15.30	10.60	4.42	15.50	10.70	4.49	15.90	11.00	4.60
35.0	12.50	9.00	3.89	12.80	9.20	3.98	13.10	9.40	4.08	13.40	9.70	4.18	13.50	9.70	4.21	13.70	9.90	4.28	14.10	10.10	4.38
46.0	9.70	7.30	4.47	10.00	7.50	4.58	10.20	7.70	4.69	10.50	7.90	4.81	10.50	7.90	4.85	10.70	8.00	4.92	11.00	8.20	5.04
50.0	7.10	6.50	3.69	7.30	6.60	3.78	7.50	6.80	3.88	7.60	7.00	3.97	7.70	7.00	4.00	7.80	7.10	4.07	8.00	7.30	4.16

Heating

TC : Total Capacity, PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	10.40	4.89	10.30	4.84	10.20	4.79	10.10	4.74	10.00	4.69	9.90	4.65
-10.0	15.80	7.25	15.70	7.18	15.50	7.11	15.30	7.04	15.20	6.97	15.00	6.90
-5.0	15.80	6.41	15.70	6.35	15.50	6.28	15.30	6.22	15.20	6.16	15.00	6.10
0.0	15.80	5.57	15.70	5.51	15.50	5.50	15.30	5.40	15.20	5.35	15.00	5.29
7.0	15.80	4.39	15.70	4.34	15.50	4.30	15.30	4.26	15.20	4.21	15.00	4.17
24.0	20.90	5.40	20.70	5.34	20.50	5.29	20.30	5.24	20.10	5.18	19.90	5.13

AC140KN4DKH/EU + AC140KX4DKH/EU

Cooling

TC(Total Capacity), SHC(Sensible Heat Capacity), PI(Power Input)

Outdoor Air Temp. (DB)	Indoor temperature (°C)																				
	20 (DB)			23 (DB)			26 (DB)			27 (DB)			28 (DB)			30 (DB)			32 (DB)		
	14 (WB)			16 (WB)			18 (WB)			19 (WB)			20 (WB)			22 (WB)			24 (WB)		
	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)	TC(kW)	SHC(kW)	PI(kW)
-15.0	16.20	10.90	4.35	16.60	11.20	4.46	17.00	11.50	4.57	17.40	11.80	4.68	17.60	11.90	4.72	17.80	12.00	4.79	18.30	12.30	4.91
21.0	14.10	9.70	4.08	14.40	10.00	4.18	14.80	10.20	4.28	15.10	10.50	4.39	15.30	10.60	4.42	15.50	10.70	4.49	15.90	11.00	4.60
35.0	12.50	9.00	3.89	12.80	9.20	3.98	13.10	9.40	4.08	13.40	9.70	4.18	13.50	9.70	4.21	13.70	9.90	4.28	14.10	10.10	4.38
46.0	9.70	7.30	4.47	10.00	7.50	4.58	10.20	7.70	4.69	10.50	7.90	4.81	10.50	7.90	4.85	10.70	8.00	4.92	11.00	8.20	5.04
50.0	7.10	6.50	3.69	7.30	6.60	3.78	7.50	6.80	3.88	7.60	7.00	3.97	7.70	7.00	4.00	7.80	7.10	4.07	8.00	7.30	4.16

Heating


TC : Total Capacity PI: Power Input

Outdoor Air Temp. (DB)	Indoor temperature (°C)											
	16.0 (DB)		18.0 (DB)		20.0 (DB)		21.0 (DB)		22.0 (DB)		24.0 (DB)	
	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
-20.0	10.40	4.89	10.30	4.84	10.20	4.79	10.10	4.75	10.00	4.70	9.90	4.65
-10.0	15.80	7.25	15.60	7.18	15.50	7.11	15.30	7.04	15.20	6.97	15.00	6.90
-5.0	15.80	6.41	15.60	6.34	15.50	6.28	15.30	6.22	15.20	6.16	15.00	6.10
0.0	15.80	5.57	15.60	5.51	15.50	5.50	15.30	5.40	15.20	5.35	15.00	5.29
7.0	15.80	4.39	15.70	4.34	15.50	4.30	15.30	4.26	15.20	4.21	15.00	4.17
24.0	20.90	5.39	20.70	5.34	20.50	5.29	20.30	5.23	20.10	5.18	19.90	5.13

4 Dimensional drawing

Indoor : 360 Cassette

AC071KN4DKH/EU



Note

1. Make sure the spacing between the ceiling and the cassette is no more than 10mm[3/8"].
2. When the conditions exceed 30°C[86°F] and RH 80% in the ceiling or fresh air is induced into the ceiling, and additional insulation is required (polyethylene foam, thickness 10mm[3/8"] or more)
3. Ceiling type panel model code : PC4NUDMAN

Table of descriptions

1	Refrigerant gas pipe	7	Suction rim for Booster fan
2	Refrigerant liquid pipe	8	Decoration cover
3	Condensate drain	9	Drain hose
4	Power & Comm. wiring conduits	10	Fresh air intake knock out hole
5	Air discharge opening	11	Display window
6	Air suction grille	12	Infrared receiver

AC090KN4DKH/EU. AC100KN4DKH/EU. AC120KN4DKH/EU. AC140KN4DKH/EU





Table of descriptions			
1	Refrigerant gas pipe	7	Suction rim for Booster fan
2	Refrigerant liquid pipe	8	Corner decoration cover
3	Condensate drain	9	Drain hose
4	Power & Comm. wiring conduits	10	Fresh air intake knock out hole
5	Air discharge opening	11	Display window
6	Air suction grille	12	Infrared receiver

4 Dimensional drawing

Indoor : 360 Cassette

AC071KN4DKH/EU



Note

1. Make sure the spacing between the ceiling and the cassette is no more than 10mm[3/8"].
2. When the conditions exceed 30°C[86°F] and RH 80% in the ceiling or fresh air is inducted into the ceiling, and additional insulation is required (polyethylene foam, thickness 10mm[3/8"] or more)
3. Open type panel model code : PC4NUNMAN


Table of descriptions

1	Refrigerant gas pipe	7	Suction rim for Booster fan
2	Refrigerant liquid pipe	8	Decoration cover
3	Condensate drain	9	Drain hose
4	Power & Comm. wiring conduits	10	Fresh air intake knock out hole
5	Air discharge opening	11	Display window
6	Air suction grille	12	Infrared receiver

4 Dimensional drawing

Indoor : 360 Cassette

AC090KN4DKH/EU, AC100KN4DKH/EU, AC120KN4DKH/EU, AC140KN4DKH/EU



Note

1. Make sure the spacing between the ceiling and the cassette is no more than 10mm[3/8"].
2. When the conditions exceed 30℃[86°F] and RH 80% in the ceiling or fresh air is inducted into the ceiling, and additional insulation is required (polyethylene foam, thickness 10mm[3/8"] or more)
3. Open type panel model code : PC4NUNMAN

Table of descriptions

1	Refrigerant gas pipe	7	Suction rim for Booster fan
2	Refrigerant liquid pipe	8	Decoration cover
3	Condensate drain	9	Drain hose
4	Power & Comm. wiring conduits	10	Fresh air intake knock out hole
5	Air discharge opening	11	Display window
6	Air suction grille	12	Infrared receiver

4 Dimensional drawing

Outdoor

AC071KX4DKH/EU

Units : mm / inches






Table of descriptions

1	Refrigerant gas pipe	7	
2	Refrigerant liquid pipe	8	
3	Power & Comm. wiring conduits	9	
4		10	
5		11	
6		12	

4 Dimensional drawing

Outdoor

AC090KX4DKH/EU, AC100KX4DKH/EU, AC100KX4DNH/EU, AC120KX4DKH/EU, AC120KX4DNH/EU

Units : mm / inches




Table of descriptions

1	Refrigerant gas pipe	7	
2	Refrigerant liquid pipe	8	
3	Drain Hole	9	
4	Power & Comm. wiring conduits	10	
5		11	
6		12	

4 Dimensional drawing

Outdoor

AC140KX4DKH/EU, AC140KX4DNH/EU

Units : mm / inches





Table of descriptions

1	Refrigerant gas pipe	7	
2	Refrigerant liquid pipe	8	
3	Drain Hole	9	
4	Power & Comm. wiring conduits	10	
5		11	
6		12	


5 Electrical wiring diagram

Indoor : 360 Cassette

AC071KN4DKH/EU, AC090KN4DKH/EU, AC100KN4DKH/EU, AC120KN4DKH/EU, AC140KN4DKH/EU



AC071KX4DKH/EU




AC090KX4DKH/EU. AC100KX4DKH/EU. AC120KX4DKH/EU. AC140KX4DKH/EU



5 Electrical wiring diagram


Outdoor

AC100KX4DNH/EU, AC120KX4DNH/EU, AC140KX4DNH/EU



6 Sound pressure level

Indoor : 360 Cassette



Unit: dB(A)

Model	High	Low
AC071KN4DKH/EU (ODU : AC071KX4DKH/EU)	36	29
AC090KN4DKH/EU (ODU : AC090KX4DKH/EU)	43	33
AC100KN4DKH/EU (ODU : AC100KX4DNH/EU)	44	33
AC100KN4DKH/EU (ODU : AC100KX4DKH/EU)	44	33

Note

* Specifications may be subject to change without prior notice


1) These operation values were obtained in an anechoic room.

2) Sound pressure level will vary depending on a range of factors such as the construction of the particular room where the equipment is installed.


3) Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AC071KN4DKH/EU (ODU : AC071KX4DKH/EU)




2) AC090KN4DKH/EU (ODU : AC090KX4DKH/EU)



3) AC100KN4DKH/EU (ODU : AC100KX4DNH/EU)




4) AC100KN4DKH/EU (ODU : AC100KX4DKH/EU)



6 Sound pressure level

Indoor : 360 Cassette



Unit: dB(A)

Model	High	Low
AC120KN4DKH/EU (ODU : AC120KX4DNH/EU)	45	35
AC120KN4DKH/EU (ODU : AC120KX4DKH/EU)	45	35
AC140KN4DKH/EU (ODU : AC140KX4DNH/EU)	45	37
AC140KN4DKH/EU (ODU : AC140KX4DKH/EU)	45	37

Note

* Specifications may be subject to change without prior notice


1) These operation values were obtained in an anechoic room.

2) Sound pressure level will vary depending on a range of factors such as the construction of the particular room where the equipment is installed.


3) Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AC120KN4DKH/EU (ODU : AC120KX4DNH/EU)




2) AC120KN4DKH/EU (ODU : AC120KX4DKH/EU)



3) AC140KN4DKH/EU (ODU : AC140KX4DNH/EU)




4) AC140KN4DKH/EU (ODU : AC140KX4DKH/EU)



6 Sound pressure level

Outdoor



Unit: dB(A)	
Model	Cooling
AC071KX4DKH/EU (IDU : AC071KN4DKH/EU)	49
AC090KX4DKH/EU (IDU : AC090KN4DKH/EU)	52
AC100KX4DNH/EU (IDU : AC100KN4DKH/EU)	52
AC100KX4DKH/EU (IDU : AC100KN4DKH/EU)	52

Note

* Specifications may be subject to change without prior notice


1) These operation values were obtained in an anechoic room.

2) Sound pressure level will vary depending on a range of factors such as the construction of the particular room where the equipment is installed.


3) Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AC071KX4DKH/EU (IDU : AC071KN4DKH/EU)




2) AC090KX4DKH/EU (IDU : AC090KN4DKH/EU)



3) AC100KX4DNH/EU (IDU : AC100KN4DKH/EU)




4) AC100KX4DKH/EU (IDU : AC100KN4DKH/EU)



6 Sound pressure level

Outdoor



Unit: dB(A)

Model	Cooling
AC120KX4DNH/EU (IDU : AC120KN4DKH/EU)	54
AC120KX4DKH/EU (IDU : AC120KN4DKH/EU)	54
AC140KX4DNH/EU (IDU : AC140KN4DKH/EU)	53
AC140KX4DKH/EU (IDU : AC140KN4DKH/EU)	53

Note

* Specifications may be subject to change without prior notice


1) These operation values were obtained in an anechoic room.

2) Sound pressure level will vary depending on a range of factors such as the construction of the particular room where the equipment is installed.


3) Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AC120KX4DNH/EU (IDU : AC120KN4DKH/EU)




2) AC120KX4DKH/EU (IDU : AC120KN4DKH/EU)



3) AC140KX4DNH/EU (IDU : AC140KN4DKH/EU)



4) AC140KX4DKH/EU (IDU : AC140KN4DKH/EU)



7 Sound power level

Indoor : 360 Cassette

Note


* Specifications may be subject to change without prior notice

- 1) dBA = A-weighted sound power level.
- 2) Reference power : 1pW.
- 3) Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AC071KN4DKH/EU (ODU : AC071KX4DKH/EU)	53
AC090KN4DKH/EU (ODU : AC090KX4DKH/EU)	60
AC100KN4DKH/EU (ODU : AC100KX4DNH/EU)	61
AC100KN4DKH/EU (ODU : AC100KX4DKH/EU)	61


1) AC071KN4DKH/EU (ODU : AC071KX4DKH/EU)




2) AC090KN4DKH/EU (ODU : AC090KX4DKH/EU)



3) AC100KN4DKH/EU (ODU : AC100KX4DNH/EU)



4) AC100KN4DKH/EU (ODU : AC100KX4DKH/EU)



7 Sound power level

Indoor : 360 Cassette

Note


* Specifications may be subject to change without prior notice

- 1) dBA = A-weighted sound power level.
- 2) Reference power : 1pW.
- 3) Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AC120KN4DKH/EU (ODU : AC120KX4DNH/EU)	61
AC120KN4DKH/EU (ODU : AC120KX4DKH/EU)	61
AC140KN4DKH/EU (ODU : AC140KX4DNH/EU)	61
AC140KN4DKH/EU (ODU : AC140KX4DKH/EU)	61


1) AC120KN4DKH/EU (ODU : AC120KX4DNH/EU)




2) AC120KN4DKH/EU (ODU : AC120KX4DKH/EU)



3) AC140KN4DKH/EU (ODU : AC140KX4DNH/EU)



4) AC140KN4DKH/EU (ODU : AC140KX4DKH/EU)



7 Sound power level

Outdoor

Note


* Specifications may be subject to change without prior notice

- 1) dBA = A-weighted sound power level.
- 2) Reference power : 1pW.
- 3) Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AC071KX4DKH/EU (IDU : AC071KN4DKH/EU)	65
AC090KX4DKH/EU (IDU : AC090KN4DKH/EU)	68
AC100KX4DNH/EU (IDU : AC100KN4DKH/EU)	69
AC100KX4DKH/EU (IDU : AC100KN4DKH/EU)	69


1) AC071KX4DKH/EU (IDU : AC071KN4DKH/EU)




2) AC090KX4DKH/EU (IDU : AC090KN4DKH/EU)



3) AC100KX4DNH/EU (IDU : AC100KN4DKH/EU)



4) AC100KX4DKH/EU (IDU : AC100KN4DKH/EU)



7 Sound power level

Outdoor

Note


* Specifications may be subject to change without prior notice

- 1) dBA = A-weighted sound power level.
- 2) Reference power : 1pW.
- 3) Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AC120KX4DNH/EU (IDU : AC120KN4DKH/EU)	70
AC120KX4DKH/EU (IDU : AC120KN4DKH/EU)	70
AC140KX4DNH/EU (IDU : AC140KN4DKH/EU)	69
AC140KX4DKH/EU (IDU : AC140KN4DKH/EU)	69


1) AC120KX4DNH/EU (IDU : AC120KN4DKH/EU)




2) AC120KX4DKH/EU (IDU : AC120KN4DKH/EU)



3) AC140KX4DNH/EU (IDU : AC140KN4DKH/EU)



4) AC140KX4DKH/EU (IDU : AC140KN4DKH/EU)




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC071KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC090KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC100KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC100KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC120KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC120KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC140KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution

Discharge angle : 60°




8 Temperature and air flow distribution

Indoor : 360 Cassette

AC140KN4DKH/EU


(1) Cooling air velocity distribution

Discharge angle : 60°




(2) Cooling temperature distribution

Discharge angle : 60°




(3) Heating air velocity distribution

Discharge angle : 60°



(4) Heating temperature distribution


Discharge angle : 60°



9 Cycle diagram

Outdoor

AC071KX4DKH/EU




Category		Symbol	Description
Compressor			Rotary Inveter Compressor
Heat Exchanger			Condensing unit
			Evaporating unit
Accumulator			Accumulator
Filter			Filter
Valve	Expansion		Electronic Expansion Valve(EEV)
	Reversing		4 Way valve (Reversing valve)
	Service		Service valve
Senser	Temperature		Pip/Air Temperature sensor

9 Cycle diagram

Outdoor

AC090KX4DKH/EU




Category		Symbol	Description
Compressor			Rotary Inverter Compressor
Heat Exchanger			Condensing unit
			Evaporating unit
Accumulator			Accumulator
Filter			Filter
Valve	Expansion		Electronic Expansion Valve (EEV)
	Reversing		4 Way valve (Reversing valve)
	Service		Service valve
Sensor	Temperature		Pip/Air Temperature sensor

9 Cycle diagram

Outdoor

AC100KX4DKH/EU, AC100KX4DNH/EU, AC120KX4DKH/EU, AC120KX4DNH/EU, AC140KX4DKH/EU, AC140KX4DNH/EU



Category		Symbol	Description
Compressor			Rotary Inverter Compressor
Heat Exchanger			Condensing unit
			Evaporating unit
Accumulator			Accumulator
Filter			Filter
Valve	Expansion		Electronic Expansion Valve (EEV)
	Reversing		4 Way valve (Reversing valve)
	Service		Service valve
Sensor	Temperature		Pip/Air Temperature sensor

10 Capacity correction

Outdoor

AC071KN4DKH/EU + AC071KX4DKH/EU

Cooling



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.91	0.90	0.88	0.86
	25	-	-	-	-	0.94	0.92	0.91	0.90	0.88	0.86
	20	-	-	-	0.96	0.94	0.92	0.91	0.90	0.88	0.86
	15	-	-	0.97	0.96	0.94	0.92	0.91	0.90	0.88	0.86
	10	-	0.98	0.97	0.96	0.94	0.92	0.91	0.90	0.88	0.86
	5	1.00	0.98	0.97	0.96	0.94	0.92	0.91	0.90	0.88	0.86
	0	1.00	0.98	0.97	0.96	0.94	0.92	0.91	0.90	0.88	0.86
	-5	1.00	0.98	0.96	0.95	0.93	0.92	0.90	0.89	0.87	0.85
	-10	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.86	0.84
	-15	-	-	0.96	0.94	0.92	0.91	0.89	0.87	0.85	0.83
	-20	-	-	-	0.93	0.92	0.90	0.89	0.87	0.84	0.82
	-25	-	-	-	-	0.91	0.90	0.88	0.86	0.84	0.80
	-30	-	-	-	-	-	0.89	0.87	0.85	0.83	0.79

Heating



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.91	0.89	0.88	0.86
	25	-	-	-	-	0.94	0.92	0.91	0.89	0.88	0.86
	20	-	-	-	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	15	-	-	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	10	-	0.98	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	5	1.00	0.98	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	0	1.00	0.98	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	-5	1.00	0.98	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	-10	-	0.98	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	-15	-	-	0.97	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	-20	-	-	-	0.95	0.94	0.92	0.91	0.89	0.88	0.86
	-25	-	-	-	-	0.94	0.92	0.91	0.89	0.88	0.86
	-30	-	-	-	-	-	0.92	0.91	0.89	0.88	0.86

AC090KN4DKH/EU + AC090KX4DKH/EU

Cooling



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.90	0.88	0.87	0.85
	25	-	-	-	-	0.93	0.92	0.90	0.88	0.87	0.85
	20	-	-	-	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	15	-	-	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	10	-	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	5	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	0	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	-5	1.00	0.98	0.96	0.94	0.93	0.91	0.89	0.88	0.86	0.84
	-10	-	0.97	0.96	0.94	0.92	0.90	0.89	0.87	0.85	0.82
	-15	-	-	0.95	0.93	0.92	0.90	0.88	0.86	0.84	0.81
	-20	-	-	-	0.93	0.91	0.89	0.87	0.85	0.83	0.80
	-25	-	-	-	-	0.90	0.89	0.87	0.85	0.82	0.78
	-30	-	-	-	-	-	0.88	0.86	0.84	0.81	0.77

Heating



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87
	25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	0	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	-30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87

10 Capacity correction

Outdoor

AC100KN4DKH/EU + AC100KX4DKH/EU

Cooling



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.90	0.88	0.87	0.85
	25	-	-	-	-	0.93	0.92	0.90	0.88	0.87	0.85
	20	-	-	-	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	15	-	-	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	10	-	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	5	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	0	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	-5	1.00	0.98	0.96	0.94	0.93	0.91	0.89	0.88	0.86	0.84
	-10	-	0.97	0.96	0.94	0.92	0.90	0.89	0.87	0.85	0.82
	-15	-	-	0.95	0.93	0.92	0.90	0.88	0.86	0.84	0.81
	-20	-	-	-	0.93	0.91	0.89	0.87	0.85	0.83	0.80
	-25	-	-	-	-	0.90	0.89	0.87	0.85	0.82	0.78
	-30	-	-	-	-	-	0.88	0.86	0.84	0.81	0.77

Heating



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87
	25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	0	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	-30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87

AC100KN4DKH/EU + AC100KX4DNH/EU

Cooling



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.90	0.88	0.87	0.85
	25	-	-	-	-	0.93	0.92	0.90	0.88	0.87	0.85
	20	-	-	-	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	15	-	-	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	10	-	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	5	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	0	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	-5	1.00	0.98	0.96	0.94	0.93	0.91	0.89	0.88	0.86	0.84
	-10	-	0.97	0.96	0.94	0.92	0.90	0.89	0.87	0.85	0.82
	-15	-	-	0.95	0.93	0.92	0.90	0.88	0.86	0.84	0.81
	-20	-	-	-	0.93	0.91	0.89	0.87	0.85	0.83	0.80
	-25	-	-	-	-	0.90	0.89	0.87	0.85	0.82	0.78
	-30	-	-	-	-	-	0.88	0.86	0.84	0.81	0.77

Heating



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87
	25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	0	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	-30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87

10 Capacity correction

Outdoor

AC120KN4DKH/EU + AC120KX4DKH/EU

Cooling



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.90	0.88	0.87	0.85
	25	-	-	-	-	0.93	0.92	0.90	0.88	0.87	0.85
	20	-	-	-	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	15	-	-	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	10	-	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	5	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	0	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	-5	1.00	0.98	0.96	0.94	0.93	0.91	0.89	0.88	0.86	0.84
	-10	-	0.97	0.96	0.94	0.92	0.90	0.89	0.87	0.85	0.82
	-15	-	-	0.95	0.93	0.92	0.90	0.88	0.86	0.84	0.81
	-20	-	-	-	0.93	0.91	0.89	0.87	0.85	0.83	0.80
	-25	-	-	-	-	0.90	0.89	0.87	0.85	0.82	0.78
	-30	-	-	-	-	-	0.88	0.86	0.84	0.81	0.77

Heating



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87
	25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	0	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	-30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87

AC120KN4DKH/EU + AC120KX4DNH/EU

Cooling



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.92	0.90	0.88	0.87	0.85
	25	-	-	-	-	0.93	0.92	0.90	0.88	0.87	0.85
	20	-	-	-	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	15	-	-	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	10	-	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	5	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	0	1.00	0.98	0.97	0.95	0.93	0.92	0.90	0.88	0.87	0.85
	-5	1.00	0.98	0.96	0.94	0.93	0.91	0.89	0.88	0.86	0.84
	-10	-	0.97	0.96	0.94	0.92	0.90	0.89	0.87	0.85	0.82
	-15	-	-	0.95	0.93	0.92	0.90	0.88	0.86	0.84	0.81
	-20	-	-	-	0.93	0.91	0.89	0.87	0.85	0.83	0.80
	-25	-	-	-	-	0.90	0.89	0.87	0.85	0.82	0.78
	-30	-	-	-	-	-	0.88	0.86	0.84	0.81	0.77

Heating



		Pipe Length (m)									
		5	10	15	20	25	30	35	40	45	50
Level Difference (m)	30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87
	25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	0	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-5	1.00	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-10	-	0.99	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-15	-	-	0.97	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-20	-	-	-	0.96	0.94	0.93	0.91	0.90	0.88	0.87
	-25	-	-	-	-	0.94	0.93	0.91	0.90	0.88	0.87
	-30	-	-	-	-	-	0.93	0.91	0.90	0.88	0.87

SAMSUNG

2015.12

Samsung Electronics Co., LTD.
B2B PM / SE

Head Office (Suwon Korea) 129, Samsung-Ro, Yeongtong-Gu, Suwon City, Gyeonggi-Do, Korea 443-742

Website : www.samsung.com Email : airconditioner@samsung.com

Images and data in this book may subject to change without prior notice.

SAMSUNG